



MATERIAL SAFETY DATA SHEET

Based on Regulation (EC) No. 1907/2006 (REACH) Article 31 Annex 11

Hand Held and Gun Applied B3 Foam

1. Identification of the substance/preparation and the company/undertaking

1.1 Identification of the substance or preparation

Not applicable

1.2 Use of the substance/preparation

Polyurethane foam

1.3 Company/undertaking preparation

JCP Construction Products
Unit 07 Princess Court, Horace Rd.
Kingston, Surrey KT1 2SL
Tel +44 208 546 6545
Fax +44 208 546 6019

1.4 Telephone number for emergencies

+44 208 546 6545

2. Hazards identification

Extremely flammable
Harmful by inhalation
Irritating to eyes, respiratory system and skin
May cause sensititation by inhalation and skin contact

3. Composition/information on ingredients

Hazardous Ingredients	CAS No. EINECS No.	Conc. In %	Hazard symbol	Risks (R-phrases)
polymethylene polyphenyl isocyanate	9016-87-9 -	> 25	Xn	20-36/37/38-42/43
dimethyl ether	115-10-6 204-065-8	1 - <10	F+	12 (1)
propane	74-98-6 200-827-9	1 - <5	F+	12 (1)
isobutane	75-28-5 200-857-2	1 - 10	F+	12 (1)

4. First aid measures

4.1 Eye contact

Rinse immediately with plenty of water
Seek medical advice

4.2 Skin contact

Rinse immediately with plenty of water
If irritation persists seek medical advice

4.3 After inhalation

Remove the victim to fresh air
Seek medical advice

4.4 After ingestion

Never give water to an unconscious person
Do not induce vomiting
Seek medical advice

MATERIAL SAFETY DATA SHEET

Hand Held and Gun Applied B3 Foam

5. Fire-fighting measures

5.1 Suitable extinguishing media

Quantities of water
Polyvalent foam
BC powder
Carbon dioxide

5.2 Unsuitable extinguishing media

None

5.3 Special exposure hazards

On burning: release of toxic and corrosive gases/vapours: hydrogen cyanide
Gas/vapours spread at floor level: ignition hazard
Gas/vapour flammable with air within explosion limits
Aerosol may explode under the effect of heat

5.4 Instructions

If exposed to fire cool the closed containers by spraying with water
Dilute toxic gases with water spray
Do not move the load if exposed to heat

5.5 Special protective equipment for firefighters

Heat/fire exposure: compressed air/oxygen apparatus
Protective clothing for exposure to Chemicals

6. Accidental release measures

6.1 Personal protection/precautions

See headings 8.2/13

6.2 Environmental precautions

Use appropriate containment to avoid environmental contamination

6.3 Method of clean up

Allow product to solidify and remove by mechanical means
Remove uncured foam with acetone

7. Handling and storage

7.1 Handling

Observe very strict hygiene - avoid contact
Use spark/explosion proof appliances and lighting system
Remove contaminated clothing immediately
Clean contaminated clothing
Use only in well ventilated area

7.2 Storage

Keep out of direct sunlight
Store in a cool area
Store in a dry area
Keep away from heat sources, ignition sources, acids, bases

Storage temperature	: < 50	°C
Quantity limit	N.D.	kg
Storage life	365	days
Material for packaging	suitable :aerosol dispenser	

7.3 Specific use

See Technical Data Sheet

MATERIAL SAFETY DATA SHEET

Hand Held and Gun Applied B3 Foam

8. Exposure controls / Personal protection

8.1 Exposure limit values

POLYMETHYLENE POLYPHENYL ISOCYANATE

WEL-LTEL	: 0.02 (-NCO)	mg/m³	-	ppm
WEL-STEL	: 0.07 (-NCO)	mg/m³	-	ppm
MAK	: -	mg/m³	-	ppm
TRGS900	: -	mg/m³	-	ppm

DIMETHYL ETHER

WEL-LTEL	: 766	mg/m³	400	ppm
WEL-STEL	: 958	mg/m³	500	ppm
TRGS900	: 1900	mg/m³	1000	ppm
MAK	: 1900	mg/m³	1000	ppm
MAC-TGG 8 h	: 950	mg/m³		
MAC-TGG 15 min	: 1500	mg/m³		
MAC-Ceiling	: -	mg/m³		
VME-8 h	: 1920	mg/m³	1000	ppm
VLE-15 min	: -	mg/m³	-	ppm
GWBB-8 h	: 1920	mg/m³	1000	ppm
GWK-15 min	: -	mg/m³	-	ppm
Momentary value	: -	mg/m³	-	ppm
EC	: 1920	mg/m³	1000	ppm
EC-STEL	: -	mg/m³	-	ppm

PROPANE

TLV-TWA	: -	mg/m³	1000	ppm
TLV-STEL	: -	mg/m³	-	ppm
TLV-Ceiling	: -	mg/m³	-	ppm
TRGS 900	: 1800	mg/m³	1000	ppm
MAK	: 1800	mg/m³	1000	ppm
GWBB-8 h	: -	mg/m³	1000	ppm
GWK-15 min	: -	mg/m³	-	ppm
Momentary value	: -	mg/m³	-	ppm

ISOBUTANE

TRGS900	: 2400	mg/m³	1000	ppm
MAK	: 2400	mg/m³	1000	ppm
MAC-TGG 8 h	:	mg/m³		
MAC-TGG 15 min.	:	mg/m³		
MAC-Ceiling	:	mg/m³		

MATERIAL SAFETY DATA SHEET

Hand Held and Gun Applied B3 Foam

VME-8 h	:	mg/m³	-	ppm
VLE-15 min.	:	mg/m³	-	ppm
GWBB-8 h	:-	mg/m³	1000	ppm
GWK-15 min	:-	mg/m³	-	ppm
Momentary value	:-	mg/m³	-	ppm
EC		mg/m³	-	ppm
EC-STEL	:	mg/m³	-	ppm

8.2 Exposure controls

8.2.1 Occupational exposure controls

Measure the concentration in the air regularly
Use only in a well ventilated area

8.2.2 Environmental exposure controls

See section 6.2, 6.3, and 13

8.3 Personal protection

8.3.1 Respiratory protection

Wear gas mask with filter type A if conc. in air > exposure limit
High vapour/gas concentration: self contained respirator

8.3.2 Hand protection

Gloves

8.3.3 Eye protection

Protective goggles

8.3.4 Skin protection

Head / neck protection
Suitable protective clothing

9. Physical and chemical properties

9.1 General information

Appearance (at 20°C)	Aerosol
Odour	Characteristic
Colour	Variable in colour

9.2 Important health, safety and environmental information

pH value	N.D.	
Boiling point/boiling range	N.D.	°C
Flashpoint	Contains extremely flammable components	
Explosion limits (explosive properties)	N.D.	Vol%
Oxidising properties	N.D.	
Vapour pressure (at 20°C)	N.D.	hPa
Vapour pressure (at 50°C)	N.D.	hPa
Relative density (at 20°C)	N.D.	
Water solubility	Insoluble	
Soluble in	No data available	
Relative vapour density	N.D.	
Viscosity (at 20°C)	N.D.	Pa.s
Partition coefficient n-octanol/water	N.D.	
Evaporation rate		
ratio to butyl acetate	N.D.	
ratio to ether	N.D.	

MATERIAL SAFETY DATA SHEET

Hand Held and Gun Applied B2 Fire Rated Foam

9.3 Other information

Melting point/melting range	N.D.	°C
Auto-ignition point	N.D.	°C
Saturation concentration	N.D.	g/m ³
Specific conductivity	N.D.	pS/m

10. Stability and reactivity

10.1 Conditions to avoid/reactivity

Unstable on exposure to heat

10.2 Materials to avoid

keep away from heat sources, ignition sources, acids, bases

10.3 Hazardous decomposition products

On burning: release of toxic and corrosive gases/vapours: phosphorous oxides, hydrogen chloride, carbon monoxide, carbon dioxide.

On heating release of toxic/combustible gases/vapours (hydrogen cyanide)

May polymerize on exposure to temperature rise

May polymerize with a lot of compounds, i.e. (strong) bases and amines

Reacts violently with (some) acids/bases

11. Toxicological Information

11.1 Acute toxicity

POLYMETHYLENE POLYPHENYL ISOCYANATE

LD50 oral rat	:	>10000	mg/kg
LD50 dermal rabbit	:	>5000	mg/kg

MATERIAL SAFETY DATA SHEET

Hand Held and Gun Applied B2 Fire Rated Foam

DIMETHYL ETHER

LC50 inhalation rat : 309 mg/1/4/h
LC50 inhalation rat : 163991 ppm/4 h

PROPANE

LC50 inhalation rat : 513 mg/1/4/h
LC50 inhalation rat : 280000 ppm/4 h

ISOBUTANE

LC50 inhalation rat : > 50 mg/1/4/h

11.2 Chronic toxicity

POLYMETHYLENE POLYPHENYL ISOCYANATE

Carcinogenicity (MAK) : category 3B
Mutagenicity (MAK) : not listed
Teratogenicity (MAK) : -

IARC classification : 3

DIMETHYL ETHER

Teratogenicity (MAK) : Group D

11.3 Routes of exposure

Inhalation, eyes and skin

11.4 Acute effects/symptoms (upon over exposure)

AFTER INHALATION

Dry / sore throat
Coughing
Irritation of the respiratory tract
Irritation of the nasal mucous membrane
Runny nose

FOLLOWING SYMPTOMS MAY OCCUR LATER

Possible inflammation of the respiratory tract
Risk of lung oedema
Respiratory difficulties

AFTER SKIN CONTACT

Tingling / irritation of the skin

AFTER INGESTION

Irritation of the gastric / intestinal mucosa
Inhibition of enzyme production

AFTER EYE CONTACT

Irritation of the eye tissue
Lacrimation

11.5 Chronic effects

May cause sensititation by skin contact
May cause sensititation by inhalation
Contains substances with certain carcinogenic properties
(polymethylenepolyphenylisocyanate)

MATERIAL SAFETY DATA SHEET

Hand Held and Gun Applied B2 Fire Rated Foam

ON CONTINUOUS EXPOSURE
Body temperature rise
Tremor
Feeling of weakness
Headache
Skin/rash / inflammation
May stain the skin
Dry skin
Risk of pneumonia

12. Ecological information

12.1 Ecotoxicity

No data available

Effect on waste water purification : no data available

12.2 Mobility

Volatile organic compound (VOC) : 18%

Insoluble in water

For other physiochemical properties see section 9

12.3 Persistence and degradability

Biogredation BOD₅	:	N.D.	%ThOD
water	:	No data available	
soil	:	T_{1/2} N.D.	days

12.4 Bioaccumulative potential

log P_{cw}	:	N.D.
BCF	:	N.D.

12.5 Other adverse effects

WGK : Classification in compliance with
Verwaltungsvorschrift wassergefährdender Stoffe (VwVwS)
of 17 May 1999

Effects on the Ozone layer Not dangerous to the Ozone layer (1999 / 45 / EC)

Greenhouse effect No data available

Effect on waste water purification No data available

13. Disposal considerations

13.1 Provisions relating to waste

Waste material code (91/689/EEC, Council Decision 2001/118/ec, OJ. L47 of 16/2/2001: 08 05 01*

Hazardous waste (91/689/EEC)

13.2 Disposal methods

Specific treatment

Do not discharge into drains or the environment

13.3 Packaging

Waste material code packaging (91/689/EEC, Council Decision 2001/118/EC, O.J. L47 of 16/2/2001): 15
01 10* 9 (packaging containing or contaminated by dangerous substances)

MATERIAL SAFETY DATA SHEET

Hand Held and Gun Applied B2 Fire Rated Foam

14. Transport information

14.1 Classification of the substance in compliance with UN recommendations

UN number : 1950
CLASS : 2.1
SUB RISKS : -
PACKING : -

14.2 ADR (Transport by road)

CLASS : 2
PACKING :
CLASSIFICATION CODE : 5F
DANGER LABEL TANKS : -
DANGER LABEL PACKAGING : 2.1
PROPER SHIPPING NAME : UN1950, Aerosol

14.3 RID (Transport by rail)

CLASS : 2
PACKING :
CLASSIFICATION CODE : 5F
DANGER LABEL TANKS : -
DANGER LABEL PACKAGING : 2.1
PROPER SHIPPING NAME : UN1950, Aerosol

14.4 ADNR (Transport by inland waterway)

CLASS : 2
PACKING :
CLASSIFICATION CODE : 5F
DANGER LABEL TANKS : -
DANGER LABEL PACKAGING : 2.1

14.5 IMDG (Maritime transport)

CLASS : 2.1
SUB RISKS : -
PACKING : -
MFRAG : -
EMS : F-D, S-U
Marine pollutant : -

14.6 ICAO (Air transport)

CLASS : 2.1
SUB RISKS : -
PACKING : -
PACKING INSTRUCTIONS PASSENGER AIRCRAFT : 203/Y203
PACKING INSTRUCTIONS CARGO AIRCRAFT : 203

14.7 Special precautions in connections with transport : None

14.8 Limited quantities (LQ) :

When substances and their packaging meet the conditions established by ADR/RID/ADNR in chapter 3.4 **only** the following prescriptions shall be complied with:

Each package shall display a diamond shaped figure with the following inscription: UN 1950, or in the case of different goods with different identification numbers within a single package: the letter 'LQ'

MATERIAL SAFETY DATA SHEET

Hand Held and Gun Applied B2 Fire Rated Foam

15. Regulatory information

15.1 EU Legislation

Classification according to directives 67/548/EEC and 1999/45/EC



Contains : polymethylenepolphenylosocyanate

R20 : Harmful by inhalation
R36/37/38 : Irritating to eyes, respiratory system and skin
R42/43 : May cause sensititation by inhalation and skin contact

S23 : Do not breath spray
S36/37/39 : Wear suitable protective clothing, gloves and eye/face protection
S38 : In case of insufficient ventilation wear respiratory equipment
S45 : In case of accident or if you feel unwell, seek medical advice
(Show the label or this sheet if possible)
S51 : Use only in well ventilated area

Keep away from sources of ignition - No smoking
Keep out of reach of children
Pressurized contained. Protect from sunlight and do not expose to temperatures exceeding 50°C
Do not pierce or burn after use
Do not spray on a naked flame or any incandescent material

Contains isocyanates. See information supplied by the manufacturer.

MATERIAL SAFETY DATA SHEET

Hand Held and Gun Applied B2 Fire Rated Foam

16. Other information

The above information has been compiled from that provided by our suppliers and other sources. None of the original information relating to hazards or potential hazards has been omitted and so the absence of a particular reference merely implies either that such information has not been determined or that it is not applicable. Should amendments become necessary, these will be published in future issues. The above information is furnished without warranty of any kind. Users should consider this data only as a supplement of other information gathered by them and make independent determination of suitability and completeness of information from all sources to ensure proper use and disposal of these materials and the safety of employees and customers.

N.A. = Not Applicable
N.D. = Not Determined
***** = Internal Classification

Full text of any R-phrases referred to under heading 2:

R12 : Extremely Flammable
R20 : Harmful by inhalation
R36/37/38 : Irritating to eyes, respiratory system and skin
R42/43 : May cause sensitization by inhalation and skin contact

Exposure Limits

TLV : Threshold Limit Value - ACGIH US 2002
WEL : Workplace Exposure Standards - United Kingdom
MEL : Maximum Exposure Limits - United Kingdom
TRGS 900 : Technische regel für Gefahrstoffe 900 (Arbeitsplatzgrenzwerte) - Germany
MAK : Maximale Arbeitsplatzkonzentrationen - Germany 2001
MAC : Maximale aanvaarde concentratie - the Netherlands 2002
VME : Valeurs limites de Moyenne d'Exposition - France 1999
VLE : Valeurs limites d'Exposition à courte terme - France 1999
GWBB : Grenswaarde beroepsmatige blootstelling - Belgium 2002
GWK : Grenswaarde kortstondige blootstelling - Belgium 2002
EC : Indicative occupational exposure limit values - directive 2000/39/EC

I : Inhalation Fraction **T** : Total dust **E** : Einatembarer Aerosolanteil
R : Respirable Fraction **A** : Alveolengängiger Aerosolanteil/Alveolar dust
C : Ceiling limit

a : aerosol **r** : rook/Rauch (fume)
d : damp (vapour) **st** : stof/Staub (dust)
du : dust **ve** : vezel (fibre)
fa : fibre **va** : vapour
fi : fibre **om** : oil mist
p : poussière (dust) **part** : particles

Chronic toxicity

K : List of the carcinogenic substances and processes - The Netherlands 2002