



Countersunk • Zinc Plated and Clear Passivated • Min 5µm

New Part Number	Old Part Number	Drill Diameter mm	Anchor Length mm	Max. Fixture Thickness mm	Minimum Hole Depth mm	Head Diameter mm	Driver Type	Quantity Per Box	Ship Weight Kg Per 100	Price £ Per 100
JAB06/08050CS	JAB08050CS	6.0	50	20	40	12.5	T30 Torx	100	1.19	22.71
JAB06/08075CS	JAB08075CS	6.0	75	45	40	12.5	T30 Torx	100	1.73	28.56
JAB06/08100CS	JAB08100CS	6.0	100	55	55	12.5	T30 Torx	100	2.58	35.76
JAB06/08130CS	JAB08130CS	6.0	130	85	55	12.5	T30 Torx	100	2.94	45.97
JAB06/08150CS	JAB08150CS	6.0	150	105	55	12.5	T30 Torx	100	3.32	52.60



Hook Bolt and Eye Hook • Zinc Plated and yellow Passivated • Min 5µm

New Part Number	Old Part Number	Drill Diameter mm	Anchor Length mm	Max. Fixture Thickness mm	Minimum Hole Depth mm	Driver Type	Quantity Per Box	Ship Weight Kg Per 100	Price £ Per 100
JAB06/08050HOOK	JAB08050HOOK	6.0	90	N/A	40	12	50	2.56	111.77
JAB08/10055HOOK	JAB10055HOOK	8.0	90	N/A	45	12	50	4.96	125.48
JAB06/08050EYE	JAB08050EYE	6.0	90	N/A	40	13	50	2.80	174.23
JAB08/10055EYE	JAB10055EYE	8.0	90	N/A	45	13	50	5.50	206.44

T30 Torx Driver Bit

Part Number	Quantity	Price £ Each
T30	1	2.15

Technical Information C20/25 Concrete

Anchor Diameter mm	Drill Diameter mm	Embedment Depth mm	Fixture Clearance Hole mm	Centre Spacing mm	Edge Distance mm	Structure Thickness mm	Rec. Tensile Load KN	Rec. Shear Load KN	Rec. Tightening Torque Nm
6	5	30	7	90	45	50	1.0	3.3	15
8	6	30 (25)	10	100	50	60	1.9 (0.8)	3.6(0.8)	25 (15)
10	8	40	12	120	60	70	2.9	8.6	40
12	10	50	14	170	80	90	4.4	14.3	60
14	12	60	16	200	90	110	6.3	19.3	80
18	16	80	20	260	120	140	8.6	24.3	100

Shear loads are for loads away from a free edge

(Figures in brackets are for JAB0830 Only)