



JJP15



JJPN10



JJP15A

J-Plug • Plasterboard Fixing

Part Number	Screw Thread Diameter mm	Screw Length mm	Max. Fixture Thickness mm	Hole Depth mm	Rec. Tensile Load KN	Rec. Shear Load KN	Quantity Per Box	Ship Wt. Kg Per 100	Price £ Per 100
JJP15A	4.5	25	15	32	0.06	0.18	100	0.50	29.14
JJP30A	4.5	40	30	32	0.06	0.18	100	0.65	30.98
JJPN10	4.5	30	10	29	0.06	0.18	100	0.20	25.46
JJP15	4.5	35	15	37	0.06	0.18	100	0.50	37.49
JJP30	4.5	50	30	37	0.06	0.18	100	0.60	38.51



J-Plug Plasterboard Kit

Part Number	Description	Price £ each
JJP15ACASE	200 JJP15A Fixings C/W Screws and Screwdriver	58.50



J-Plug Plasterboard Tub

Part Number	Description	Price £ each
JJP15ATUB	500 JJP15A Fixings C/W Screws and Screwdriver	£135.00



Ankernut

A synthetic rubber sleeve with brass threaded insert suitable for use in hollow materials and occasional use in solid materials.

Part Number	Thread Diameter mm	Hole Diameter mm	Wall Thickness mm	Overall Length mm	Flange Thickness mm	Flange Diameter mm	Rec. Tightening Torque Nm	Quantity Per Box	Ship Wt. Kg Per 100	Price £ Per 100
LNN03024	3	8	2.0-15.0	24	1.0	11.0	1	50	0.17	52.10
LNN04011	4	8	0.4-2.0	13	1.0	11.0	1	50	0.19	43.07
LNN04024	4	8	2.0-15.0	25	1.0	11.0	1	50	0.30	52.07
LNN05015	5	10	0.4-4.0	14	1.0	13.0	1.8	50	0.24	45.49
LNN05025	5	10	8.0-16.0	25	1.3	14.0	1.8	50	0.36	46.97
LNN05040	5	10	20.0-30.0	40	1.3	14.0	1.8	50	0.40	52.43
LNN06015	6	13	0.4-3.0	15	1.3	16.0	4	50	0.42	57.88
LNN06025	6	13	6.0-12.0	25	1.3	16.0	4	50	0.58	64.38
LNN06035	6	13	12.0-25.0	35	1.3	16.0	4	50	0.78	65.43
LNN08025	8	16	4.0-10.0	25	5.7	22.0	8	50	1.12	101.74
LNN08050	8	18	25.0-35.0	50	1.6	20.0	8	50	1.88	122.69
LNN10055	10	20	25.0-35.0	55	1.3	22.5	10	25	2.28	142.83
LNN12075	12	24	35.0-45.0	75	1.3	27.0	15	25	4.00	233.92

Loads will vary subject to the condition of the base material



Rosett Cavity Fixing • Torx 25 Drive

Part Number	Screw Length mm	Wall Thickness mm	Max. Fixture Thickness mm	Hole Diameter mm	Rec. Tensile Load KN	Rec. Shear Load KN	Quantity Per Box	Ship Wt. Kg Per 100	Price £ Per 100
BR05055	55	9-18	15	10	0.38	0.5	25	1.17	45.24
BR05080	85	9-18	40	10	0.38	0.5	25	1.49	48.36
RR05065	65	18-30	12	10	0.7	0.85	25	1.35	46.12
RR05090	90	18-30	38	10	0.7	0.85	25	1.66	51.64
BRHOOK	-	9-18	-	10	0.2	0.35	25	1.55	76.44
RRHOOK	-	18-30	-	10	0.2	0.35	25	1.78	77.53

T25 Torx Driver Bit

T25	-	-	-	-	-	-	1	-	1.99
-----	---	---	---	---	---	---	---	---	------