

## Nylon Wall Plugs • Suitable for Solid Base Materials



Part Number	Anchor Hole Size mm	Plug Length mm	Wood Screw Gauge No mm	Wood Screw Size mm	Minimum Hole Depth mm	Rec. Tensile Load KN	Quantity Per Box	Ship Wt. Kg Per 100	Price £ Per 100
NP05	5	25	4-6	2.5-3.5	30	0.47	100	0.04	3.20
NP06	6	30	6-10	3.5-5.0	35	0.75	100	0.08	4.28
NP07	7	30	8-12	4.0-5.5	35	0.87	100	0.12	5.33
NP08	8	40	10-14	5.0-6.0	45	1.12	100	0.15	6.21
NP10	10	50	14-18	6.0-8.0	55	2.20	50	0.29	12.20
NP12	12	60	18-24	8.0-10.0	70	2.75	25	0.52	22.72
NP14	14	70	24-32	10.0-12.0	80	4.75	20	0.74	33.67

## Universal Plugs • Suitable for Hollow or Solid Base Materials



NUP06035	6	38	6-8	3.5-4.0	40	0.47	200	0.04	9.92
NUP08050	8	41	10-12	4.5-5.5	55	0.97	100	0.12	14.51
NUP10060	10	61	12-14	5.5-6.0	65	1.40	50	0.15	16.90

## Carded Plastic Plugs (Sold in Outers)



Part Number	Colour	Hole Size mm	Plug Length mm	Wood Screw Gauge mm	Wood Screw Size mm	Minimum Hole Depth mm	Quantity Per Card	Ship Wt. Kg Per 100	Price £ Per 1000
YPCARD	Yellow	5	22	No. 4-8	2.5-4	30	100	0.04	13.60
RPCARD	Red	5.5	34	No. 6-10	3.5-5	40	100	0.64	14.91
BPCARD	Brown	7	37	No. 10-14	5-6	45	100	1.12	17.33

## JCP Standard • Plastic Plugs (Sold in Outers)



AYP	Yellow	5	22	No. 4-8	2.5-4	30	100	0.40	12.86
ARP	Red	6	34	No. 6-10	3.5-5	40	100	0.64	13.60
ABP	Brown	7	37	No. 10-14	5-6	45	100	1.12	16.75

## JCP Premium • Plastic Plugs (Sold in Outers)



JCPRED	Red	6	37	No. 6-10	3.5-5	45	100	0.60	15.65
JCPBROWN	Brown	7	37	No. 10-14	5-6	45	100	1.00	17.96



A zinc plated, sprung steel sleeve suitable for use in concrete, concrete blocks, dense natural stone and solid bricks.

## SuperQuick Nails

Part Number	Anchor Hole Size mm	Anchor Length mm	Max. Fixture Thickness mm	Min. Hole Depth mm	Rec. Tensile Load KN	Rec. Shear Load KN	Quantity Per Box	Ship Wt. Kg Per 100	Price £ Per 100
SQN06030	6	30	5	35	0.55	0.55	100	0.30	10.17
SQN06040	6	40	10	40	0.55	0.55	100	0.40	11.23
SQN06050	6	50	20	40	0.55	0.55	100	0.50	12.82
SQN06060	6	60	30	40	0.55	0.55	100	0.60	14.13
SQN06080	6	80	50	40	0.55	0.55	100	0.80	16.70
SQN08070	8	70	30	50	1.1	1.1	100	1.15	20.55
SQN08090	8	90	50	50	1.1	1.1	100	1.48	22.35
SQN08110	8	110	70	50	1.1	1.1	100	1.80	27.78
SQN08130	8	130	90	50	1.1	1.1	50	2.11	38.37
SQN08150	8	150	110	50	1.1	1.1	50	2.44	48.59
SQN08180	8	180	140	50	1.1	1.1	25	2.98	68.89