


Data Sheet



Ankerbolt, Hook and Eyebolts are a hardened steel, self tapping screws for use in concrete, solid brick and hard natural stone.

HOOK BOLTS

Part No.	Outside Diam	Drill Diam	Hook Diam	Overall Length	Thread Length	Min Hole Depth
	mm	mm	mm	mm	mm	mm
JAB06/08050HOOK	8.0	6.0	13.0	90.0	50.0	40.0
JAB08/10055HOOK	10.0	8.0	13.0	90.0	55.0	45.0

EYE BOLTS

Part No.	Outside Diam	Drill Diam	Eye Diam	Overall Length	Thread Length	Min Hole Depth
	mm	mm	mm	mm	mm	mm
JAB06/08050EYE	8.0	6.0	13.0	90.0	50.0	40.0
JAB08/10055EYE	10.0	8.0	15.0	90.0	55.0	45.0

Performance Data (C20/25 Concrete)

Drill Diam	Characteristic Resistance	Design Resistance	Recommended Resistance	Spacing	Edge Distance
mm	kN	kN	kN	mm	mm
6.0	6.0	3.3	2.3	65.0	55.0
8.0	9.0	4.9	3.5	80.0	75.0

(Loads are in any direction)

JCP Hook Bolts and Eye Bolts are only to be used for static loads. They are not to be used for safety harness anchorage points, dynamic loads or as lifting eyes

SALES OFFICES

Dartford 01322 277733
 Elland 01422 370121
 Milton Keynes 01908 330050

Stone 01785 819819
 Swindon 01793 527829

