

JCP CONSTRUCTION PRODUCTS

Scaffold Ring Bolts

Data Sheet



JCP Scaffold Ring Bolts are used together with M16 Drop In Anchors or M16 Internal Threaded Sockets installed with Spin In Glass Capsules or Injection Resin

Part No.	Thread	Eye	Overall	Max
	Diam	Diam	Length	Load
	mm	mm	mm	Kg
DSRBM16	16	53	210	1270

Test Loads

Test No	Proof Load kN	Remarks
K406	25.0	After a proof Load of 25kN had been applied and released the Scaffold Ring Bolt showed no signs of deformation
K406	25.0	After a proof Load of 25kN had been applied and released the Scaffold Ring Bolt showed no signs of deformation

JCP Scaffold Ring Bolts are only to be used for scaffold restrains and loaded in tension and must be installed to ensure they are not subjected to shear loading. They are not to be used for safety harness anchorage points or as lifting eyes

SALES OFFICES							
Dartford	01322 277733	Stone	01785 819819	HEXSTONE			
Elland	01422 370121	Swindon	01793 527829				
Milton Keynes	01908 330050						
JCP Construction Products, Unit 14 Teddington Business Park, Station Rd, Teddington, Middlesex TW11 9BQ							
Tel 020 8943 1800	Fax 020 894	3 1140	Web	www.jcpfixings.co.uk			