

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name: Expanding Foam Hand Held B2 Rated (JF750B2H)**
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
Assembly foam
- **Application of the substance / the mixture** Construction chemicals
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
JCP Construction Products
Unit 14 Teddington Business Park,
Station Rd., Teddington, TW11 9BQ
Tel: +44 208 943 1800
Fax: +44 208 943 1140
Web: www.jcpfixings.co.uk
- **Further information obtainable from:** jcpenquiries@owlett-jaton.com
- **1.4 Emergency telephone number:** +44 (0)208 943 1800 8.30am-5.00pm Monday to Friday

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



GHS08 health hazard

Resp. Sens. 1	H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Carc. 2	H351	Suspected of causing cancer.
STOT RE 2	H373	May cause damage to organs through prolonged or repeated exposure.



GHS07

Acute Tox. 4	H332	Harmful if inhaled.
Skin Irrit. 2	H315	Causes skin irritation.
Eye Irrit. 2	H319	Causes serious eye irritation.
Skin Sens. 1	H317	May cause an allergic skin reaction.
STOT SE 3	H335	May cause respiratory irritation.
Lact.	H362	May cause harm to breast-fed children.
Aquatic Chronic 4	H413	May cause long lasting harmful effects to aquatic life.

· **Additional information:**
The classification of the preparation with the assignment of the phrase H413 taking into account the content of chlorinated alkanes C14-C17 was made on the basis of the study "FEICA Fact Sheet on the classification and labelling of one-component moisture curing polyurethane foams containing medium-chained chlorinated paraffins (MCCP)".

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the GB CLP regulation.

(Contd. on page 2)

Trade name: Expanding Foam Hand Held B2 Rated (JF750B2H)

(Contd. of page 1)

· **Hazard pictograms**



GHS02 GHS07 GHS08

· **Signal word** Danger

· **Hazard-determining components of labelling:**

diphenylmethanediisocyanate, isomers and homologues
chlorinated paraffins, C14-17

· **Hazard statements**

H222 Extremely flammable aerosol.
H229 Pressurised container: May burst if heated.
H332 Harmful if inhaled.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H317 May cause an allergic skin reaction.
H351 Suspected of causing cancer.
H362 May cause harm to breast-fed children.
H335 May cause respiratory irritation.
H373 May cause damage to organs through prolonged or repeated exposure.
H413 May cause long lasting harmful effects to aquatic life.

· **Precautionary statements**

P102 Keep out of reach of children.
P260 Do not breathe gas.
P263 Avoid contact during pregnancy and while nursing.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

P302+P352 IF ON SKIN: Wash with plenty of water.
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308+P313 IF exposed or concerned: Get medical advice/attention.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Additional information:**

As from 24 August 2023 adequate training is required before industrial or professional use. Further information at: www.feica.eu/PUinfo

Do not pierce or burn, even after use.

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Do not spray on an open flame or other ignition source.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Persons already sensitised to diisocyanates may develop allergic reactions when using this product.

Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product.

This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to standard EN 14387) is used.

EUH204 Contains isocyanates. May produce an allergic reaction.

· **2.3 Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:**

CAS: 85535-85-9	chlorinated paraffins, C14-17
-----------------	-------------------------------

· **vPvB:**

CAS: 85535-85-9	chlorinated paraffins, C14-17
-----------------	-------------------------------

· **Determination of endocrine-disrupting properties**

CAS: 1244733-77-4	tris(2-chlorisopropyl)-phosphate
-------------------	----------------------------------

List II

GB

(Contd. on page 3)

Trade name: Expanding Foam Hand Held B2 Rated (JF750B2H)

(Contd. of page 2)

SECTION 3: Composition/information on ingredients

• 3.2 Mixtures

• **Description:** Mixture of substances listed below with nonhazardous additions.

• Dangerous components:

CAS: 9016-87-9 EC number: 618-498-9	diphenylmethanediisocyanate, isomers and homologues ⚠ Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373; ⚠ Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335, EUH204 Specific concentration limits: Skin Irrit. 2; H315: C ≥ 5 % Eye Irrit. 2; H319: C ≥ 5 % Resp. Sens. 1; H334: C ≥ 0.1 % STOT SE 3; C ≥ 5 %	30 - 60%
CAS: 85535-85-9 EINECS: 287-477-0 Reg.nr.: 01-2119519269-33-xxxx	chlorinated paraffins, C14-17 ⚠ Aquatic Acute 1, H400 (M=100); Aquatic Chronic 1, H410 (M=10); Lact., H362, EUH066 PBT; vPvB	< 20%
CAS: 1244733-77-4 EC number: 867-935-0 Reg.nr.: 01-2119486772-26-XXXX	tris(2-chloro-1-methylethyl)phosphate ⚠ Acute Tox. 4, H302; Aquatic Chronic 3, H412	< 20%
CAS: 75-28-5 EINECS: 200-857-2 Reg.nr.: 01-2119485395-27-xxxx	isobutane ⚠ Flam. Gas 1A, H220; Press. Gas (Comp.), H280	< 15%
CAS: 74-98-6 EINECS: 200-827-9 Reg.nr.: 01-2119486944-21-xxxx	propane ⚠ Flam. Gas 1A, H220; Press. Gas (Comp.), H280	< 15%
CAS: 86675-46-9 Reg.nr.: 01-2119972940-30-xxxx	halogenated polyetherpolyol ⚠ Acute Tox. 4, H302	< 15%
CAS: 106-97-8 EINECS: 203-448-7 Reg.nr.: 01-2119474691-31-xxxx	butane, pure ⚠ Flam. Gas 1A, H220; Press. Gas (Comp.), H280	< 15%
CAS: 115-10-6 EINECS: 204-065-8 Reg.nr.: 01-2119472128-37-xxxx	dimethyl ether ⚠ Flam. Gas 1A, H220; Press. Gas (Comp.), H280	< 10%

• SVHC

CAS: 85535-85-9 | chlorinated paraffins, C14-17

• **Additional information:** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

• 4.1 Description of first aid measures

• After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

• After skin contact:

Remove uncured foam using a piece of cloth and an unaggressive solvent, e.g. ethanol. Wash your hands and the cleaned skin surface using soapy water. Cured foam can be removed mechanically with the use of a brush, soap and plenty of water. Use protective cream after skin surface has been cleaned.

• **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.

• After swallowing:

Do not induce vomiting; call for medical help immediately.
Rinse out mouth and then drink plenty of water.

• 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

• 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

GB

(Contd. on page 4)

Trade name: Expanding Foam Hand Held B2 Rated (JF750B2H)

(Contd. of page 3)

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**
 - Carbon dioxide.
 - Fire-extinguishing powder.
 - Foam.
 - Water spray.
 - Use fire extinguishing methods suitable to surrounding conditions.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet.
- **5.2 Special hazards arising from the substance or mixture**
 - Can form explosive gas-air mixtures.
 - Formation of toxic gases is possible during heating or in case of fire.
- **5.3 Advice for firefighters**
- **Protective equipment:**
 - Wear fully protective suit.
 - Wear self-contained respiratory protective device.
- **Additional information** Cool endangered receptacles with water spray.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
 - Keep away from ignition sources.
 - Wear protective clothing.
 - Do not inhale vapour/spray.
 - Ensure adequate ventilation.
- **6.2 Environmental precautions:** Do not allow to enter sewers / surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
 - Uncured foam adheres easily, hence it should be removed with caution. Remove instantly using a piece of cloth and solvents , e.g. acetone, alcohol. Remove cured foam mechanically.
 - Dispose contaminated material as waste according to section 13.
 - Ensure adequate ventilation.
- **6.4 Reference to other sections** See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
 - Open and handle receptacle with care.
 - Do not pierce or burn even after use. Use only as directed on the label.
 - Do not mix with any other chemical products.
 - Ensure good ventilation / exhaustion at the workplace.
- **Information about fire - and explosion protection:**
 - Do not spray onto a naked flame or any incandescent material.
 - Keep ignition sources away - Do not smoke.
 - Protect against electrostatic charges.
 - Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
 - This product is subject to regulations governing the storage of highly flammable aerosol products.
 - Storage rooms should be equipped with heat and smoke detectors.
 - Electrical equipment should be explosion-proof.
 - Store in a cool location.
 - Observe official regulations on storing packagings with pressurised containers.
- **Information about storage in one common storage facility:**
 - Do not store together with acids.
 - Do not store together with alkalis (caustic solutions).
 - Store away from reducing agents.
 - Store away from oxidising agents.
 - Store away from foodstuffs.
 - Store away from plastic, rubber, aluminum, light-metals.

(Contd. on page 5)

Trade name: Expanding Foam Hand Held B2 Rated (JF750B2H)

(Contd. of page 4)

- **Further information about storage conditions:**
Store receptacle in a well ventilated area.
Store in vertical position in closed original containers.
Store at temperature from +5°C to +30°C.
Protect from frost.
Store under lock and key and out of the reach of children.
Protect from heat and direct sunlight.
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

• 8.1 Control parameters

• Ingredients with limit values that require monitoring at the workplace:

CAS: 9016-87-9 diphenylmethanediisocyanate, isomers and homologues

WEL	Short-term value: 0.07 mg/m ³ Long-term value: 0.02 mg/m ³ Sen; as -NCO
-----	---

CAS: 115-10-6 dimethyl ether

WEL	Short-term value: 958 mg/m ³ , 500 ppm Long-term value: 766 mg/m ³ , 400 ppm
-----	---

CAS: 106-97-8 butane, pure

WEL	Short-term value: 1810 mg/m ³ , 750 ppm Long-term value: 1450 mg/m ³ , 600 ppm Carc (if more than 0.1% of buta-1.3-diene)
-----	---

- **Regulatory information** WEL: EH40/2020

• DNELs

CAS: 9016-87-9 diphenylmethanediisocyanate, isomers and homologues

Oral	DNEL	20 mg/kg/Tag (General population, consumers)
Dermal	DNEL	0.05 mg/kg/Tag (General population, consumers)
Inhalative	DNEL	0.05 mg/m ³ (General population, consumers) 0.05 mg/m ³ (Workers)

• PNECs

CAS: 9016-87-9 diphenylmethanediisocyanate, isomers and homologues

(freshwater)	1 mg/l
(sea water)	0.1 mg/l
(soil)	1 mg/kg

- **Additional information:** The lists valid during the making were used as basis.

• 8.2 Exposure controls

- **Appropriate engineering controls** No further data; see section 7.
- **Individual protection measures, such as personal protective equipment**

• General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Avoid contact with the eyes and skin.
Do not inhale gases / fumes / aerosols.

• Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

• Hand protection



Protective gloves

EN 374

The glove material has to be impermeable and resistant to the product / the substance / the preparation.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation.

(Contd. on page 6)

Trade name: Expanding Foam Hand Held B2 Rated (JF750B2H)

(Contd. of page 5)

- **Material of gloves**

Polyethylene gloves.

Recommended thickness of the material: ≥ 0.02 mm.

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material**

Short-term contact ≥ 10 min (EN 374)

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye/face protection**



Tightly sealed goggles

EN 166

- **Body protection:** Protective work clothing.

SECTION 9: Physical and chemical properties

- **9.1 Information on basic physical and chemical properties**

- **General Information**

- **Physical state**

Liquid

- **Colour:**

Different according to colouring

- **Odour:**

Characteristic

- **Odour threshold:**

Not determined

- **Melting point/freezing point:**

Not determined

- **Boiling point or initial boiling point and boiling range**

Not applicable, as aerosol

- **Flammability**

Extremely flammable aerosol.

- **Lower and upper explosion limit**

- **Lower:**

1.5 Vol %

- **Upper:**

11.0 Vol %

- **Flash point:**

 < 0 °C

- **Auto-ignition temperature:**

Not specified

- **Decomposition temperature:**

Not determined

- **pH**

Not applicable

- **Solubility**

- **water:**

Insoluble

Reacts with water

- **Partition coefficient n-octanol/water (log value)**

Not determined

- **Vapour pressure:**

 > 500 kPa (in the container) $< 1 \cdot 10^{-5}$ mmHg w 25°C (MDI)

- **Density and/or relative density**

- **Density at 20 °C:**

 ≤ 1.3 (PMDI) g/cm³

- **Relative density**

Not determined

- **Relative gas density**

Not determined.

- **Particle characteristics**

Void

- **9.2 Other information**

- **Appearance:**

- **Form:**

Rapidly curing foam dispensed by gaseous propellant from an aerosol container

- **Important information on protection of health and environment, and on safety.**

- **Ignition temperature:**

 $> +350$ °C (propellant)

(Contd. on page 7)

Trade name: Expanding Foam Hand Held B2 Rated (JF750B2H)

(Contd. of page 6)

- | | |
|--|---------------------------------|
| · Explosive properties: | Heating may cause an explosion. |
| · Information with regard to physical hazard classes | |
| · Explosives | Void |
| · Flammable gases | Void |
| · Aerosols | |
| Extremely flammable aerosol. | |
| Pressurised container: May burst if heated. | |
| · Oxidising gases | Void |
| · Gases under pressure | Void |
| · Flammable liquids | Void |
| · Flammable solids | Void |
| · Self-reactive substances and mixtures | Void |
| · Pyrophoric liquids | Void |
| · Pyrophoric solids | Void |
| · Self-heating substances and mixtures | Void |
| · Substances and mixtures, which emit flammable gases in contact with water | Void |
| · Oxidising liquids | Void |
| · Oxidising solids | Void |
| · Organic peroxides | Void |
| · Corrosive to metals | Void |
| · Desensitised explosives | Void |

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:**
Strongly reacts with water and other substances containing an active hydrogen atom.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity**
Harmful if inhaled.

- **LD/LC50 values relevant for classification:**

CAS: 9016-87-9 diphenylmethanediisocyanate, isomers and homologues

Oral	LD50	>10,000 mg/kg (rat) (OECD401)
Dermal	LD50	>9,400 mg/kg (rabbit) (OECD402)
Inhalative	LC50/4h	1.5 mg/l (ATE)

CAS: 85535-85-9 chlorinated paraffins, C14-17

Dermal	LD50	4,000 mg/kg (rat)
Inhalative	LC50	>3,300 mg/l (rat)

CAS: 1244733-77-4 tris(2-chloro-1-methylethyl)phosphate

Oral	LD50	632 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rat)
Inhalative	LC50	>4.6 mg/l (rat)

- **Skin corrosion/irritation**
Causes skin irritation.

(Contd. on page 8)

Trade name: Expanding Foam Hand Held B2 Rated (JF750B2H)

(Contd. of page 7)

- **Serious eye damage/irritation**
Causes serious eye irritation.
- **Respiratory or skin sensitisation**
May cause allergy or asthma symptoms or breathing difficulties if inhaled.
May cause an allergic skin reaction.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity**
Suspected of causing cancer.
- **Reproductive toxicity**
May cause harm to breast-fed children.
- **STOT-single exposure**
May cause respiratory irritation.
- **STOT-repeated exposure**
May cause damage to organs through prolonged or repeated exposure.
- **Aspiration hazard** Based on available data, the classification criteria are not met.
- **11.2 Information on other hazards**

• **Endocrine disrupting properties**

CAS: 1244733-77-4	tris(2-chlorisopropyl)-phosphate	List II
-------------------	----------------------------------	---------

SECTION 12: Ecological information

• **12.1 Toxicity**

• **Aquatic toxicity:**

CAS: 9016-87-9 diphenylmethanediisocyanate, isomers and homologues

EC50	1,640 mg/l (algae)
	>1,000 mg/l (daphnia) (OECD202)
	>100 mg/l (Sedimentation) (OECD209)
LC50	>1,000 mg/l (fish) (OECD)

- **12.2 Persistence and degradability** Not biodegradable.
- **12.3 Bioaccumulative potential** Does not accumulate in organisms.
- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**

• **PBT:**

CAS: 85535-85-9	chlorinated paraffins, C14-17
-----------------	-------------------------------

• **vPvB:**

CAS: 85535-85-9	chlorinated paraffins, C14-17
-----------------	-------------------------------

- **12.6 Endocrine disrupting properties** For information on endocrine disrupting properties see section 11.
- **12.7 Other adverse effects**

• **Additional ecological information:**

• **General notes:**

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water.

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

SECTION 13: Disposal considerations

• **13.1 Waste treatment methods**

• **Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Dispose of in a safe manner in accordance with local / national regulations.

Do not allow to enter surface or ground water.

Assigning a code from the waste catalogue depends on the sector, in which the user operates, as well as on arrangements made between the waste generator and a competent environment protection department.

• **European waste catalogue**

15 01 11*	metallic packaging containing a hazardous solid porous matrix (for example asbestos), including empty pressure containers
HP3	Flammable
HP4	Irritant - skin irritation and eye damage

(Contd. on page 9)



Trade name: Expanding Foam Hand Held B2 Rated (JF750B2H)

(Contd. of page 8)

HP5	Specific Target Organ Toxicity (STOT)/Aspiration Toxicity
HP7	Carcinogenic
HP13	Sensitising
HP14	Ecotoxic

- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

· 14.1 UN number or ID number	
· ADR, IMDG, IATA	UN1950
· 14.2 UN proper shipping name	
· ADR	1950 AEROSOLS
· IMDG, IATA	AEROSOLS
· 14.3 Transport hazard class(es)	
· ADR	
	
· Class	2 5F Gases.
· Label	2.1
· IMDG, IATA	
	
· Class	2.1 Gases.
· Label	2.1
· 14.4 Packing group	Not applicable.
· 14.5 Environmental hazards:	
· Marine pollutant:	No.
· 14.6 Special precautions for user	Warning: Gases.
· Hazard identification number (Kemler code):	-
· EMS Number:	F-D,S-U
· 14.7 Maritime transport in bulk according to IMO instruments	Not applicable.
· Transport/Additional information:	
· ADR	
· Remarks:	Exemption from ADR provisions by LQ principal (rule 3.4) - Inner packaging, max. 1 liter in capacity; outer packaging – max. gross weight of 30kg. - Inner packaging, max. 1 liter in capacity, based on common ground and covered with shrink film – max. gross weight of 20kg.
· UN "Model Regulation":	UN 1950 AEROSOLS, 2.1

GB

(Contd. on page 10)

Trade name: Expanding Foam Hand Held B2 Rated (JF750B2H)

(Contd. of page 9)

SECTION 15: Regulatory information

• 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

1907/2006/CE Regulation, UK REACH
1272/2008/CE Regulation, GB CLP
2020/878/UE Regulation

• Directive 2012/18/EU

• **Named dangerous substances - ANNEX I** None of the ingredients is listed.

• **Seveso category** P3a FLAMMABLE AEROSOLS

• **Qualifying quantity (tonnes) for the application of lower-tier requirements** 150 t

• **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t

• **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3, 56, 74

• DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

• REGULATION (EU) 2019/1148

• Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

• Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

• Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

• Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

• REGULATION (EC) No 1005/2009 on substances that deplete the ozone layer – ANNEX I (Ozone- depleting potential)

• Substances of very high concern (SVHC) according to UK REACH

CAS: 85535-85-9 | chlorinated paraffins, C14-17

• **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

• Relevant phrases

H220 Extremely flammable gas.

H280 Contains gas under pressure; may explode if heated.

H302 Harmful if swallowed.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335 May cause respiratory irritation.

H351 Suspected of causing cancer.

H362 May cause harm to breast-fed children.

H373 May cause damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

EUH204 Contains isocyanates. May produce an allergic reaction.

• Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

(Contd. on page 11)

Trade name: Expanding Foam Hand Held B2 Rated (JF750B2H)

(Contd. of page 10)

EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
DNEL: Derived No-Effect Level (UK REACH)
PNEC: Predicted No-Effect Concentration (UK REACH)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Flam. Gas 1A: Flammable gases – Category 1A
Aerosol 1: Aerosols – Category 1
Press. Gas (Comp.): Gases under pressure – Compressed gas
Acute Tox. 4: Acute toxicity – Category 4
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
Resp. Sens. 1: Respiratory sensitisation – Category 1
Skin Sens. 1: Skin sensitisation – Category 1
Carc. 2: Carcinogenicity – Category 2
Lact.: Reproductive toxicity – effects on or via lactation
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1
Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3
Aquatic Chronic 4: Hazardous to the aquatic environment - long-term aquatic hazard – Category 4

*** Data compared to the previous version altered.**

Points marked with * have changed from the previous version of the card