



JCP
CONSTRUCTION
PRODUCTS®

CATALOGUE 2025

Owlett-Jaton

www.jcpfixings.co.uk • www.owlett-jaton.com



WELCOME TO JCP

OVER 20 YEARS OF FIXING EXPERTISE

JCP Construction Products is a leading supplier of high-quality construction fixings exclusively to the distributor. Established in 2001, we have grown to be a leading force in the UK fixings market, offering unrivalled technical support. The specialist fixings division of Owlett-Jaton, JCP supplies a wide range of anchoring products for use within the construction industry.



OUR COMMITMENT TO STOCK MEANS PRODUCTS ARE AVAILABLE, COMPETITIVELY PRICED, FOR NEXT-DAY DELIVERY THROUGHOUT MOST OF THE UK MAINLAND.

Supplying fixings to suit a variety of applications, JCP products come with full technical specification and include CE and ETA certified ranges. With quality and technical support underpinning JCP's approach, continual innovation ensures our range of products meets the ever-changing demands of the industry.


Our highly trained field representatives offer on-site testing throughout the UK, to demonstrate the suitability of our products.



FREE, NEXT-DAY DELIVERY WITH LOW MINIMUM ORDER LEVELS ACROSS THE MAJORITY OF THE UK MAINLAND.


www.jcpfixings.co.uk

To provide fast and easy access to the technical data for the JCP range, we have added QR codes to each of the ranges for your convenience.



The JCP website is easy to navigate and provides the technical information required to help our customers, the distributors, to support their customers.

For end-users, technical help can be requested at the click of a button. Installers can easily download data sheets and view installation information on-site. Whilst arranging on-site support, design support, or training has never been as easy.





**PRO
Suite**


Look out
for the logo showing
which products
feature
on the Anchor
Calculation Program

The Anchor Calculation Program provides solutions for anchoring into both cracked and non-cracked concrete. The tool is designed for engineers, specifiers and architects to simplify specifying connections to surfaces such as floors, ceilings and walls, and takes into account loadings, spacing and edge distances. It includes 3D graphics, along with hole depth optimisation for chemical anchors.

Developed by our Technical Department, the JCP Anchor Specification Program also includes a rebar calculator, making it now a 'Suite' of programs. The two programs together, the ACP and Rebar calculator offer choice as to which one works best for the project being worked on.

The program can perform the structural analysis for numerous configurations of fixings for different base plate geometries. Calculations can be carried out in accordance with EN1992-4 covering the design of fasteners under static, quasi static and seismic actions, as well as fire exposure. Users have the option to choose the EOTA Guideline and Technical Report relative to the design of anchors in concrete as the design standard.

The software and database are updated regularly to ensure the program is compliant with any changes in legislation or industry standards.




The JCP Anchor Calculation Program is free to download via
www.jcpfixings.co.uk




RESIN CALCULATOR

“ Our free resin calculator helps to calculate the volume of resin required for a project based on the number of holes, anchor diameters and embedment depth. It is suitable for rebar and threaded bars. ”

THE RESIN CALCULATOR IS FREE TO DOWNLOAD VIA
www.jcpfixings.co.uk



Our sales offices are open Monday to Thursday 8.30 am to 5.30 pm and 8.30 am to 5.00 pm on Fridays.
Account-holders can order online - 24 hours a day, 7 days a week from www.owlett-jaton.com





TECHNICAL SUPPORT



ON-SITE SUPPORT

Throughout the UK we offer on-site testing of our products by our highly experienced field representatives. Whether a building regulation requirement or for peace of mind, we will provide advice on behalf of a distributor. On-site pull out tests are part of the JCP culture.

In addition, our technical support team can provide a troubleshooting technical back up when required.

“ Highly experienced, our technical support team have many years of knowledge within the industry and can be relied on to offer guidance when required. ”

BACKED BY TECHNICAL KNOW-HOW AND EXPERIENCE

Further technical information, specifications, anchor calculations etc. are also available via our technical helpline.

In-depth technical support comes as standard with JCP.

TECHNICAL DATA LIBRARY

Datasheets can be found on the JCP website for products within the range. The data sheets provide detailed information on the following; where applicable.

- ✓ Product information
- ✓ Load and range data
- ✓ Performance data
- ✓ Installation instructions
- ✓ Features
- ✓ Base material guidance
- ✓ Related products





Our technical team offer training sessions to provide a hands-on-experience with our fixings. Sessions are tailored to meet the needs of the audience enabling you to navigate through the software interface, enter project-specific data, and interpret results with practical exercises and real-world case studies.

Who Should Attend?



Construction Professionals



Civil and Structural Engineers



Architects

Courses are delivered in two versions:

BASIC TRAINING

What you'll learn:

- Introduction To JCP
- Different Anchor Types Within The JCP Range
- How To Design And Assess Fasteners
- Codes And Regulations
- Design Methods
- ACP Introduction
- Simple Example
- Anchor Selection And Calculation Report



2-3 Hours



**Online Or
In Person**



Free

ADVANCED TRAINING

What you'll learn:

- Introduction To JCP
- Anchor Types Within The JCP Range
- How To Design And Assess Fasteners
- Different Failure Modes In Concrete
- Different Failure Modes In Masonry
- Codes And Regulations
- CE Marking, EADS And ETAS
- Design Methods
- ACP Introduction
- Simple Example
- Anchor Selection And Calculation Report
- Advanced ACP Features including Custom Geometry, Lever Arm, Depth Optimisation, Load Combinations, Fire Design, Seismic Design and Reinforcement
- Result Interpretation And Design Optimisation
- Installation Practices
- Job-Site Tests Regimes For Anchors



5-6 Hours



**Online Or
In Person**



Free

THE CERTIFIED RANGE

“ The JCP range includes numerous certified products to support installers in meeting building specification requirements. ”



PROVIDING PEACE OF MIND

Look for these symbols alongside our products to easily identify which apply.



CE

Indicates the product conforms with harmonised standards within the European Economic Area.



SEISMIC

Relates to anchors which are rated for use in concrete under seismic actions. C2 is the most stringent category. To qualify as C1 and /or C2 anchors must comply with EN1992-4 or TR045.



FIRE RESISTANCE

Offers fire resistance loading.



WRAS

Approved for use in contact with potable (drinking) water.



ETA FIRE STOPPING AND SEALING

The product has been tested based on EAD 350141-00-1106 and is approved to be used individually or in combination with other components to form a linear joint or gap seal to prevent or restrict the passage of fire between elements or components or to maintain the integrity and insulation performance of fire separating elements.



ETA OPTION 1

Anchors which have been approved for use in cracked and non-cracked concrete. They can be used for safely supporting applications in area's most vulnerable to cracking.



ETA OPTION 7

Versatile anchors approved for use in non-cracked concrete. They are very versatile for concrete with a strength class over 20/25.



ETA MULTIPLE-USE

The product has been tested based on EAD 330747-00-0601 or ETAG 020 and is approved to be used for installation of fasteners for redundant non-structural systems.



ETA MASONRY


The product has been tested based on EAD 330076-00-0604 and is approved to be used for installation of metal anchors directly into different types of masonry with or without sieve sleeves.





THROUGHBOLTS

PAGE 14



ANKERBOLTS

PAGE 20



DROP IN ANCHORS

PAGE 28



HEAVY DUTY ANCHORS

PAGE 34



INJECTION RESINS

PAGE 41



NYLON FRAME FIXINGS

PAGE 90

CRACKED CONCRETE PRODUCTS

**ETA Option 1 Throughbolts
BZP & Stainless Steel**
Pages 15 & 18

**ETA Ankerbolt Option 1
BZP & Stainless Steel**
Pages 21 & 23

**ETA Drop In Anchors
BZP & Stainless Steel**
Pages 28-30

**ETA Option 1 Heavy Duty
Anchors BZP & Stainless
Steel** Pages 34-36

**Resins - Pure Epoxy,
Ultra-Bond, Vinylester**
Pages 41-43

**ETA Frame Fixings
BZP & Stainless Steel**
Pages 91

“ Our technical team are available for any questions you have ”

CONTENTS

HEAVY DUTY ANCHORS

THROUGHBOLTS AND ACCESSORIES

Throughbolts	14
Wirehangers	19
Nail In Sockets	19

ANKERBOLTS AND ACCESSORIES

Ankerbolts.....	20
Ankerbolt Drop-In	26
Masonry Screws	26
Socket Bolts.....	26
Hook and Eye Bolts	27

INTERNAL THREADED ANCHORS

Drop-In Anchors.....	28
Drop-In Anchor Setting Punches	31
Stop Drill Bits	31

HOOK AND EYE BOLTS

Forged Hook Bolts.....	32
Forged Eye Bolts	32
Scaffold Ring Bolts	33
Scaffold Retaining Eyes	33
Scaffold Eye Plugs	33

HEAVY DUTY EXPANSION ANCHORS

Heavy Duty Anchors	34
--------------------------	----

BLIND BOLTS

Blind Bolts.....	37
------------------	----

CHEMICAL ANCHORS AND ACCESSORIES

INJECTION RESINS AND GLASS CAPSULES

J-Fix Pure Epoxy Resin	41
J-Fix Ultra Bond 100 Epoxy Resin.....	41
J-Fix Vinylester Resin.....	42
J-Fix Vinylester Fast Cure Resin	42
J-Fix Epoxy Acrylate Resin.....	43
J-Fix Polyester Styrene Free Resin.....	43
J-Fix Polyester Resin.....	43
J-Fix Spin In Glass Capsules	44
J-Fix Hammer In Glass Capsules.....	44

ANCHORING CEMENTS

Rockite.....	44
Kwixset	45

THREADED STUDS AND SOCKETS

J-Fix Studs.....	45
Injection Resin Sockets	48
Internal Threaded Sockets	48

INJECTION RESIN ACCESSORIES

Injection Tools.....	49
Injection Tool Accessories	49
Nylon Sleeves	50
Wire Mesh Sleeve	50
Wire Cleaning Brushes.....	50
Blow Out Pump.....	50

CRACK STITCHING ACCESSORIES

Crack Stitch Twist Starter Kit.....	51
Pointing Gun.....	51
Stitching Bar	52
Cementitious Grout.....	52

PU FOAMS AND ACCESSORIES

Polyurethane Cleaner.....	52
B1 Fire Stop Expanding Foam	53
B3 Expanding Foam	53
Applicator Guns	53

MEDIUM DUTY ANCHORS

SLEEVE ANCHORS

Sleeve Anchors.....	54
---------------------	----

SHIELD ANCHORS

Shield Anchors.....	57
---------------------	----

CONCRETE SCREWS

Concrete Screws	61
-----------------------	----

SELF-DRILLING SCREWS

METALFIX SELF-DRILLING SCREWS

Metalfix Self-Drilling Screws	63
Metalfix Self-Drilling Screws with Washers ..	64
General Purpose Self-Drilling Screws	66
Metalfix Loose Washers	67
Pozi Pan Head Self-Drilling Screws	67



Metalfix Stitching Screws.....	68
Metalfix High-Thread Self-Drilling Screws.....	69
Metalfix Low Profile Self-Drilling Screws ..	69
Wafer Head Self-Drilling Screws	70
Metalfix Magnetic Sockets.....	70
WOODFIX SELF-DRILLING SCREWS	
Woodfix Self-Drilling Screws	71
Woodfix Gash Point Screws	72
Woodfix High-Thread Screws.....	73

FIBRE CEMENT SCREWS

Fibre Cement Screws	74
---------------------------	----

COVER CAPS

Coloured Cover Caps	75
---------------------------	----

INTERNAL THREADED SELF-DRILLING SCREWS

Vertical Hangers	76
Horizontal Hangers.....	76
Gash Point Vertical Hangers	77
Gash Point Horizontal Hangers.....	77
Setting Tool.....	77

LIGHT DUTY FIXINGS

NAIL IN ANCHORS

Nail In Anchors	79
-----------------------	----

CONSTRUCTION NAILS

Plastic Headed Nails	80
Masonry Nails.....	81

SANITARY FIXINGS

Basin Fixings	82
W.C Fixings	82

BRACKETS

Vertical Flange Clips.....	83
Angle Brackets	83

WALL SCREWS

Wall Screws.....	84
------------------	----

BIGTWIST NAILS

Bigtwist Nails	86
----------------------	----

FIXING BANDS

Fixing Bands.....	87
-------------------	----

NYLON AND CAVITY FIXINGS

NYLON HAMMER SCREWS

Nylon Hammer Screws.....	88
--------------------------	----

NYLON FRAME FIXINGS

Nylon Frame Fixings.....	90
--------------------------	----

PLUGS

Push Plugs	92
Nylon Wall Plugs	92
Plastic Plugs	93
Metal Expansion Plugs.....	94

CAVITY FIXINGS

J-Plug Plasterboard Fixings.....	95
Rosett Cavity Fixings.....	96
Ankernuts	97
Road Fixing Kit.....	97
Hollow Wall Anchors.....	98
Hollow Wall Anchor Setting Tool.....	98
Spring Toggles.....	99
Plastic Toggles.....	99

PA AND GAS

GAS NAILS

Drivefast Gas Nails.....	100
Brad Nails and Gas	102

CARTRIDGE TOOLS AND ACCESSORIES

Ceiling Hangers.....	103
PA97 Cartridge Tool Kit	103
Cartridge Strips.....	103
Shot Fired Pins.....	104
Plastic Washered Pins.....	104
Magazine Pins.....	104

DRILL BITS

DRILL BITS

SDS Drill Bits	105
SDS Drill Bit Sets.....	107
Masonry Drill Bits.....	107
Masonry Drill Bit Sets	107
HSS Drill Bits	108
Cobalt HSS Drill Bits.....	109
HSS Reduced Shank Drill Bits	109
HSS Long Shank Drill Bits.....	110
HSS Drill Bit Cases.....	110
HSS Countersink Drill Bits.....	110
Cobalt Countersink Drill Bits.....	111
Tungsten Carbide Drill Bits.....	111
Auger Drill Bits.....	112
Flat Wood Bits	112
Centre Spur Wood Bits.....	112
Torx Driver Bits	112



PRODUCT FINDER

Product	Page No.	Non-Cracked Concrete	Cracked Concrete	Stone	Dense Concrete Blocks-Solid	Solid Brickwork	Perforated Brickwork	Light Aggregate Block-Solid	Light Aggregate Block-Hollow	Aerated Concrete Blocks-Solid	Hollow Concrete Planks	Hollow Clay Pots	Plasterboard	Solid Steel	Hollow Steel Section	Timber
Throughbolts ZYP	14	●			●											
Throughbolts Option 1 BZP	15	●	●		●											
Throughbolts Option 7 BZP	16	●			●											
Throughbolts Hot Dipped Galv	17	●			●											
Throughbolts A2 Stainless Steel	17	●			●											
Throughbolts Option 1 A4 Stainless Steel	18	●	●		●											
Throughbolts Option 7 A4 Stainless Steel	18	●			●											
Wire Hangers	19	●			●											
Nail In Sockets	19	●			●											
Ankerbolts	20	●		●	●	●		●			●					
Ankerbolts Option 1 BZP	21	●	●	●	●	●		●			●					
Ankerbolts A4 Stainless Steel	25	●		●	●	●		●			●					
Drop In Anchors ZYP	28	●														
Approved Drop In Anchors BZP	28	●	●		●											
Lipped Drop In Anchors ZYP	29	●									●					
Drop In Anchors A4 Stainless Steel	29	●									●					
Approved Lipped Drop In Anchors BZP	30	●			●						●					
Lipped Drop In Anchors A4 Stainless Steel	30	●	●		●						●					
Scaffold Eye and Plugs	33	●		●	●	●		●								
Heavy Duty Anchors	34	●	●													
Blind Bolt	37													●	●	
J-Fix Epoxy Resin	41	●	●	●	●	●		●		●						
J-Fix Vinylester Resin	42	●	●	●	●	●		●		●						
J-Fix Epoxy Acrylate Resin	43	●		●	●											
J-Fix Polyester Styrene Free Resin	43			●	●	●	●	●	●	●	●	●				
J-Fix Polyester Resin	43			●	●	●	●	●	●	●	●	●				
Spin In Capsules	44	●														
Hammer In Capsules	44	●														
Rockite (Interior)	44	●			●											
Kwikset (Exterior)	45	●			●											
J-Fix Injection Resin Sleeve	50						●		●		●	●				
Crack Stitching	51					●	●	●	●	●						

Full Suitability ● More Suitable Alternative Available ●

Product	Page No.	Non-Cracked Concrete	Cracked Concrete	Stone	Dense Concrete Blocks-Solid	Solid Brickwork	Perforated Brickwork	Light Aggregate Block-Solid	Light Aggregate Block-Hollow	Aerated Concrete Blocks-Solid	Hollow Concrete Planks	Hollow Clay Pots	Plasterboard	Solid Steel	Hollow Steel Section	Timber
Sleeve Anchors	54	●		●	●	●										
Shield Anchors	57	●			●	●	●	●	●	●	●		●			
Concrete Screws	61	●		●	●	●	●									
Self Drilling Screws	63													●	●	
Gash Point Screws	72															●
Nail In Anchors	79	●			●											
Masonry Nails	81					●	●	●								
Plastic Headed Nails	80					●	●	●								
Sanitary Fixings	82	●			●	●		●								
Wall Screws	84	●			●	●	●	●	●	●	●		●			
Bigtwist Nails	86															●
Hammerscrews	88	●		●	●	●	●	●	●							
Nylon Frame Fixings	90	●		●	●	●		●	●							
Approved Frame Fixings	91	●	●	●	●	●	●	●	●	●						
Nylon Plugs	92	●		●	●	●	●	●	●	●	●					
Plastic Plugs	93	●		●	●	●	●	●	●	●	●					
Metal Plugs	94									●						
J-Pug Plasterboard Fixings	95												●			
Rosett Cavity Fixings	96											●	●			
Ankernuts	97	●					●		●			●	●			
Hollow Wall Anchors	98												●			
Spring Toggles	99												●			
Plastic Toggles	99												●			
Drivefast Nails	101															●
Powder Actuated Drive Pins	104	●			●	●								●	●	

Full Suitability ● More Suitable Alternative Available ●

www.jcpfixings.co.uk

Our sales offices are open Monday to Thursday 8.30 am to 5.30 pm and 8.30 am to 5.00 pm on Fridays.

Account-holders can order online - 24 hours a day, 7 days a week from www.owlett-jaton.com



NEW PRODUCTS FROM JCP

“Introducing new products to the range underlines our commitment to mirroring the ever-changing demands of the construction industry and, ultimately, the needs of our customers.”



ETA OPTION 1 HEXAGON FLANGE HEAD ANKERBOLTS BZP

PAGE 21

The ankerbolt is a self-tapping anchor for use in a variety of base materials, with the self-tapping action providing a positive anchorage in cracked and non-cracked concrete, brick, stone, and blocks.

- ✓ Concrete C20/25 To C50/60
- ✓ Cracked Concrete
- ✓ Non-Cracked Concrete

AVAILABLE AUGUST 2025



ETA SOCKET BOLTS BZP

PAGE 26

A self-tapping socket anchor which cuts its own thread in the base material. Suitable for use in solid concrete, hollow concrete, bricks, dense blocks and most natural stone.

- ✓ Concrete C20/25 To C50/60
- ✓ Cracked Concrete
- ✓ Non-Cracked Concrete
- ✓ Multiple-Use
- ✓ Fire Resistance Classification R120

AVAILABLE AUGUST 2025



J-FIX POLYESTER RESINS-300ML

PAGE 43

Polyester resin is a general purpose resin suitable for brickwork, most natural stone and concrete.

- ✓ ETA Option 7
- ✓ Concrete C20/25 To C50/60
- ✓ Non-Cracked Concrete
- ✓ Dry/Wet/Flooded Holes
- ✓ Expansion Free
- ✓ Close Spacing And Edge Distance



CLIPPED HEAD DRIVEFAST NAILS ONLY

PAGE 101

Polyester resin is a general purpose resin suitable for brickwork, most natural stone and concrete.

- ✓ 34° Angled Clipped Head Nails
- ✓ Includes Fuel Cell Pack
- ✓ Conform To Eurocode 5 Service Classes 1, 2, And 3



THE FULL JCP RANGE IS AVAILABLE TO
ORDER FROM WWW.OWLETT-JATON.COM



The Product Range

- ✓ Over 1,900 Products
- ✓ Technical Drawings
- ✓ Features and Benefits







THROUGHBOLTS AND ACCESSORIES

The throughbolt is the ultimate 'through fixing' with the hole diameter as the bolt diameter, ideal for bolting in place awkward fixtures without the need for marking out, removal, and repositioning.

- ☒ Fast And Secure Installation
 ☒ Three Way Expansion Sleeve
 ☒ Reaction To Fire Class A1
 ☒ Through Fixing



d_0 =Anchor Hole Size L =Anchor Length L_{th} =Thread Length h_1 =Minimum Hole Depth t_{fix} =Max Fixture Thickness



THROUGHBOLTS ZYP

- ☒ Concrete C20/25 To C50/60
 ☒ Non-Cracked Concrete



**ZINC AND
YELLOW PLATED**

Part Number	Anchor Hole Size mm d_0	Anchor Length mm L	Thread Length mm L_{th}	Minimum Hole Depth mm h_1	Max Fixture Thickness mm t_{fix}	Quantity Per Box	Price £ Per 100
TB06045	6	45	18	35	5	100	11.81
TB06055	6	55	30	35	15	100	12.52
TB06085	6	85	60	35	45	100	14.32
TB08050	8	50	20	40	5	100	15.73
TB08065	8	65	30	40	20	100	17.53
TB08080	8	80	45	40	35	50	18.68
TB08100	8	100	60	40	55	50	21.37
TB08130	8	130	90	40	85	50	25.39
TB10065	10	65	30	50	8	50	25.88
TB10075	10	75	35	50	18	50	27.65
TB10090	10	90	55	50	33	50	29.88
TB10100	10	100	60	50	43	50	31.66
TB10120	10	120	80	50	63	20	38.68
TB10150	10	150	100	50	93	20	44.48
TB10175	10	175	100	50	118	20	52.67
TB12080	12	80	35	65	5	20	42.97
TB12100	12	100	55	65	25	20	48.02
TB12120	12	120	70	65	45	20	54.32
TB12140	12	140	90	65	65	20	59.62
TB12180	12	180	100	65	105	20	78.28
TB16105	16	105	55	85	10	20	86.05
TB16125	16	125	72	85	30	20	97.21
TB16150	16	150	90	85	55	20	110.33
TB16175	16	175	115	85	80	10	131.74
TB16220	16	220	125	85	125	10	168.93
TB20130	20	130	75	100	20	10	182.44
TB20160	20	160	100	100	50	10	201.84
TB20215	20	215	115	100	105	10	253.90
TB24180	24	180	105	120	45	10	368.64
TB24260	24	260	150	120	125	5	478.96



ETA OPTION 1 THROUGH BOLTS BZP

- ☒ Concrete C20/25 To C50/60
- ☒ Cracked Concrete ☒ Non-Cracked Concrete
- ☒ Fire Resistance Loading ☒ Seismic C1 + C2



**BRIGHT ZINC
PLATED**

Part Number	Anchor Hole Size mm d_o	Anchor Length mm L	Thread Length mm L_{th}	Standard Embedment		Shallow Embedment		Quantity Per Box	Price £ Per 100
				Minimum Hole Depth mm h_1	Max Fixture Thickness mm t_{fix}	Minimum Hole Depth mm h_1	Max Fixture Thickness mm t_{fix}		
ETA08075	8	75	20	60	10	49	21	100	73.19
ETA08095	8	95	40	60	30	49	41	100	82.95
ETA08115	8	115	60	60	50	49	61	100	92.71
ETA10090	10	90	20	75	10	55	30	50	107.00
ETA10110	10	110	40	75	30	55	50	50	124.08
ETA10130	10	130	60	75	50	55	70	50	136.63
ETA12110	12	110	30	90	15	70	35	25	162.77
ETA12125	12	125	45	90	30	70	50	25	191.35
ETA12160	12	160	80	90	65	70	85	25	252.00
ETA12180	12	180	80	90	85	70	105	25	258.27
ETA16135	16	135	35	110	15	90	35	20	328.67
ETA16170	16	170	70	110	50	90	70	20	371.54
ETA16200	16	200	80	110	80	90	100	10	513.75
ETA20165	20	165	50	125	30	-	-	10	1,154.02
ETA20195	20	195	70	125	60	-	-	10	1,379.87



ETA OPTION 1 THROUGH BOLTS A4 STAINLESS STEEL

SEE PAGE 18

**A4-316
STAINLESS STEEL**










ETA OPTION 7 THROUGH BOLTS BZP

✓ Concrete C20/25 To C50/60 ✓ Non-Cracked Concrete



**BRIGHT ZINC
PLATED**

Part Number	Anchor Hole Size mm d_0	Anchor Length mm L	Thread Length mm L_{th}	Standard Embedment		Shallow Embedment		Quantity Per Box	Price £ Per 100
				Minimum Hole Depth mm h_1	Max Fixture Thickness mm t_{fx}	Minimum Hole Depth mm h_1	Max Fixture Thickness mm t_{fx}		
AWA06060	6	60	25	55	3	50*	8	100	13.14
AWA06080	6	80	45		23		28	100	15.03
AWA08050*	8	50	17	-	-	45*	3	100	16.52
AWA08065	8	65	22	-	-	50**	8	100	18.41
AWA08075	8	75	32	65	3		18	50	19.61
AWA08090	8	90	46		18		33	50	22.43
AWA08100	8	100	50		28		43	50	22.95
AWA08115	8	115	65		43		58	50	24.43
AWA08130	8	130	80		58		73	50	26.66
AWA10065*	10	65	22	-	-	55*	3	50	27.17
AWA10075	10	75	27	-	-	60	8	50	29.03
AWA10090	10	90	43	75	8		23	50	31.37
AWA10100	10	100	53		18		33	50	33.25
AWA10120	10	120	71		38		53	20	40.61
AWA10150	10	150	95		68		83	20	46.70
AWA12080*	12	80	32	-	-	60*	10	20	43.95
AWA12090	12	90	35	-	-	70	10	20	45.12
AWA12100	12	100	44	85	5		20	20	50.42
AWA12110	12	110	53		15		30	20	53.55
AWA12120	12	120	63		25		40	20	57.04
AWA12140	12	140	83		45		60	20	62.60
AWA12160	12	160	95		65		80	20	70.89
AWA12180	12	180	95		85		100	20	82.20
AWA12200	12	200	95		105		120	20	87.98
AWA16105*	16	105	40	-	-	85*	6	20	90.35
AWA16125	16	125	60	-	-	100	11	20	102.07
AWA16145	16	145	80	115	16		31	20	115.85
AWA16170	16	170	105		41		56	10	138.33
AWA16220	16	220	115		91		106	10	177.38
AWA20130	20	130	60	-	-	110	5	10	191.56
AWA20170	20	170	100	135	20		45	10	211.93
AWA20215	20	215	115		65		90	10	266.60
AWA24180	24	180	100	155	5	125	33	10	387.08
AWA24260	24	260	150		85		113	5	502.90

* Not included in ETA

** Use restricted to the anchoring of structural components which are statically indeterminate.

RETAIL BAGS

Product Part Number	Bag Part Number	Size	Quantity Per Bag	Price £ Per Bag
AWA08065	JB8100	M8 x 65	6	3.84
AWA08100	JB8103	M8 x 100	6	4.15
AWA10075	JB8106	M10 x 75	4	3.84
AWA10090	JB8109	M10 x 90	4	4.15
AWA10120	JB8112	M10 x 120	4	5.03
AWA12100	JB8115	M12 x 100	4	5.03
AWA16125	JB8118	M16 x 125	2	5.91



TRADE BAGS

Product Part Number	Bag Part Number	Size	Quantity Per Bag	Price £ Per Bag
AWA08050*	JP3042	M8 x 50	40	14.31
AWA08075	JP3043	M8 x 75	20	14.31
AWA08100	JP3044	M8 x 100	15	14.31
AWA10100	JP3045	M10 x 100	18	14.31
AWA10120	JP3046	M10 x 120	10	14.31
AWA12080	JP3047	M12 x 80	10	14.31
AWA12100	JP3048	M12 x 100	12	14.31
AWA12140	JP3051	M12 x 140	10	14.31
AWA12180	JP3054	M12 x 180	8	14.31
AWA16105	JP3055	M16 x 105	5	14.31
AWA16125	JP3056	M16 x 125	5	14.31





THROUGHBOLTS HDG

- ✓ Concrete C20/25 To C50/60
- ✓ Non-Cracked Concrete
- ✓ BS EN ISO1461:2009



**HOT DIPPED
GALVANISED**

Part Number	Anchor Hole Size mm d_0	Anchor Length mm L	Thread Length mm L_{th}	Minimum Hole Depth mm h_1	Max Fixture Thickness mm t_{fix}	Quantity Per Box	Price £ Per 100
TG08050	8	50	15	45	5*	100	30.48
TG08075	8	75	40	65	10	100	36.45
TG08095	8	95	50	65	30	100	39.83
TG08120	8	120	85	65	55	100	45.73
TG10060	10	60	20	50	10*	50	52.53
TG10070	10	70	30	50	20*	50	55.94
TG10080	10	80	40	70	10	50	58.09
TG10100	10	100	55	70	30	50	66.93
TG10125	10	125	80	70	50	50	72.91
TG12085	12	85	40	70	10*	25	90.28
TG12100	12	100	55	90	5	25	96.22
TG12115	12	115	60	90	20	25	98.30
TG12145	12	145	95	90	50	25	117.45
TG12180	12	180	110	90	85	25	135.19
TG16110	16	110	50	85	15*	20	180.52
TG16125	16	130	65	110	10	20	194.92
TG16150	16	150	90	110	30	20	209.77
TG16200	16	200	115	110	80	20	265.23
TG20170	20	170	100	130	25	10	388.99
TG20220	20	220	125	130	75	10	503.02
TG20280	20	280	150	130	135	10	771.00

* Reduced loading due to shallow embedment



THROUGHBOLTS A2 STAINLESS STEEL

- ✓ Concrete C20/25 To C50/60
- ✓ Non-Cracked Concrete
- ✓ Suitable For External Use



**A2-304
STAINLESS STEEL**

Part Number	Anchor Hole Size mm d_0	Anchor Length mm L	Thread Length mm L_{th}	Minimum Hole Depth mm h_1	Max Fixture Thickness mm t_{fix}	Quantity Per Box	Price £ Per 100
TSSA206045	6	40	20	35	5	100	51.85
TSSA206065	6	65	30	35	25	100	60.26
TSSA208050	8	50	18	40	5	100	79.14
TSSA208075	8	75	41	40	30	50	96.00
TSSA208095	8	95	60	40	50	50	108.00
TSSA208120	8	120	64	40	75	50	139.68
TSSA210060	10	60	20	50	3	50	128.07
TSSA210080	10	80	40	50	23	50	153.80
TSSA210100	10	100	59	50	43	50	172.69
TSSA210125	10	125	85	50	68	20	194.70
TSSA210150	10	150	78	50	93	20	471.61
TSSA210175	10	175	88	50	118	20	630.98
TSSA212085	12	85	40	65	10	20	206.36
TSSA212100	12	100	60	65	25	20	240.98
TSSA212115	12	115	59	65	40	20	277.19
TSSA212145	12	145	80	65	70	20	304.73
TSSA212200	12	200	85	65	125	20	623.62
TSSA216110	16	110	50	85	15	20	554.91
TSSA216125	16	125	65	85	30	20	603.78
TSSA216150	16	150	90	85	55	20	689.26
TSSA216175	16	175	83	85	80	10	904.59
TSSA220170	20	170	83	100	60	10	1,349.42
TSSA220220	20	220	115	100	110	10	1,808.89



ETA OPTION 1 THROUGH BOLTS A4 STAINLESS STEEL



- ☒ Concrete C20/25 To C50/60
 ☒ Cracked Concrete
 ☒ Non-Cracked Concrete
☒ Fire Resistance Loading
 ☒ Seismic C1 + C2
 ☒ Suitable For External Use And Marine Environments

**A4-316
STAINLESS STEEL**

Part Number	Anchor Hole Size mm d_0	Anchor Length mm L	Thread Length mm L_{th}	Standard Embedment		Shallow Embedment		Quantity Per Box	Price £ Per 100
				Minimum Hole Depth mm h_1	Max Fixture Thickness mm t_{fx}	Minimum Hole Depth mm h_1	Max Fixture Thickness mm t_{fx}		
ETA08065SS*	8	65	22	-	-	50	11	100	272.09
ETA08080SS	8	80	37	60	15	50	26	100	293.21
ETA08095SS	8	95	52	60	30	50	41	100	358.19
ETA08115SS	8	115	72	60	50	50	61	100	400.01
ETA10080SS*	10	80	32	-	-	55	20	50	386.21
ETA10100SS	10	100	52	75	20	55	40	50	433.31
ETA10130SS	10	130	82	75	50	55	70	50	646.93
ETA10180SS	10	180	132	75	100	55	120	50	1051.81
ETA12095SS*	12	95	36	-	-	70	20	25	578.29
ETA12110SS	12	110	51	90	15	70	35	25	655.86
ETA12125SS	12	125	66	90	30	70	50	25	709.87
ETA12160SS	12	160	101	90	65	70	85	25	960.85
ETA12200SS	12	200	135	90	105	70	125	25	1,191.11
ETA16115SS*	16	115	36	-	-	90	15	20	1,317.41
ETA16135SS	16	135	56	110	15	90	35	20	1,504.21
ETA16170SS	16	170	91	110	50	90	70	20	1,963.52
ETA16220SS	16	220	80	110	100	-	-	10	2,670.96
ETA20165SS	20	165	50	125	30	-	-	10	4,000.14
ETA20195SS	20	195	70	125	60	-	-	10	4,424.93
ETA20235SS	20	235	80	125	100	-	-	5	5,152.67

* Reduced loading due to shallow embedment



ETA OPTION 7 THROUGH BOLTS A4 STAINLESS STEEL



- ☒ Concrete C20/25 To C50/60
 ☒ Non-Cracked Concrete
☒ Fire Resistance Loading
 ☒ Suitable For External Use And Marine Environments

**A4-316
STAINLESS STEEL**

Part Number	Anchor Hole Size mm d_0	Anchor Length mm L	Thread Length mm L_{th}	Minimum Hole Depth mm h_1	Max Fixture Thickness mm t_{fx}	Quantity Per Box	Price £ Per 100
TSS06040	6	40	16	35	5*	100	107.18
TSS06065	6	67	30	55	10	100	132.99
TSS08050	8	50	22	45	5*	100	126.13
TSS08075	8	75	40	65	10	100	142.79
TSS08095	8	95	60	65	30	100	168.61
TSS08120	8	120	85	65	55	100	201.94
TSS10060	10	60	25	50	10*	50	191.48
TSS10080	10	85	40	70	10	50	221.21
TSS10100	10	105	60	70	30	50	255.85
TSS10125	10	125	80	70	50	50	290.49
TSS10175	10	175	80	70	100	50	426.42
TSS10215	10	215	80	70	140	25	609.08
TSS12085	12	95	50	80	14*	25	341.46
TSS12100	12	105	60	90	10	25	357.15
TSS12115	12	115	70	90	20	25	406.16
TSS12145	12	145	100	90	50	25	484.91
TSS12200	12	200	100	90	105	25	734.22
TSS16110	16	115	60	90	13*	20	839.11
TSS16125	16	130	70	110	10	20	932.89
TSS16150	16	150	90	110	30	20	974.39
TSS16175	16	180	110	110	60	20	1,174.37
TSS20170	20	180	70	130	35	10	1,875.59
TSS20220	20	240	70	130	95	10	2,858.15

* Reduced loading due to shallow embedment




WIREHANGERS ZYP

ZINC AND
YELLOW PLATED

The wirehanger is an expansion anchor for securing suspension wires.

- ✓ Non-Cracked Concrete
- ✓ Fast And Secure Installation
- ✓ Pull Down Expansion
- ✓ Hammer In Fixing



d_0 =Anchor Hole Size L =Anchor Length d_{eye} =Eye Diameter h_1 =Minimum Hole Depth

Part Number	Anchor Hole Size mm d_0	Anchor Length mm L	Eye Diameter mm d_{eye}	Minimum Hole Depth mm h_1	Rec Tensile Load kN	Quantity Per Box	Price £ Per 100
TW06055	6	60	6	40	1.5	100	14.74




NAIL IN SOCKETS BZP

A dual-thread socket for multiple use in non-structural concrete applications. Simply hammer into the base material.



BRIGHT ZINC
PLATED

- ✓ Concrete C12/15
- ✓ Concrete C20/25 To C50/60
- ✓ Cracked Concrete
- ✓ Non-Cracked Concrete
- ✓ Fast And Secure Installation
- ✓ Auto Expanding Action
- ✓ No Torque Wrench Required
- ✓ Fire Resistance Classification R120



d_0 =Anchor Hole Size L =Anchor Length h_1 =Minimum Hole Depth

Part Number	Anchor Hole Size mm d_0	Anchor Length mm L	Internal Thread Diameter M	Minimum Hole Depth mm h_1	Rec Tensile Load kN	Quantity Per Box	Price £ Per 100
NAS0625	6	25	8 & 10	30	2.14	100	116.24
NAS0630	6	30	8 & 10	35	2.81	100	123.86

JCP IS A MEMBER OF THE EUROPEAN CONSORTIUM OF ANCHOR PRODUCERS

A small group of small and medium-sized European producers, the members join forces in a 100% self-financed consortium to influence the standardisation of their products. The products include mechanical, chemical and plastic anchors, powder actuated tools and their components, concrete and wood screws and 3-D nailing plates.






ANKERBOLTS AND ACCESSORIES

The anchorbolt is a self-tapping anchor for use in a variety of base materials, with the self-tapping action providing a positive anchorage in cracked and non-cracked concrete, brick, stone, and blocks.

- ✓ Fast and Secure Installation ✓ Expansion Free ✓ Undercutting Action ✓ Through Fixing ✓ High-Performance



d_0 = Anchor Hole Size L = Anchor Length t_{fix} = Max Fixture Thickness h_1 = Minimum Hole Depth



HEXAGON FLANGE HEAD ANKERBOLTS BZP

- ✓ Concrete C20/25 To C50/60 ✓ Non-Cracked Concrete



**BRIGHT ZINC
PLATED**

Part Number	Anchor Hole Size mm d_0	Anchor Length mm L	Max Fixture Thickness mm t_{fix}	Minimum Hole Depth mm h_1	Across Flats mm A/F	Quantity Per Box	Price £ Per 100
JAB05/06050	5	50	25	35	8	100	13.58
JAB05/06075	5	75	50	35	8	100	17.61
JAB05/06100	5	100	75	35	8	100	24.40
JAB06/08030	6	30	5	35	10	100	15.28
JAB06/08050	6	50	20	40	10	100	20.28
JAB06/08075	6	75	45	40	10	100	25.96
JAB06/08100	6	100	70	40	10	100	33.11
JAB06/08130	6	130	100	40	10	100	45.77
JAB06/08150	6	150	120	40	10	100	50.38

RETAIL BAGS

Product Part Number	Bag Part Number	Size mm	Quantity Per Bag	Price £ Per Bag
JAB06/08050	JB8300	6 x 50	6	3.12
JAB06/08075	JB8303	6 x 75	6	3.63
JAB06/08100	JB8306	6 x 100	4	3.63



TRADE BAGS

Product Part Number	Bag Part Number	Size mm	Quantity Per Bag	Price £ Per Bag
JAB05/06050	JP3066	5 x 50	64	16.20
JAB06/08050	JP3069	6 x 50	30	16.20
JAB06/08075	JP3072	6 x 75	26	16.20
JAB06/08100	JP3075	6 x 100	20	16.20





ETA OPTION 1 HEXAGON FLANGE HEAD ANKERBOLTS BZP **NEW**



**BRIGHT ZINC
PLATED**

✓ Concrete C20/25 To C50/60 ✓ Cracked Concrete ✓ Non-Cracked Concrete ✓ Fire Resistance Loading

Part Number	Anchor Hole Size mm d_h	Anchor Length mm L	Max Fixture Thickness mm t_{fx}	Minimum Hole Depth mm h_1	Across Flats mm A/F	Quantity Per Box	Price £ Per 100
JAB06/08050FETA	6	50	5	50	10	100	18.95
JAB06/08075FETA	6	75	30	50	10	100	25.20
JAB06/08100FETA	6	100	55	50	10	100	32.14
JAB06/08130FETA	6	130	85	50	10	100	44.44
JAB08/10060FETA	8	60	10	60	13	100	37.66
JAB08/10080FETA	8	80	30	60	13	100	44.90
JAB08/10100FETA	8	100	50	60	13	100	56.29
JAB08/10130FETA	8	130	80	60	13	50	75.72
JAB08/10150FETA	8	150	100	60	13	50	87.94
JAB10/12060FETA	10	60	5	65	15	50	59.36
JAB10/12075FETA	10	75	20	65	15	50	69.09
JAB10/12100FETA	10	100	45	65	15	50	87.84
JAB10/12130FETA	10	130	75	65	15	25	115.89
JAB10/12150FETA	10	150	95	65	15	25	131.05
JAB12/14075FETA	12	75	10	75	16	50	116.46
JAB12/14100FETA	12	100	35	75	16	50	139.98
JAB12/14130FETA	12	130	65	75	16	25	184.94
JAB12/14150FETA	12	150	85	75	16	20	214.68
JAB12/14200FETA	12	200	135	75	16	20	271.56
JAB14/16100FETA	14	100	15	95	18	25	235.22
JAB14/16130FETA	14	130	45	95	18	20	276.66
JAB14/16150FETA	14	150	65	95	18	10	312.59
JAB14/16200FETA	14	200	115	95	18	10	395.35
JAB16/18110FETA	16	110	10	115	20	10	306.47
JAB16/18125FETA	16	125	25	115	20	10	345.32
JAB16/18150FETA	16	150	50	115	20	10	389.12
JAB16/18200FETA	16	200	100	115	20	10	497.25

AVAILABLE AUGUST 2025





ETA ANKERBOLTS A4 STAINLESS STEEL

SEE PAGE 25

**A4-316
STAINLESS STEEL**








HEXAGON HEAD ANKERBOLTS BZP

✓ Concrete C20/25 To C50/60 ✓ Non-Cracked Concrete



**BRIGHT ZINC
PLATED**

Part Number	Anchor Hole Size mm d_0	Anchor Length mm L	Max Fixture Thickness mm t_{fix}	Minimum Hole Depth mm h_1	Across Flats mm A/F	Quantity Per Box	Price £ Per 100
JAB08/10060	8	60	20	55	15	100	38.79
JAB08/10075	8	75	35	55	15	100	46.24
JAB08/10100	8	100	60	55	15	100	57.98
JAB08/10130	8	130	90	55	15	50	77.99
JAB08/10150	8	150	110	55	15	50	90.57
JAB10/12060	10	60	10	70	17	50	61.14
JAB10/12075	10	75	25	70	17	50	71.16
JAB10/12100	10	100	50	70	17	50	90.48
JAB10/12130	10	130	80	70	17	25	119.37
JAB10/12150	10	150	100	70	17	25	134.98
JAB12/14075	12	75	15	85	19	50	119.96
JAB12/14100	12	100	40	85	19	50	144.18
JAB12/14130	12	130	70	85	19	25	190.49
JAB12/14150	12	150	90	85	19	20	221.12
JAB12/14200	12	200	140	85	19	20	279.71
JAB14/16075	14	75	5	100	24	25	213.76
JAB14/16100	14	100	30	100	24	25	242.28
JAB14/16130	14	130	60	100	24	20	284.96
JAB14/16150	14	150	80	100	24	10	321.97
JAB14/16200	14	200	130	100	24	10	407.21
JAB16/18100*	16	100	20	110	27	10	315.66
JAB16/18150*	16	150	70	110	27	10	400.80
JAB16/18200*	16	200	120	110	27	10	512.16

* Mechanical Galvanised

RETAIL BAGS

Product Part Number	Bag Part Number	Size mm	Quantity Per Bag	Price £ Per Bag
JAB08/10060	JB8309	8 x 60	4	3.63
JAB08/10075	JB8312	8 x 75	4	4.15
JAB08/10100	JB8315	8 x 100	4	5.03
JAB08/10150	JB8317	8 x 150	4	5.56
JAB10/12075	JB8318	10 x 75	4	5.48
JAB10/12100	JB8321	10 x 100	4	6.37
JAB10/12150	JB8324	10 x 150	2	5.48



TRADE BAGS

Product Part Number	Bag Part Number	Size mm	Quantity Per Bag	Price £ Per Bag
JAB08/10060	JP3078	8 x 60	18	16.20
JAB08/10075	JP3081	8 x 75	14	16.20
JAB08/10100	JP3084	8 x 100	12	16.20
JAB08/10150	JP3087	8 x 150	8	16.20
JAB10/12075	JP3090	10 x 75	12	16.20
JAB10/12100	JP3093	10 x 100	8	16.20
JAB10/12130	JP3096	10 x 130	6	16.20
JAB10/12150	JP3099	10 x 150	6	16.20





ETA OPTION 1 HEXAGON HEAD ANKERBOLTS BZP



- ✓ Concrete C20/25 To C50/60
- ✓ Cracked Concrete
- ✓ Non-Cracked Concrete
- ✓ Fire Resistance Loading

BRIGHT ZINC PLATED

Part Number	Anchor Hole Size mm d_0	Anchor Length mm L	Max Fixture Thickness mm t_{fix}	Minimum Hole Depth mm h_1	Across Flats mm A/F	Quantity Per Box	Price £ Per 100
JAB08/10075ETA	8	80	5	90	15	100	59.13
JAB08/10100ETA	8	100	25	90	15	100	68.39
JAB08/10130ETA	8	130	55	90	15	50	73.85
JAB08/10150ETA	8	150	75	90	15	50	84.65
JAB10/12100ETA	10	100	15	100	17	50	106.32
JAB10/12130ETA	10	130	45	100	17	25	140.90
JAB10/12150ETA	10	150	65	100	17	25	159.60
JAB12/14100ETA	12	100	5	110	19	50	172.48
JAB12/14130ETA	12	130	35	110	19	25	227.50
JAB12/14150ETA	12	150	55	110	19	20	255.32
JAB12/14200ETA	12	200	105	110	19	20	260.38
JAB14/16130ETA	14	130	20	130	24	20	308.34
JAB14/16150ETA	14	150	50	130	24	10	346.27
JAB14/16200ETA	14	200	90	130	24	10	424.50
JAB16/18150ETA	16	150	30	145	27	10	439.21
JAB16/18200ETA	16	200	80	145	27	10	568.80



COUNTERSUNK HEAD ANKERBOLTS BZP



BRIGHT ZINC PLATED

- ✓ Concrete C20/25 To C50/60
- ✓ Non-Cracked Concrete

Part Number	Anchor Hole Size mm d_0	Anchor Length mm L	Max Fixture Thickness mm t_{fix}	Minimum Hole Depth mm h_1	Head Diameter mm	Driver Type TX	Quantity Per Box	Price £ Per 100
JAB05/06030CS	5	30	5	35	9.5	T25	100	9.01
JAB05/06050CS	5	50	20	40	9.5	T25	100	11.87
JAB05/06075CS	5	75	45	40	9.5	T25	100	16.31
JAB05/06100CS	5	100	70	40	9.5	T25	100	22.93
JAB06/08030CS	6	30	5	35	12.5	T30	100	12.33
JAB06/08050CS	6	50	20	40	12.5	T30	100	16.58
JAB06/08075CS	6	75	45	40	12.5	T30	100	22.38
JAB06/08100CS	6	100	70	40	12.5	T30	100	31.89
JAB06/08130CS	6	130	100	40	12.5	T30	100	40.93
JAB06/08150CS	6	150	120	40	12.5	T30	100	48.27
JAB08/10060CS	8	60	20	55	17.5	T45	100	38.53
JAB08/10075CS	8	75	35	55	17.5	T45	100	46.95
JAB08/10100CS	8	100	60	55	17.5	T45	100	61.18
JAB10/12060CS	10	60	10	70	21	T50	50	62.84
JAB10/12075CS	10	75	25	70	21	T50	50	76.71
JAB10/12100CS	10	100	50	70	21	T50	50	99.79

RETAIL BAGS

Product Part Number	Bag Part Number	Size mm	Quantity Per Bag	Price £ Per Bag
JAB06/08075CS	JB8327	6 x 75	6	3.63
JAB06/08100CS	JB8330	6 x 100	4	3.84





PAN HEAD ANKERBOLTS BZP

✓ Concrete C20/25 To C50/60 ✓ Non-Cracked Concrete



**BRIGHT ZINC
PLATED**

Part Number	Anchor Hole Size mm d_0	Anchor Length mm L	Max Fixture Thickness mm t_{fix}	Minimum Hole Depth mm h_1	Head Diameter mm	Driver Type TX	Quantity Per Box	Price £ Per 100
JAB05/06050PH	5	50	25	35	11	T25	100	18.35
JAB05/06075PH	5	75	50	35	11	T25	100	23.14
JAB05/06100PH	5	100	75	35	11	T25	100	27.03
JAB06/08030PH	6	30	5	35	16	T30	100	20.41
JAB06/08050PH	6	50	20	40	16	T30	100	25.96
JAB06/08075PH	6	75	45	40	16	T30	100	33.30
JAB06/08100PH	6	100	70	40	16	T30	100	42.38



HEXAGON FLANGE HEAD ANKERBOLTS GALV

✓ Concrete C20/25 To C50/60 ✓ Non-Cracked Concrete



**MECHANICAL
GALVANISED**

Part Number	Anchor Hole Size mm d_0	Anchor Length mm L	Max Fixture Thickness mm t_{fix}	Minimum Hole Depth mm h_1	Across Flats mm A/F	Quantity Per Box	Price £ Per 100
JAB06/08050G	6	50	20	40	10	100	21.21
JAB06/08075G	6	75	45	40	10	100	27.61
JAB06/08100G	6	100	70	40	10	100	34.63



HEXAGON HEAD ANKERBOLTS GALV

✓ Concrete C20/25 To C50/60 ✓ Non-Cracked Concrete



**MECHANICAL
GALVANISED**

Part Number	Anchor Hole Size mm d_0	Anchor Length mm L	Max Fixture Thickness mm t_{fix}	Minimum Hole Depth mm h_1	Across Flats mm A/F	Quantity Per Box	Price £ Per 100
JAB08/10060G	8	60	20	55	15	100	40.88
JAB08/10100G	8	100	60	55	15	100	59.87
JAB08/10150G	8	150	110	55	15	50	93.05
JAB10/12060G	10	60	10	70	17	50	64.98
JAB10/12100G	10	100	50	70	17	50	94.55
JAB10/12150G	10	150	100	70	17	25	138.84
JAB12/14100G	12	100	40	85	19	50	148.55
JAB12/14150G	12	150	90	85	19	20	223.89
JAB12/14200G	12	200	140	85	19	20	288.75



ETA HEXAGON FLANGE HEAD ANKERBOLTS A4 STAINLESS STEEL



**A4-316
STAINLESS STEEL**

- ✓ Concrete C20/25 To C50/60
- ✓ Cracked Concrete
- ✓ Non-Cracked Concrete
- ✓ Bi-Metallic
- ✓ Carbon Steel Tip With Leading Threads To Cut Into Concrete
- ✓ Fire Resistance Loading
- ✓ Suitable For External Use And Marine Environments

Part Number	Anchor Hole Size mm d_0	Anchor Length mm L	Max Fixture Thickness mm t_{fx}	Minimum Hole Depth mm h_1	Across Flats mm A/F	Quantity Per Box	Price £ Per 100
JAB06/08050SS*	6	50	5	55	10	100	179.31
JAB06/08075SS	6	75	30	55	10	100	239.22
JAB06/08100SS	6	100	55	55	10	100	287.07
JAB08/10060SS*	8	60	8	65	13	100	311.64
JAB08/10075SS	8	75	23	65	13	100	385.34
JAB08/10100SS	8	100	48	65	13	100	484.91
JAB10/12075SS*	10	75	5	80	17	50	549.14
JAB10/12100SS*	10	100	25	85	17	50	686.63
JAB10/12135SS	10	135	60	85	17	25	753.11
JAB10/12150SS*	10	150	75	85	17	25	1,037.06
JAB12/14100SS*	12	100	25	85	19	50	925.86

* Not included in ETA



ETA COUNTERSUNK ANKERBOLTS A4 STAINLESS STEEL



**A4-316
STAINLESS STEEL**

- ✓ Concrete C20/25 To C50/60
- ✓ Cracked Concrete
- ✓ Non-Cracked Concrete
- ✓ Bi-Metallic
- ✓ Carbon Steel Tip With Leading Threads To Cut Into Concrete
- ✓ Fire Resistance Loading
- ✓ Suitable For External Use And Marine Environments

Part Number	Anchor Hole Size mm d_0	Anchor Length mm L	Max Fixture Thickness mm t_{fx}	Minimum Hole Depth mm h_1	Head Diameter mm	Driver Type TX	Quantity Per Box	Price £ Per 100
JAB06/08050CSSS*	6	50	5	55	15	T40	100	191.81
JAB06/08075CSSS	6	75	20	65	15	T40	100	250.00
JAB06/08100CSSS	6	100	45	65	15	T40	100	311.64
JAB08/10050CSSS	8	50	5	55	18	T45	100	262.50
JAB08/10060CSSS	8	60	15	55	18	T45	100	276.16
JAB08/10075CSSS	8	75	20	65	18	T45	100	302.71
JAB08/10100CSSS	8	100	45	65	18	T45	100	382.97

* Not included in ETA



ETA PAN HEAD ANKERBOLTS A4 STAINLESS STEEL



**A4-316
STAINLESS STEEL**

- ✓ Concrete C20/25 To C50/60
- ✓ Cracked Concrete
- ✓ Non-Cracked Concrete
- ✓ Bi-Metallic
- ✓ Carbon Steel Tip With Leading Threads To Cut Into Concrete
- ✓ Fire Resistance Loading
- ✓ Suitable For External Use And Marine Environments

Part Number	Anchor Hole Size mm d_0	Anchor Length mm L	Max Fixture Thickness mm t_{fx}	Minimum Hole Depth mm h_1	Head Diameter mm	Driver Type TX	Quantity Per Box	Price £ Per 100
JAB06/08050PHSS	6	50	5	55	16.5	T40	100	161.90
JAB06/08075PHSS	6	75	30	55	16.5	T40	100	222.57
JAB06/08100PHSS	6	100	55	55	16.5	T40	100	270.48



BI-METAL MASONRY SCREWS A4 STAINLESS STEEL

**A4-316
STAINLESS STEEL**

A high-quality, self-tapping screw which speeds up installation time, enables thread cutting, and avoids corrosion.

- ✓ Super Fast ✓ Efficient Thread Cutting ✓ Excellent Corrosion Resistance ✓ Bi-Metallic ✓ Undercutting Action ✓ Expansion Free

Part Number	Anchor Hole Size mm d_0	Anchor Length mm L	Max Fixture Thickness mm t_{fx}	Minimum Hole Depth mm h_1	Across Flats mm A/F	Quantity Per Box	Price £ Per 100
MS63045SS	5	45	15	40	8	100	72.70
MS63057SS	5	57	27	40	8	100	90.20
MS63070SS	5	70	40	40	8	100	98.58




ANKERBOLT DROP-IN BZP

A self-tapping anchor providing a flush internal thread. Ideal for threaded rods or bolts.



**BRIGHT ZINC
PLATED**

- ✓ Undercutting Action ✓ Provides A Flush Fixing



d_0 =Anchor Hole Size L=Anchor Length h_1 =Minimum Hole Depth


Part Number	Anchor Hole Size mm d_0	Anchor Length mm L	Minimum Hole Depth mm h_1	Internal Thread Diameter M	Head Diameter mm	Driver Type	Quantity Per Box	Price £ Per 100
JABDBM10	13	32	50	10	N/A	6mm Hex	100	78.08



ANKERBOLT DROP-IN SETTING TOOL BZP

The ankerbolt drop in setting tool is designed to assist in rapid and repetitive application of drop-in anchors.

- ✓ Used With An Impact Driver



Part Number	Drive Size	Quantity Per Box	Price £ Per Each
JABDBM10ST	1/2	1	7.11

ETA SOCKET BOLTS BZP NEW

A self-tapping socket anchor which cuts its own thread in the base material. Suitable for use in solid concrete, hollow concrete, bricks, dense blocks and most natural stone.



**BRIGHT ZINC
PLATED**

- ✓ Concrete C20/25 To C50/60 ✓ Cracked Concrete ✓ Non-Cracked Concrete ✓ Fire Resistance Classification R120

Part Number	Anchor Hole Size mm d_0	Anchor Length mm L	Minimum Hole Depth mm h_1	Across Flats mm A/F	Quantity Per Box	Price £ Per 100
JAB06/08035M10	6	35	45	13	100	44.25
JAB06/08055M10	6	55	65	13	100	47.50

AVAILABLE AUGUST 2025




SOCKET BOLTS BZP

- ✓ Concrete C20/25 To C50/60 ✓ Fire Resistance Classification R120



**BRIGHT ZINC
PLATED**



d_0 = Anchor Hole Size L = Anchor Length h_1 = Minimum Hole Depth

Part Number	Anchor Hole Size mm d_0	Anchor Length mm L	Minimum Hole Depth mm h_1	Internal Thread Diameter M	Across Flats mm A/F	Quantity Per Box	Price £ Per 100
JAB06/08SOCKET	6	75	50	8 & 10	17	50	125.93
JAB06/08SOCM08	6	55	50	8	13	100	48.23
JAB06/08SOCM10	6	55	50	10	13	100	46.24




ETA DUAL THREADED SOCKET BOLTS BZP

- ✓ Concrete C20/25 To C50/60 ✓ Cracked Concrete ✓ Non-Cracked Concrete
✓ ETAG 001-6 ✓ Fire Resistance Classification R120



**BRIGHT ZINC
PLATED**



d_0 = Anchor Hole Size L = Anchor Length h_1 = Minimum Hole Depth


Part Number	Anchor Hole Size mm d_0	Anchor Length mm L	Minimum Hole Depth mm h_1	Internal Thread Diameter M	Across Flats mm A/F	Quantity Per Box	Price £ Per 100
JAB06/08SOCETA	6	85	65	8 & 10	13	100	127.96



HOOK BOLTS AND EYE BOLTS BZP

- ✓ Fast And Secure Installation ✓ Expansion Free

**BRIGHT ZINC
PLATED**



d_0 = Anchor Hole Size L = Anchor Length h_1 = Minimum Hole Depth

Part Number	Anchor Hole Size mm d_0	Thread Length mm	Anchor Length mm L	Minimum Hole Depth mm h_1	Eye Diameter mm	Quantity Per Box	Price £ Per 100
JAB06/08050HOOK	6	50	90	65	13	50	77.02
JAB08/10055HOOK	8	55	100	70	14	50	107.28
JAB06/08050EYE	6	50	90	65	13	50	89.36
JAB08/10055EYE	8	55	100	70	14	50	139.09

RETAIL BAGS

Product Part Number	Bag Part Number	Size mm	Quantity Per Bag	Price £ Per Bag
JAB06/08050HOOK	JB8332	6 x 50 (90mm overall)	2	4.15
JAB06/08050EYE	JB8333	6 x 50 (90mm overall)	2	4.15







INTERNAL THREADED ANCHORS

A deformation-controlled internally threaded socket anchor suitable for multiple use. The anchor can be accurately set independent of the hole depth, preventing the anchor from being inserted too far. The internal thread is suitable for bolts or threaded studs.

- ✓ Fast And Secure Installation
- ✓ Deformation-Controlled Expansion
- ✓ Reaction To Fire Class A1
- ✓ Permanent Socket Allows For Removal And Replacement Of The Fixture



M=Internal Thread Diameter d_0 =Anchor Hole Size L=Anchor Length h_1 =Minimum Hole Depth L_{th} =Internal Thread Length



DROP-IN ANCHORS ZYP



ZINC AND
YELLOW PLATED

- ✓ Concrete C20/25 To C50/60
- ✓ Non-Cracked Concrete

Part Number	Internal Thread Diameter M	Anchor Hole Size mm d_0	Anchor Length mm L	Minimum Hole Depth mm h_1	Internal Thread Length mm L_{th}	Quantity Per Box	Price £ Per 100
DBM06	6	8	25	25	10	100	4.92
DBM08	8	10	30	30	14	100	7.95
DBM10	10	12	40	40	15	50	15.01
DBM12	12	15	50	50	20	50	34.65
DBM16	16	20	65	65	22	25	65.49
DBM20	20	25	80	80	30	25	169.34



ETA DROP-IN ANCHORS BZP



- ✓ Solid Cracked Concrete C20/25 To C50/60
- ✓ Solid Non-Cracked Concrete C20/25 To C50/60
- ✓ Fire Resistance Loading
- ✓ Manufactured In Europe

BRIGHT ZINC
PLATED

Part Number	Internal Thread Diameter M	Anchor Hole Size mm d_0	Anchor Length mm L	Minimum Hole Depth mm h_1	Internal Thread Length mm L_{th}	Quantity Per Box	Price £ Per 100
ADB08	8	10	30	30	13	100	28.14
ADB10	10	12	40	40	15	50	46.56
ADB12	12	15	50	50	18	50	73.02
ADB16	16	20	65	65	23	25	151.39



ETA MULTIPLE-USE DROP-IN ANCHORS BZP



- ✓ Solid Cracked Concrete C20/25 To C50/60
- ✓ Solid Non-Cracked Concrete C20/25 To C50/60
- ✓ Fire Resistance Loading
- ✓ Cost-Effective Solution

BRIGHT ZINC PLATED

Part Number	Internal Thread Diameter M	Anchor Hole Size mm d_0	Anchor Length mm L	Minimum Hole Depth mm h_1	Internal Thread Length mm L_{th}	Quantity Per Box	Price £ Per 100
DBM0830	8	10	30	30	13	100	13.50
DBM1040	10	12	40	40	19	50	20.77
DBM1250	12	16	50	50	22	50	42.25



ETA DROP-IN ANCHORS A4 STAINLESS STEEL



- ✓ Solid Cracked Concrete C20/25 To C50/60
- ✓ Solid Non-Cracked Concrete C20/25 To C50/60
- ✓ Fire Resistance Loading
- ✓ Suitable For External Use And Marine Environments
- ✓ Manufactured In Europe

A4-316 STAINLESS STEEL

Part Number	Internal Thread Diameter M	Anchor Hole Size mm d_0	Anchor Length mm L	Minimum Hole Depth mm h_1	Internal Thread Length mm L_{th}	Quantity Per Box	Price £ Per 100
DSSM06	6	8	30	30	11	100	123.72
DSSM08	8	10	30	30	13	100	153.24
DSSM10	10	12	40	40	15	50	270.05
DSSM12	12	15	50	50	19	50	503.67
DSSM16	16	20	65	65	25	25	959.93



LIPPED DROP-IN ANCHORS ZYP



ZINC AND YELLOW PLATED

- ✓ Concrete C20/25 To C50/60
- ✓ Non-Cracked Concrete

Part Number	Internal Thread Diameter M	Anchor Hole Size mm d_0	Anchor Length mm L	Minimum Hole Depth mm h_1	Internal Thread Length mm L_{th}	Quantity Per Box	Price £ Per 100
DBM06SH	6	8	25	25	10	100	9.03
DBM08SH	8	10	30	30	14	100	13.95
DBM10SH	10	12	30	30	15	50	19.25
DBM10SHL	10	12	40	40	15	50	23.15
DBM12SH	12	15	50	50	20	50	46.90
DBM16SH	16	20	65	65	22	25	62.98



ETA LIPPED DROP-IN ANCHORS BZP



- ✓ Concrete C20/25 To C50/60
- ✓ Cracked Concrete
- ✓ Non-Cracked Concrete
- ✓ Solid Concrete C12/15 To C50/60
- ✓ Fire Resistance Loading
- ✓ Manufactured In Europe
- ✓ Hollow Concrete Planks

**BRIGHT ZINC
PLATED**

Part Number	Internal Thread Diameter M	Anchor Hole Size mm d_0	Anchor Length mm L	Minimum Hole Depth mm h_1	Internal Thread Length mm L_{th}	Quantity Per Box	Price £ Per 100
ADBM0825SH	8	10	25	25	12	100	25.02
ADBM0830SH	8	10	30	35	13	100	25.32
ADBM1025SH	10	12	25	25	12	50	31.05
ADBM1030SH	10	12	30	30	13	50	33.80
ADBM1040SH	10	12	40	40	15	50	41.90
ADBM1225SH	12	15	25	25	12	50	54.26
ADBM1250SH	12	15	50	50	18	50	65.72



ETA LIPPED MULTIPLE-USE DROP-IN ANCHORS BZP **NEW LINES ADDED**



- ✓ Concrete C20/25 To C50/60
- ✓ Cracked Concrete
- ✓ Non-Cracked Concrete
- ✓ Solid Concrete C12/15 To C50/60
- ✓ Fire Resistance Loading
- ✓ Cost-Effective Solution

**BRIGHT ZINC
PLATED**

Part Number	Internal Thread Diameter M	Anchor Hole Size mm d_0	Anchor Length mm L	Minimum Hole Depth mm h_1	Internal Thread Length mm L_{th}	Quantity Per Box	Price £ Per 100
DBM0825SH*	8	10	25	25	10	100	15.10
DBM0830SH	8	10	30	30	13	100	15.34
DBM1025SH*	10	12	25	25	10	50	20.85
DBM1030SH	10	12	30	30	13	50	21.17
DBM1040SH	10	12	40	40	19	50	25.46
DBM1250SH	12	16	50	50	22	50	51.59



ETA LIPPED DROP IN ANCHORS A4 STAINLESS STEEL



- ✓ Concrete C20/25 To C50/60
- ✓ Cracked Concrete
- ✓ Non-Cracked Concrete
- ✓ Solid Concrete C12/15 To C50/60
- ✓ Fire Resistance Loading
- ✓ Suitable For External Use And Marine Environments
- ✓ Manufactured In Europe

**A4-316
STAINLESS STEEL**

Part Number	Internal Thread Diameter M	Anchor Hole Size mm d_0	Anchor Length mm L	Minimum Hole Depth mm h_1	Internal Thread Length mm L_{th}	Quantity Per Box	Price £ Per 100
ADSSM08SH	8	10	30	30	13	100	177.07
ADSSM10SH	10	12	40	40	15	50	311.55
ADSSM12SH	12	15	50	50	18	50	581.64

* Not Included In ETA


**BRIGHT ZINC
PLATED**


ETA DROP-IN ANCHOR SETTING PUNCHES BZP

The setting tool is designed to assist in rapid and repetitive application of drop in anchors into the substrate.

- ✓ Safely Install ETA Approved Drop In Anchors ✓ Used With A Hammer

Part Number	Quantity Per Box	Price £ Per Each
ESM0825	1	17.00
ESM0830	1	17.00
ESM1025	1	17.60
ESM1030	1	17.60
ESM1040	1	17.60
ESM1225	1	30.00
ESM1250	1	30.00



With Hand Guard

DROP IN ANCHOR SETTING PUNCHES BZP

- ✓ Safely Install Drop In Anchors ✓ Used With A Hammer

Part Number	Quantity Per Box	Price £ Per Each
DZSP06	1	2.35
DZSP08	1	3.30
DZSP10	1	4.70
DZSP12	1	5.00
DZSP16*	1	5.50
DZSP20*	1	6.00

* Without hand guard



Without Hand Guard



STOP DRILL BITS

For drilling the correct hole depth for 25mm and 30mm drop in anchors, reducing the risk of hitting rebar.

- ✓ Collar To Ensure Correct Depth

Part Number	Diameter mm	Working Length mm	Overall Length mm	Quantity Per Box	Price £ Per Each
SD10025	10	25	110	1	2.96
SD10030	10	30	110	1	2.96
SD12025	12	25	110	1	3.25
SD12030	12	30	110	1	3.25



HOOK AND EYE BOLTS


Hook and eye bolts can be used with a variety of internal threaded fixings for static loads. Scaffold ring bolts, retaining eyes and eye plugs are used as part of scaffold restraint system.



FORGED HOOK BOLTS BZP

**BRIGHT ZINC
PLATED**

✓ Forging Process Helps Prevent Hook Opening Out When Load Is Applied



M=Thread Diameter L_{th} =Thread Length


Part Number	Thread Diameter M	Thread Length mm L_{th}	Hook Diameter mm	Outside Hook Diameter mm	Quantity Per Box	Price £ Per 100
FHM06	6	50	8	22	50	56.77
FHM08	8	60	10	30	50	85.83
FHM10	10	73	12	36	25	152.37
FHM12	12	90	16	47	10	258.94



FORGED EYE BOLTS BZP

**BRIGHT ZINC
PLATED**

✓ Forging Process Helps Offer Strength When Load Is Applied



M=Thread Diameter L_{th} =Thread Length

Part Number	Thread Diameter M	Thread Length mm L_{th}	Eye Diameter mm	Outside Eye Diameter mm	Quantity Per Box	Price £ Per 100
FEM06	6	50	10	19	50	77.52
FEM08	8	60	11	23	50	107.36
FEM10	10	73	14	28	25	164.19
FEM12	12	90	16	34	10	279.01




SCAFFOLD RING BOLTS HDG

HOT DIPPED
GALVANISED

Used together with M16 drop in anchors or M16 internal threaded sockets for restraining scaffolding.

✓ Tested To Excess Of 1275kgs



M=Thread Diameter


Part Number	Thread Diameter M	Thread Length mm	Eye Diameter mm	Overall Length mm	Quantity Per Box	Price £ Per Each
DSRBM16	16	34.5	51	210	1	5.38



SCAFFOLD RETAINING EYES BZP

BRIGHT ZINC
PLATED

✓ Can Be Used In Concrete, Masonry And Natural Stone ✓ Reusable




L= Shank and Thread Length

Part Number	Thread Diameter mm	Thread Length mm	Eye Diameter mm	Shank and Thread Length mm L	Quantity Per Box	Price £ Per 100
SRE12120	12	60	23	120	20	185.19
SRE12160	12	60	23	160	10	222.22



NYLON SCAFFOLD EYE PLUGS

✓ Can Be Used In Concrete, Masonry And Natural Stone



d_0 = Anchor Hole Size L = Overall Length h_1 = Minimum Hole Depth


Part Number	Anchor Hole Size mm d_0	Overall Length mm L	Minimum Hole Depth mm h_1	Quantity Per Box	Price £ Per 100
SRP14100	14	100	110	20	16.67



HEAVY DUTY EXPANSION ANCHORS

A high-performance heavy-duty torque-controlled anchor with a three part expansion sleeve allowing for smaller spacings and edge distances.

- ✓ Fast And Secure Installation
- ✓ Three Way Expansion Sleeve
- ✓ Reaction To Fire Class A1
- ✓ High-Performance
- ✓ Through Fixing



d_0 =Anchor Hole Size M =Thread Diameter L =Anchor Length t_{fix} =Maximum Fixture Thickness h_1 =Minimum Hole Depth



ETA OPTION 1 HEXAGON BOLT HEAVY DUTY ANCHORS BZP



- ✓ Concrete C20/25 To C50/60
- ✓ Cracked Concrete
- ✓ Non-Cracked Concrete
- ✓ Fire Resistance Loading
- ✓ Seismic C1 + C2

**BRIGHT ZINC
PLATED**

Part Number	Anchor Hole Size mm d_0	Thread Diameter M	Anchor Length mm L	Max Fixture Thickness mm t_{fix}	Minimum Hole Depth mm h_1	Quantity Per Box	Price £ Per 100
JHD0610	10	6	75	10	65	50	133.46
JHD0630	10	6	95	30	65	50	144.22
JHD0650	10	6	115	50	65	50	152.22
JHD0810	12	8	85	10	80	50	167.90
JHD0830	12	8	105	30	80	50	189.42
JHD0850	12	8	125	50	80	25	203.26
JHD1015	15	10	106	15	95	25	243.55
JHD1025	15	10	116	25	95	25	257.38
JHD1045	15	10	136	45	95	25	299.20
JHD1210	18	12	117	10	105	20	373.62
JHD1220	18	12	127	20	105	20	433.89
JHD1240	18	12	147	40	105	20	456.34
JHD1270	18	12	177	70	105	20	514.77
JHD1610	24	16	130	10	130	10	778.61
JHD1620	24	16	150	20	130	10	780.15
JHD1650	24	16	180	50	130	10	903.76
JHD2030	28	20	192	30	160	5	1,467.42
JHD2060	28	20	222	60	160	5	1,734.03
JHD2460	32	24	262	60	180	5	4,397.35



ETA OPTION 1 STUD AND NUT HEAVY DUTY ANCHORS BZP



- ☒ Concrete C20/25 To C50/60
 ☒ Cracked Concrete
 ☒ Non-Cracked Concrete
☒ Fire Resistance Loading
 ☒ Seismic C1 + C2

BRIGHT ZINC PLATED

Part Number	Anchor Hole Size mm d_0	Thread Diameter M	Anchor Length mm L	Max Fixture Thickness mm t_{fx}	Minimum Hole Depth mm h_1	Quantity Per Box	Price £ Per 100
NHD0810	12	8	90	10	80	50	173.43
NHD0830	12	8	110	30	80	50	188.81
NHD0850	12	8	130	50	80	25	204.80
NHD1015	15	10	111	15	95	25	248.16
NHD1025	15	10	121	25	95	25	266.61
NHD1045	15	10	141	45	95	25	304.74
NHD1210	18	12	122	10	105	20	393.61
NHD1220	18	12	132	20	105	20	424.67
NHD1240	18	12	152	40	105	20	477.25
NHD1270	18	12	182	70	105	20	529.53
NHD1620	24	16	157	20	130	10	834.27
NHD1650	24	16	187	50	130	10	928.06



ETA OPTION 1 COUNTERSUNK HEAD HEAVY DUTY ANCHORS BZP



- ☒ Concrete C20/25 To C50/60
 ☒ Cracked Concrete
 ☒ Non-Cracked Concrete
☒ Fire Resistance Loading
 ☒ Seismic C1 + C2

BRIGHT ZINC PLATED

Part Number	Anchor Hole Size mm d_0	Thread Diameter M	Anchor Length mm L	Max Fixture Thickness mm t_{fx}	Minimum Hole Depth mm h_1	Head Diameter mm	Quantity Per Box	Price £ Per 100
SLSK10/10	10	6	70	10	65	18	50	249.26
SLSK10/25	10	6	85	25	65	18	50	261.62
SLSK10/45	10	6	100	40	65	18	50	284.28
SLSK12/10	12	8	80	10	80	20	50	299.04
SLSK12/25	12	8	95	25	80	20	50	321.36
SLSK12/50	12	8	120	50	80	20	25	351.57
SLSK15/10*	15	10	95	10	95	25	25	405.13
SLSK15/25*	15	10	110	25	95	25	25	432.60
SLSK15/50*	15	10	135	50	95	25	25	494.74
SLSK18/20	18	12	115	20	105	30	20	655.08
SLSK18/40	18	12	135	40	105	30	20	738.85

* Torx T50 Drive



ETA OPTION 1 HEXAGON BOLT HEAVY DUTY ANCHORS A4 STAINLESS STEEL



- ☒ Concrete C20/25 To C50/60
 ☒ Cracked Concrete
 ☒ Non-Cracked Concrete
☒ Fire Resistance Loading
 ☒ Seismic C1 + C2
 ☒ Suitable For External Use And Marine Environments

A4-316 STAINLESS STEEL

Part Number	Anchor Hole Size mm d_0	Thread Diameter M	Anchor Length mm L	Max Fixture Thickness mm t_{fx}	Minimum Hole Depth mm h_1	Quantity Per Box	Price £ Per 100
JHD0810SS	12	8	85	10	80	50	1,077.06
JHD0830SS	12	8	105	30	80	50	1,221.96
JHD0850SS	12	8	125	50	80	25	1,592.48
JHD1015SS	15	10	106	15	95	25	1,600.42
JHD1025SS	15	10	116	25	95	25	1,747.38
JHD1045SS	15	10	136	45	95	25	2,338.01
JHD1210SS	18	12	117	10	105	20	2,503.95
JHD1225SS	18	12	127	20	105	20	2,743.72
JHD1240SS	18	12	147	40	105	20	2,976.94



ETA OPTION 1 STUD AND NUT HEAVY DUTY ANCHORS A4 STAINLESS STEEL



- ☒ Concrete C20/25 To C50/60
- ☒ Cracked Concrete
- ☒ Non-Cracked Concrete
- ☒ Fire Resistance Loading
- ☒ Seismic C1 + C2
- ☒ Suitable For External Use And Marine Environments

**A4-316
STAINLESS STEEL**

Part Number	Anchor Hole Size mm d_0	Thread Diameter M	Anchor Length mm L	Max Fixture Thickness mm t_{fx}	Minimum Hole Depth mm h_1	Quantity Per Box	Price £ Per 100
SLB12/10SS	12	8	90	10	80	50	1,077.06
SLB12/30SS	12	8	110	30	80	50	1,221.96
SLB14/15SS	15	10	111	15	95	25	1,600.42
SLB14/25SS	15	10	121	25	95	25	1,747.38
SLB18/20SS	18	12	132	20	105	20	2,503.95
SLB18/40SS	18	12	152	40	105	20	2,743.72




ETA OPTION 1 COUNTERSUNK HEAD HEAVY DUTY ANCHORS A4 STAINLESS STEEL



- ☒ Concrete C20/25 To C50/60
- ☒ Cracked Concrete
- ☒ Non-Cracked Concrete
- ☒ Fire Resistance Loading
- ☒ Seismic C1 + C2
- ☒ Suitable For External Use And Marine Environments

**A4-316
STAINLESS STEEL**

Part Number	Anchor Hole Size mm d_0	Thread Diameter M	Anchor Length mm L	Max Fixture Thickness mm t_{fx}	Minimum Hole Depth mm h_1	Head Diameter mm	Quantity Per Box	Price £ Per 100
SLSK12/10SS	12	8	80	10	80	20	50	1,705.99
SLSK12/25SS	12	8	95	25	80	20	50	1,820.87
SLSK12/50SS	12	8	120	50	80	20	25	1,916.43
SLSK15/15SS	15	10	100	15	95	25	25	2,144.12
SLSK15/25SS	15	10	110	25	95	25	25	2,272.46
SLSK15/50SS	15	10	135	50	95	25	25	2,905.18
SLSK18/20SS	18	12	115	20	105	30	20	4,070.90
SLSK18/40SS	18	12	135	40	105	30	20	4,312.05



The JCP Anchor Calculation Program is free to download via
www.jcpfixings.co.uk





BLIND BOLTS

BLINDBOLT® The Blind Bolt® is a constructional cavity fixing, suitable for fixing to steel sections where access is available from one side only, with the unique design reducing installation time and expense.

HDBOLT® With its expanding base and unique pin locking mechanism, the Heavy Duty Blind Bolt is the ideal fixing solution between heavyweight steel sections, with the unique design reducing installation time and expense.

TWBOLT® The Thin Wall Bolt is for blind fixing to lightweight sheet steel or cladding material, offering a neat, low profile head with no stud protrusion.

- ☒ Fast And Secure Installation
 ☒ Reaction To Fire Class A1
 ☒ High-Performance
 ☒ Installation And Removal Video's Available



Blind Bolt - Tech Data



HD Bolt - Tech Data



TW Bolt - Tech Data

d_0 = Hole Diameter M = Bolt Size L = Length $t_{fix\ min}$ = Minimum Fixture Thickness $t_{fix\ max}$ = Maximum Fixture Thickness



BLIND BOLTS ZINC FLAKE

**ZINC
FLAKE**

- ☒ Removable
 ☒ Grade 10.9 Steel
 ☒ Design Values To BS 5950-1
 ☒ Design Values To EN 1993-1-8
 ☒ Reusable
 ☒ Horizontal And Vertically Down Positions
 ☒ 1000 Hour Salt Spray Protection

Part Number	Hole Diameter mm d_0	Bolt Size M	Length mm L	Min Fixture Thickness mm $t_{fix\ min}$	Max Fixture Thickness mm $t_{fix\ max}$	Quantity Per Box	Price £ Per Each
BB08050ZF	9	8	50	9	24	50	2.60
BB10060ZF	11	10	60	10	25	40	2.88
BB10095ZF	11	10	95	25	64	20	4.40
BB10130ZF	11	10	130	55	100	20	4.57
BB12070ZF	13	12	70	12	35	20	5.60
BB14075ZF	15	14	75	14	35	25	7.77
BB14125ZF	15	14	125	28	82	20	11.52
BB14185ZF	15	14	185	75	142	15	29.70
BB30140ZF*	32	30	140	27	56	5	28.57

* It is strongly recommended to use the installation gauge when installing these bolts.



BLIND BOLTS HDG

**HOT DIPPED
GALVANISED**

- ✓ Removable ✓ Grade 10.9 Steel ✓ Design Values To BS 5950-1 ✓ Design Values To EN 1993-1-8
- ✓ Reusable ✓ Horizontal And Vertically Down Positions

Part Number	Hole Diameter mm d_0	Bolt Size M	Length mm L	Min Fixture Thickness mm $t_{fix\ min}$	Max Fixture Thickness mm $t_{fix\ max}$	Quantity Per Box	Price £ Per Each
BB12070HDG	13	12	70	12	33	20	4.10
BB12120HDG	13	12	120	30	84	25	6.03
BB12180HDG	13	12	180	80	143	20	7.27
BB16090HDG*	17	16	90	13	43	20	7.38
BB16130HDG*	17	16	130	40	75	15	10.20
BB16180HDG*	17	16	180	55	132	10	13.28
BB20110HDG*	22	20	110	21	52	10	14.00
BB20140HDG*	22	20	140	21	82	8	15.22
BB20180HDG*	22	20	180	80	120	10	16.90
BB20250HDG*	22	20	250	130	190	10	21.38
BB24130HDG*	26	24	130	21	62	5	21.30

* It is strongly recommended to use the installation gauge when installing these bolts.



BLIND BOLTS A4 STAINLESS STEEL

**A4-70
STAINLESS STEEL**

- ✓ Removable ✓ Design Values To BS 5950-1 ✓ Design Values To EN 1993-1-8
- ✓ Reusable ✓ Horizontal And Vertically Down Positions

Part Number	Hole Diameter mm d_0	Bolt Size M	Length mm L	Min Fixture Thickness mm $t_{fix\ min}$	Max Fixture Thickness mm $t_{fix\ max}$	Quantity Per Box	Price £ Per Each
BB08050A4	9	8	50	9	24	50	7.00
BB10060A4	11	10	60	10	29	40	9.35
BB12090A4	13	12	90	12	55	20	10.93
BB16100A4	17	16	100	13	53	20	18.58



HEAVY DUTY BLIND BOLTS ZINC FLAKE

**ZINC
FLAKE**

- ✓ Grade 8.8 Steel ✓ No Over-Sized Hole Required ✓ Increased Assembly Efficiency
- ✓ Unique Pin Locking Design ✓ 1000 Hour Salt Spray Protection

Part Number	Hole Diameter mm d_0	Bolt Size M	Length mm L	Min Fixture Thickness mm $t_{fix\ min}$	Max Fixture Thickness mm $t_{fix\ max}$	Quantity Per Box	Price £ Per Each
BBHD0845ZF	8	8	45	7	25	50	2.63
BBHD1045ZF	10	10	45	7	25	40	2.90
BBHD1060ZF	10	10	60	7	40	40	2.98
BBHD1245ZF	12	12	45	8	22	20	3.27
BBHD1260ZF	12	12	60	8	34	20	3.45
BBHD1275ZF	12	12	75	8	48	20	4.97
BBHD1660ZF	16	16	60	12	30	20	7.22
BBHD1675ZF	16	16	75	12	45	20	7.40
BBHD2070ZF	20	20	70	15	32	10	12.50
BBHD2085ZF	20	20	85	15	47	10	13.20



HEAVY DUTY BLIND BOLTS A4 STAINLESS STEEL

**A4-70
STAINLESS STEEL**

- ☒ No Over-Sized Hole Required
 ☒ Increased Assembly Efficiency
 ☒ Unique Pin Locking Design

Part Number	Hole Diameter mm d_0	Bolt Size M	Length mm L	Min Fixture Thickness mm $t_{fix\ min}$	Max Fixture Thickness mm $t_{fix\ max}$	Quantity Per Box	Price £ Per Each
BBHD0845A4	8	8	45	7	25	50	5.15
BBHD1045A4	10	10	45	7	25	40	6.12
BBHD1060A4	10	10	60	7	40	40	7.37
BBHD1245A4	12	12	45	8	22	20	7.47
BBHD1260A4	12	12	60	8	37	20	9.33
BBHD1660A4	16	16	60	12	30	20	16.40
BBHD2070A4	20	20	70	15	32	10	22.40



THIN WALL BLIND BOLTS ZINC NICKEL

ZINC NICKEL

- ☒ No Over-Sized Hole Required
 ☒ High Shear Capacity
 ☒ Low Profile Head
 ☒ Grade 8.8 Steel

Part Number	Blind Bolt Product Code	Hole Diameter mm d_0	Length mm L	Min Fixture Thickness mm $t_{fix\ min}$	Max Fixture Thickness mm $t_{fix\ max}$	Quantity Per Box	Price £ Per Each
BBTW0810ZN	TW5ZF-10	8	35	2	10	100	2.52
BBTW0816ZN	TW5ZF-16	8	40	8	16	100	3.18
BBTW1010ZN	TW6ZF-10	10	40	2	10	50	3.30
BBTW1016ZN	TW5ZF-16	10	45	8	16	50	4.02
BBTW1310ZN	TW8ZF-10	13	45	2	10	50	6.93
BBTW1316ZN	TW8ZF-16	13	50	8	16	50	8.05



THIN WALL BLIND BOLTS A2 STAINLESS STEEL

**A2-70
STAINLESS STEEL**

- ☒ No Over-Sized Hole Required
 ☒ High Shear Capacity
 ☒ Low Profile Head

Part Number	Blind Bolt Product Code	Hole Diameter mm d_0	Length mm L	Min Fixture Thickness mm $t_{fix\ min}$	Max Fixture Thickness mm $t_{fix\ max}$	Quantity Per Box	Price £ Per Each
BBTW0810SS	TW5SS-10	8	35	2	10	100	4.17
BBTW0816SS	TW5SS-16	8	40	8	16	100	4.83
BBTW1010SS	TW6SS-10	10	40	2	10	50	5.40
BBTW1016SS	TW6SS-16	10	45	8	16	50	6.65
BBTW1310SS	TW8SS-10	13	45	2	10	50	10.07
BBTW1316SS	TW8SS-16	13	50	8	16	50	12.23




BLINDBOLT®

THE SMART SOLUTION FOR STEELWORK CONNECTIONS

A simple yet ingenious solution for connections with access from one side only.

Blind bolts are a fully tested assembly for 'blind' fixings to hollow sections and other applications with one-sided access, carrying shear and/or tension. Simple to install, check and tighten – and remove if required.

- Quick and easy to install from one side
- Designed for ordinary clearance holes
- A true removable blind fixing available for structural connections
- Fully tested by the SCI



Watch the downward
installation video here



Watch the vertical
installation video here

Also Available

HDBOLT®



TWBOLT®

APPLICATIONS

Hollow sections
Girders and beams
Masonry support systems
Cladding and façades
Marine



Full technical details, design resistances and SCI report available from www.blindbolt.co.uk



INJECTION RESINS AND GLASS CAPSULES

Chemical Anchors used for installing threaded studs, rebar or internal threaded sockets for structural applications.



- ✓ High-Performance ✓ Good, Better, Best Options Available

J-FIX PURE EPOXY RESIN



Pure epoxy resin is a 3:1 ratio resin with very high load capacities, and is approved for use in contact with potable (drinking) water. Suitable for use in the majority of base materials.



- ✓ ETA Option 1 ✓ Concrete C20/25 To C50/60 ✓ Cracked Concrete ✓ Non-Cracked Concrete
 ✓ 100 Years Working Life ✓ Seismic C1 + C2 ✓ Dry/Wet/Flooded Holes ✓ Expansion Free ✓ Close Spacing And Edge Distance

Part Number	Description	Volume ml	Quantity Unit/Box	Price £ Per Each
JF375E	Red Pure Epoxy Resin in Cartridge + 1 Mixer Nozzle	385	1/12	23.30

J-FIX ULTRA-BOND 100 EPOXY RESIN



Ultra-Bond 100 epoxy resin is a formulation derived from pure epoxy with very high bond strength. The two-component chemical anchoring injection system in a 3:1 ratio can achieve high loads and is used for high-performance structural applications where loading is critical.



- ✓ ETA Option 1 ✓ Our Highest-Strength Resin ✓ Concrete C20/25 To C50/60 ✓ Cracked Concrete ✓ Non-Cracked Concrete
 ✓ 100 Years Working Life ✓ Seismic C1 + C2 ✓ Dry/Wet/Flooded Holes ✓ Expansion Free ✓ Close Spacing And Edge Distance

Part Number	Description	Volume ml	Quantity Unit/Box	Price £ Per Each
JF585E	Red Ultra-Bond Epoxy Resin in Cartridge + 1 Mixer Nozzle	585	1/12	33.40





J-FIX ULTRA-BOND 100 EPOXY RESIN



ETA Option 1 approved, the J-Fix Ultra Bond 100 is suitable for high loads featuring large diameters and deep embedment. Longer working times make it ideal for large holes and high temperatures.

It is also approved for use under seismic actions C1 and C2. Offering high durability and resistance to chemicals, Ultra-Bond 100 is a low-emitting material and qualified to be categorised as LEED v4 and v4.1 Beta according to ISO 16000, EN 16516, ISO 11890-2 and ASTM D2369 testing standards.








- ☒ 24 Month Shelf Life From Date of Manufacture
- ☒ Ideal for Rotary Hammer Drilled Dry and Wet Holes
- ☒ Longer Working Times for Large Holes and High Temperatures

J-FIX VINYLESTER RESIN

Pure vinylester resin is a high strength resin, which can be used in dry, damp, and flooded holes, and comes complete with a WRAS Approval number.



- ☒ ETA Option 1 ☒ ETA For Masonry ☒ Concrete C20/25 To C50/60 ☒ Cracked Concrete ☒ Non-Cracked Concrete
- ☒ 100 Years Working Life ☒ Styrene Free ☒ Seismic C1 ☒ Dry/Wet/Flooded Holes ☒ Expansion Free ☒ Close Spacing And Edge Distance

Part Number	Description	Volume ml	Quantity Unit/Box	Price £ Per Each
JFV380SF	Vinylester High Load Resin in Cartridge + 1 Mixer Nozzle	410	1/12	16.51
JFV300SF	Vinylester High Load Resin in Cartridge + 1 Mixer Nozzle	300	1/12	12.73

J-FIX VINYLESTER FAST CURE WINTER GRADE RESIN

Winter grade vinylester resin can be used in temperatures down to -20°C or as a fast cure resin in warmer temperatures.



- ☒ ETA Option 1 ☒ ETA For Masonry ☒ Concrete C20/25 To C50/60 ☒ Cracked Concrete
- ☒ Non-Cracked Concrete ☒ Winter Grade ☒ 100 Years Working Life ☒ Styrene Free ☒ Seismic C1
- ☒ Dry/Wet/Flooded Holes ☒ Expansion Free ☒ Close Spacing And Edge Distance

Part Number	Description	Volume ml	Quantity Unit/Box	Price £ Per Each
JFEA410SF	Winter Grade Vinylester Resin in Cartridge + 1 Mixer Nozzle	410	1/12	17.68

J-FIX EPOXY ACRYLATE RESIN

Epoxy acrylate resin is suitable for use in non-cracked concrete, other base materials and in damp conditions.



- ☒ ETA Option 7
- ☒ Concrete C20/25 To C50/60
- ☒ Non-Cracked Concrete
- ☒ Styrene Free
- ☒ Dry/Wet/Flooded Holes
- ☒ Expansion Free
- ☒ Close Spacing And Edge Distance

Part Number	Description	Volume ml	Quantity Unit/Box	Price £ Per Each
JFEA380SF	Grey Styrene Free Epoxy Acrylate Resin in Cartridge + 1 Mixer Nozzle	410	1/12	13.64

J-FIX POLYESTER STYRENE FREE RESIN

Polyester styrene free resin is a general purpose resin suitable for brickwork, most natural stone, and concrete.



- ☒ ETA Option 7
- ☒ Concrete C20/25 To C50/60
- ☒ Non-Cracked Concrete
- ☒ Styrene Free
- ☒ Dry/Wet/Flooded Holes
- ☒ Expansion Free
- ☒ Close Spacing And Edge Distance

Part Number	Description	Volume ml	Quantity Unit/Box	Price £ Per Each
JF380PSF	Grey Styrene Free Polyester Resin in Cartridge + 1 Mixer Nozzle	410	1/12	11.03
JF300PSF	Grey Styrene Free Polyester Resin in Cartridge + 2 Mixer Nozzle	300	1/12	9.26
JFEA300SF	Grey Styrene Free Polyester Resin in Cartridge + 1 Mixer Nozzle	300	1/12	9.45
JF150P	Grey Styrene Free Polyester Resin in Cartridge + 2 Mixer Nozzles	150	1/12	8.80

NEW

J-FIX POLYESTER RESIN

Polyester resin is a general purpose resin suitable for brickwork, most natural stone and concrete.



- ☒ ETA Option 7
- ☒ Concrete C20/25 To C50/60
- ☒ Non-Cracked Concrete
- ☒ Dry/Wet/Flooded Holes
- ☒ Expansion Free
- ☒ Close Spacing And Edge Distance

Part Number	Description	Volume ml	Quantity Unit/Box	Price £ Per Each
JF380P	Grey Polyester Resin in Cartridge + 1 Mixer Nozzle	410	1/12	10.12
JF300P	Grey Polyester Resin in Cartridge + 2 Mixer Nozzle	300	1/12	7.25

NEW

APPROXIMATE RESIN FIXING PER CARTRIDGE

Thread Diameter mm	Hole Size mm	Hole Depth mm	585ml	410ml	375ml	300ml	150ml
M8	10	80	110	78	71	57	25
M10	12	90	73	52	48	38	17
M12	14	110	46	34	31	25	11
M16	18	125	30	22	20	16	7
M20	22	170	14	11	10	8	3
M24	26	210	9	7	6	5	2



J-FIX SPIN-IN GLASS CAPSULES

The spin in glass capsule anchor contains a quartz aggregate and is used with threaded studs to provide a stress free anchorage in concrete, offering exceptional load capability.

- ☒ ETA Option 7
- ☒ Non-Cracked Concrete
- ☒ Good Resistance To Vibrating Loads
- ☒ Can Be Used In Wet And Corrosive Environment
- ☒ Expansion Free
- ☒ Epoxy Acrylate



Part Number	Thread Diameter mm	Length mm	Max Fixture Thickness mm	Hole Diameter mm	Min Hole Depth mm	Quantity Per Box	Price £ Per 100
JCAPSM08	8	80	9	10	80	10	117.63
JCAPSM10	10	80	11	12	90	10	117.63
JCAPSM12	12	95	13	14	110	10	119.70
JCAPSM16	16	95	17	18	125	10	135.93
JCAPSM20	20	160	17	22	170	10	256.20
JCAPSM24	24	175	22	26	210	6	295.36
JCAPSM30	30	230	25	32	280	5	551.68



J-FIX HAMMER-IN GLASS CAPSULES

The epoxy acrylate hammer in capsules are suitable for use in solid concrete and natural stone, and can be used with reinforcing bar or threaded rods, achieving high loads by using two capsules at double embedment depth.

- ☒ Increased Embedment Depth
- ☒ Expansion Free
- ☒ Exact Resin Quantity Per Hole
- ☒ Rapid Installation
- ☒ For Use With Rebar/Flat Ended Studs

Part Number	Rebar Nominal Diameter mm	Thread Diameter mm	Capsule Diameter mm	Capsule Length mm	Min Hole Depth mm	Quantity Per Box	Price £ Per 100
JCAPHM10	10	10	11	90	100	10	138.56
JCAPHM12	12	12	13	110	110	10	146.78
JCAPHM16	16	16	17	125	125	10	165.76
JCAPHM20	20	20	22	175	200	6	318.75
JCAPHM24	25	24	24	210	250	6	373.37
JCAPHM30	32	30	33	265	300	6	708.76



ANCHORING CEMENTS

ROCKITE (INTERIOR GRADE)

Rockite is a fast-setting hydraulic expansion cement. When mixed with water it provides a compound that can be used internally for grouting, anchoring or patching. 1kg (2.2lb) dry powder weight fills approximately 700 cubic centimetres.



- ☒ Fast Setting
- ☒ Crack-Free Finish
- ☒ Mix With Water
- ☒ Expanding

Part Number	Description	Quantity	Price £ Per Each
57 9020	0.45kg (1lb) Carton	1	4.25
57 9002	2.27kg (5lb) Carton	1	16.34
57 9003	4.54kg (10lb) Pail	1	30.47
57 9004	22.70kg (50lb) Carton	1	115.98
57 9005	22.70kg (50lb) Pail	1	130.48



PAIL



CARTON

KWIXSET (EXTERIOR GRADE)

Kwixset is a fast-setting hydraulic type cement for external or internal use.

- ☒ Fast Setting
- ☒ Ideal For External Or Internal Use
- ☒ No Further Treatment Required For External Use
- ☒ Expanding

Part Number	Description	Quantity	Price £ Per Each
57 9011	11.35kg (25lb) Pail	1	82.99
57 9012	22.70kg (50lb) Pail	1	156.32





Caution: Rockite and Kwixset have very strong expansion properties which generate the high tensile loads that can be achieved and as such their use in hollow bricks or blocks is not recommended.





THREADED STUDS AND SOCKETS

For use with J-Fix Spin-In Glass Capsules or J-Fix Injection Resin Systems.

- ☒ Plain Ended For Injection Resin Only
- ☒ Chisel Ended For Injection Resin And Glass Capsules
- ☒ Chisel Ended Studs Come Complete With Setting Tool For Glass Capsules



M=Thread Diameter L=Length t_{fix} =Maximum Fixture Thickness h_1 =Minimum Hole Depth



M=Internal Thread Diameter L_{th} =Internal Thread Length d_0 =Hole Diameter L=Anchor Length h_1 =Minimum Hole Depth

J-FIX STUDS BZP

- ☒ Chisel Point
- ☒ Grade 5.8 Threaded Stud
- ☒ Depth Mark Indicates Embedment Depth At Standard Embedment



BRIGHT ZINC PLATED

Part Number	Thread Diameter M	Length mm L	Max Fixture Thickness mm t_{fix}	Min Hole Depth mm h_1	Quantity Per Box	Price £ Per 100
JSTUD08110	8	110	18	80	10	36.38
JSTUD10130	10	130	25	90	10	52.55
JSTUD12160	12	160	34	110	10	79.35
JSTUD16190	16	190	45	125	10	156.52
JSTUD20260	20	260	55	170	10	305.46
JSTUD24300	24	300	55	210	5	504.27
JSTUD30380	30	380	55	280	5	1,000.19



J-FIX STUDS PLAIN ENDED BZP

- ✓ Plain Ended ✓ Grade 5.8 Threaded Stud



**BRIGHT ZINC
PLATED**

Part Number	Thread Diameter M	Length mm L	Max Fixture Thickness mm t_{fx}	Min Hole Depth mm h_1	Quantity Per Box	Price £ Per 100
JSTUD08150PE	8	150	62	80	10	41.02
JSTUD10105PE	10	105	5	90	10	60.29
JSTUD10150PE	10	150	50	90	10	64.25
JSTUD10200PE	10	200	100	90	10	77.35
JSTUD12110PE	12	110	-	-	10	64.60
JSTUD12150PE	12	150	27	110	10	87.29
JSTUD12200PE	12	200	77	110	10	109.39
JSTUD16110PE	16	110	-	-	10	133.98
JSTUD16250PE	16	250	104	128	10	221.93
JSTUD16350PE	16	350	204	128	10	279.51
JSTUD20200PE	20	200	9	170	10	305.15
JSTUD20400PE	20	400	209	170	10	484.66



J-FIX STUDS ZYP - HIGH TENSILE

- ✓ Chisel Point ✓ High Tensile Grade 8.8 Threaded Stud
✓ Depth Mark Indicates Embedment Depth At Standard Embedment



**ZINC AND
YELLOW PLATED**

Part Number	Thread Diameter M	Length mm L	Max Fixture Thickness mm t_{fx}	Min Hole Depth mm h_1	Quantity Per Box	Price £ Per 100
JSTUD08110HT	8	110	18	80	10	42.56
JSTUD10130HT	10	130	25	90	10	62.81
JSTUD12160HT	12	160	34	110	10	97.19
JSTUD16190HT	16	190	45	125	10	192.53
JSTUD20260HT	20	260	55	170	10	385.84
JSTUD24300HT	24	300	55	210	5	626.45
JSTUD30380HT	30	380	55	280	5	1,245.61



J-FIX STUDS GALV

- ✓ Chisel Point ✓ Grade 5.8 Threaded Stud
✓ Depth Mark Indicates Embedment Depth At Standard Embedment ✓ BS EN ISO 1461:2009



**HOT DIPPED
GALVANISED**

Part Number	Thread Diameter M	Length mm L	Max Fixture Thickness mm t_{fx}	Min Hole Depth mm h_1	Quantity Per Box	Price £ Per 100
JSTUD08110G	8	110	18	80	10	43.26
JSTUD10130G	10	130	25	90	10	66.25
JSTUD12160G	12	160	34	110	10	99.56
JSTUD16190G	16	190	45	125	10	194.24
JSTUD20260G	20	260	55	170	5	382.10
JSTUD24300G	24	300	55	210	5	617.86



**FREE, NEXT-DAY DELIVERY WITH LOW MINIMUM ORDER LEVELS
ACROSS THE MAJORITY OF THE UK MAINLAND.**



J-FIX STUDS GALV - HIGH TENSILE



**HOT DIPPED
GALVANISED**

- ✓ Chisel Point ✓ High Tensile Grade 8.8 Threaded Stud
- ✓ Depth Mark Indicates Embedment Depth At Standard Embedment ✓ BS EN ISO 1461:2009

Part Number	Thread Diameter M	Length mm L	Max Fixture Thickness mm t_{fx}	Min Hole Depth mm h_1	Quantity Per Box	Price £ Per 100
JSTUD08110GHT	8	110	18	80	10	59.16
JSTUD10130GHT	10	130	25	90	10	87.77
JSTUD12160GHT	12	160	34	110	10	130.08
JSTUD16190GHT	16	190	45	125	10	250.71
JSTUD20260GHT	20	260	55	170	5	507.59
JSTUD24300GHT	24	300	55	210	5	857.33



J-FIX STUDS A2 STAINLESS STEEL



**A2-304
STAINLESS STEEL**

- ✓ Chisel Point ✓ Grade 70 Stainless Steel Threaded Stud
- ✓ Depth Mark Indicates Embedment Depth At Standard Embedment ✓ Suitable For External Use

Part Number	Thread Diameter M	Length mm L	Max Fixture Thickness mm t_{fx}	Min Hole Depth mm h_1	Quantity Per Box	Price £ Per 100
JSTUD08110SS	8	110	18	80	10	120.08
JSTUD10130SS	10	130	25	90	10	197.87
JSTUD12160SS	12	160	34	110	10	331.43
JSTUD16190SS	16	190	45	125	10	688.64
JSTUD20260SS	20	260	55	170	5	1,420.59
JSTUD24300SS	24	300	55	210	5	2,309.95



J-FIX STUDS A4 STAINLESS STEEL



**A4-316
STAINLESS STEEL**

- ✓ Chisel Point ✓ Grade 70 Stainless Steel Threaded Stud
- ✓ Depth Mark Indicates Embedment Depth At Standard Embedment ✓ Suitable For External Use And Marine Environments

Part Number	Thread Diameter M	Length mm L	Max Fixture Thickness mm t_{fx}	Min Hole Depth mm h_1	Quantity Per Box	Price £ Per 100
JSTUD08110SSA4	8	110	18	80	10	158.54
JSTUD10130SSA4	10	130	25	90	10	272.32
JSTUD12160SSA4	12	160	34	110	10	450.64
JSTUD16190SSA4	16	190	45	125	10	939.89
JSTUD20260SSA4	20	260	55	170	5	1,975.37
JSTUD24300SSA4	24	300	55	210	5	3,253.29

Available from

www.owlett-jaton.com

- Full range of allthread studs in sizes M4 to M12
- Studding in 1 metre and 3 metre lengths

Owlett-Jaton



J-FIX STUDS PLAIN ENDED A4 STAINLESS STEEL



**A4-316
STAINLESS STEEL**

- ✓ Plain Ended
- ✓ Grade 70 Stainless Steel Threaded Stud
- ✓ Suitable For External Use And Marine Environments

Part Number	Thread Diameter M	Length mm L	Max Fixture Thickness mm t_{fix}	Min Hole Depth mm h_1	Quantity Per Box	Price £ Per 100
JSTUD08150PESS	8	150	62	80	10	186.17
JSTUD10105PESS	10	105	5	90	10	225.03
JSTUD10150PESS	10	150	50	90	10	294.79
JSTUD10200PESS	10	200	100	90	10	363.67
JSTUD12110PESS	12	110	-	-	10	332.99
JSTUD12150PESS	12	150	27	110	10	407.85
JSTUD12200PESS	12	200	77	110	10	510.49
JSTUD16110PESS	16	110	-	-	10	596.57
JSTUD16250PESS	16	250	104	128	10	1,118.53
JSTUD16350PESS	16	350	204	128	10	1,473.68
JSTUD20200PESS	20	200	9	170	10	1,488.36
JSTUD20400PESS	20	400	209	170	10	2,674.54



INJECTION RESIN INTERNALLY THREADED SOCKETS BZP

**BRIGHT ZINC
PLATED**

- ✓ For Use In Solid Masonry/Brickwork
- ✓ Provides A Flush Fixing
- ✓ Use With Set Screws, Bolts Or Threaded Rod
- ✓ Allows Removal Of Bolt To Leave Reusable Socket

Part Number	Internal Thread M	Internal Thread Length mm L_{th}	Outside Diameter mm	Hole Diameter mm d_0	Anchor Length mm L	Min Hole Depth mm h_1	Quantity Per Box	Price £ Per 100
INJM06	6	20	8	10	50	60	10	68.33
INJM08	8	25	12	14	80	90	10	98.00
INJM10	10	30	14	16	80	90	10	117.92
INJM12	12	30	16	18	80	90	10	135.11



INTERNAL THREADED SOCKETS BZP



**BRIGHT ZINC
PLATED**

- ✓ Provides A Flush Fixing
- ✓ Expansion Free
- ✓ High Loads
- ✓ Permanent Threaded Socket
- ✓ Allows Removal Of Bolt To Leave Reusable Socket

Part Number	Internal Thread M	Internal Thread Length mm L_{th}	Outside Diameter mm	Hole Diameter mm d_0	Anchor Length mm L	Min Hole Depth mm h_1	Quantity Per Box	Price £ Per 100
ITSM08BZP	8	30	12	14	90	90	10	102.20
ITSM10BZP	10	35	16	18	90	90	10	146.10
ITSM12BZP	12	40	20	22	90	90	10	207.10
ITSM16BZP	16	40	24	28	125	125	10	386.71



INTERNAL THREADED SOCKETS A2 STAINLESS STEEL



**A2-304
STAINLESS STEEL**

- ✓ Provides A Flush Fixing
- ✓ Suitable for External Use
- ✓ Expansion Free
- ✓ High Loads
- ✓ Permanent Threaded Socket
- ✓ Allows Removal Of Bolt To Leave Reusable Socket
- ✓ Suitable For External Use

Part Number	Internal Thread M	Internal Thread Length mm L_{th}	Outside Diameter mm	Hole Diameter mm d_0	Anchor Length mm L	Min Hole Depth mm h_1	Quantity Per Box	Price £ Per 100
ITSM08SS	8	30	12	14	90	90	10	297.60
ITSM10SS	10	35	16	18	90	90	10	463.81
ITSM12SS	12	40	20	22	90	90	10	682.87
ITSM16SS	16	40	24	28	125	125	10	1,324.15



INTERNAL THREADED SOCKETS A4 STAINLESS STEEL



**A4-316
STAINLESS STEEL**

- ✓ Provides A Flush Fixing
- ✓ Suitable For External Use And Marine Environments
- ✓ Expansion Free
- ✓ High Loads
- ✓ Permanent Threaded Socket
- ✓ Allows Removal Of Bolt To Leave Reusable Socket

Part Number	Internal Thread M	Internal Thread Length mm L _{th}	Outside Diameter mm	Hole Diameter mm d ₀	Anchor Length mm L	Min Hole Depth mm h _i	Quantity Per Box	Price £ Per 100
ITSM08SSA4	8	30	12	14	90	90	10	370.70
ITSM10SSA4	10	35	16	18	90	90	10	593.20
ITSM12SSA4	12	40	20	25	90	90	10	885.40
ITSM16SSA4	16	40	24	28	125	125	10	1,757.43



INJECTION RESIN ACCESSORIES

A range of injection resin accessories.


- ✓ For Use With The J-Fix Injection Resin Systems
- ✓ Compatible With Other Resins



INJECTION TOOLS

- ✓ Easy-To-Use
- ✓ Hand Operated

Part Number	Description	Ship Wt.Kg Per Each	Price £ Per Each
JTOOL150	For Any 150ml and 300ml Cartridge	0.60	6.58
JTOOL300	For Any 150ml and 300ml Cartridge	1.00	13.28
JTOOL375	For JF375E 385ml Cartridge	1.40	58.21
JTOOL380	For Any 410ml Cartridge	1.30	25.79
JTOOL410	For Any 410ml Cartridge	1.35	34.95
JTOOL600	For JF585E 585ml Cartridge	1.85	65.00




INJECTION TOOL ACCESSORIES

- ✓ Mixer Nozzles
- ✓ Extension Tube

Part Number	Description	Ship Wt.Kg Per Each	Price £ Per Each
JMN130	Mixer Nozzle	1.00	1.00
JMN190	Extension Tube for JMN130	1.00	0.90
JMN150E	Mixer Nozzle for JF375E and JF585E Pure Epoxy	1.00	1.65





NYLON SLEEVE WITH STUD ALIGNMENT COLLAR

- ✓ For Use With Injection Resin In Hollow Bricks And Blocks
- ✓ Perforated, Allowing The Resin To Evenly Permeate
- ✓ Stud Alignment Collar Aids With Accurate Positioning Of The Stud

Part Number	Hole Diameter mm	Sleeve Size mm	For Stud Size M	Quantity Per Bag	Price £ Per 100
JNSLM08/12	16	15 x 85	8-12	10	22.89
JNSLM08/12L	16	15 x 130	8-12	10	25.94
JNSLM16	22	20 x 85	16	10	30.83



WIRE MESH SLEEVE

- ✓ Perforated, Allowing The Resin To Evenly Permeate
- ✓ Can Be Cut On Site To Required Length

Part Number	Hole Diameter mm	Inside Diameter mm	For Stud Size M	Length mm	Quantity Per Box	Price £ Per Each
JMMSM08	12	8.7	M8	1000	1	6.22
JMMSM10/12	16	12.5	M10-M12	1000	1	6.94
JMMSM16	22	18.0	M16	1000	1	7.50
JMMSM20	26	22.0	M20	1000	1	7.89

WIRE CLEANING BRUSHES

- ✓ Cleaned Surfaces Ensure Optimum Bond Strength Of Fixing
- ✓ Hand Operated

Part Number	Brush Diameter mm	Pack Quantity	Price £ Per Each
CB08	8	1	4.76
CB10	10	1	6.23
CB12	12	1	6.62
CB16	16	1	7.36
CB20	20	1	7.85
CB25	25	1	7.60
CBW30	30	1	8.34
CBFW25	FLAT	1	8.34



Round Wire Brush

Flat Brush



BLOW OUT PUMP

Used to remove dust from holes prior to applying J-Fix Injection Resin Systems.

- ✓ Should Be Used After Application Of Round Wire Cleaning Brush
- ✓ Hand Operated

Part Number	Hole Diameter mm	Pack Quantity	Price £ Per Each
BOP1	10+	1	10.95



CRACK STITCHING ACCESSORIES

A range of crack stitching accessories for use when permanently repairing vertical or stepped cracks in masonry walls.



- ✓ Stabilises The Structure ✓ Helps Prevent Against Further Cracking
- ✓ Preserves Structural Integrity ✓ Non-Disruptive Repair Method

CRACK STITCH TWIST STARTER KIT

A complete system for reinforcing masonry and crack stitching.

KIT CONTAINS:

• 10 Lengths of 6mm x 1000mm Stitching Bar • 1 x 3ltr Tub of Cementitious Grout • 1 x 9.5mm Nozzle • 1 x Crack Stitching Pointing Gun • 1 x Mixing Paddle • 1 x Finger Trowel

- ✓ Eliminates The Need To Rebuild A Wall ✓ Absorbs Further Localised Stress
- ✓ Minimises The Likelihood Of Further Cracking



Part Number	Description	Pack Quantity	Price £ Per Each
CSKIT	Crack Stitch Twist Starter Set	1	261.83

POINTING GUN

Crack-stitching pointing gun comes complete with cartridge, cone, and mortar nozzle.

- ✓ Enables Accurate Grout Application, Reducing Waste ✓ Hand Operated



Part Number	Description	Pack Quantity	Price £ Per Each
CSGUN	Crack Stitching Gun	1	65.63

STITCHING BAR A2 STAINLESS STEEL

**A2-304
STAINLESS STEEL**

1 metre bar for use as masonry reinforcement and crack stitching.

- ✓ Eliminates The Need To Rebuild A Wall
- ✓ Absorbs Further Localised Stress
- ✓ Minimises The Likelihood Of Further Cracking

Part Number	Size mm	Quantity Per Box	Price £ Per Each
CS061000	6 x 1000	10	6.42
CS081000	8 x 1000	10	8.67



CEMENTITIOUS GROUT

Cementitious grout for use in crack stitching.

- ✓ Gives Excellent Flow For Easy Application
- ✓ Low Liquid To Powder Ratio Provides A Thixotropic Grout
- ✓ Free From Chlorides And Nitrates

Part Number	Size	Pack Quantity	Price £ Per Each
CSGROUT	3 Litre Tub	1	59.85



PU FOAMS AND ACCESSORIES

Ready-to-use construction foams, sealants and accessories for a wide variety of construction applications.

- ✓ Ready-To-Use
- ✓ Gun Grade Options
- ✓ Fire Resistance Options
- ✓ Effective Cavity Filling



POLYURETHANE CLEANER

Polyurethane cleaner for cleaning un-cured foam, which attaches to standard foam applicator guns.

- ✓ Ideal For Preserving Applicator Guns By Cleaning Out The Nozzle

Part Number	Description	Volume ml	Quantity Unit/ Box	Price £ Per Each
JF500C	Polyurethane Cleaner	500	1/12	5.15

B1 RATED FIRE STOP EXPANDING FOAM

B1 rated expanding foam is a one-part, self-expanding, ready-to-use polyurethane construction foam designed for sealing joints in walls and service openings to prevent the passage of smoke and fire.



- ✓ Good Volume Expansion For Effective Filling
- ✓ Hand Held Aerosol And Gun Grade Cans
- ✓ Excellent Heat Resistance
- ✓ Can Provide Up To 4 Hours Fire Resistance
- ✓ High Thermal And Acoustic Insulation
- ✓ Resistant To Mould And Fungal Attack

Part Number	Description	Volume ml	Quantity Unit/ Box	Price £ Per Each
JF750B1H	Grade B1 Hand Held Expanding Foam + 1 Nozzle	750	1/12	12.96
JF750B1G	Grade B1 Gun Applied Expanding Foam	750	1/12	12.96



B3 RATED EXPANDING FOAM

B3 rated expanding foam is a one-part, self-expanding, ready-to-use polyurethane construction foam designed for filling irregular gaps.

- ✓ Good Volume Expansion For Effective Filling
- ✓ Hand Held Aerosol And Gun Grade Cans
- ✓ Low Curing Pressure Avoids Deformation Of Building Elements
- ✓ CFC Free Propellant
- ✓ Excellent Adhesion
- ✓ High Thermal And Acoustic Insulation
- ✓ Excellent Mounting Capabilities
- ✓ Excellent Stability

Part Number	Description	Volume ml	Quantity Unit/ Box	Ship Wt.Kg Each	Price £ Per Each
JF750B3H	Grade B3 Hand Held Expanding Foam + 1 Nozzle	750	1/12	0.84	9.19
JF750B3G	Grade B3 Gun Applied Expanding Foam	750	1/12	0.84	9.53



APPLICATOR GUNS

A choice of professional and conventional applicator guns for use with gun grade expanding foam.

- ✓ Designed To Evenly And Accurately Distribute Foam
- ✓ Hand Operated

Part Number	Description	Quantity Unit/ Box	Price £ Per Each
JFGUNC	Professional	1	28.98
JFGUNB	Conventional	1	18.33



PROFESSIONAL



CONVENTIONAL



HEAVY DUTY ANCHORS



LIGHT DUTY FIXINGS



CHEMICAL ANCHORS



NYLON AND CAVITY FIXINGS



MEDIUM DUTY ANCHORS



PA AND GAS



SELF-DRILLING SCREWS



DRILL BITS

SPECIALIST FIXINGS BACKED BY TECHNICAL SUPPORT

www.jcpfixings.co.uk






SLEEVE ANCHORS

Thin walled sleeve anchors suitable for use in concrete, stone, brickwork, perforated bricks, and dense concrete blocks.



- ✓ Through Fixing
- ✓ Suitable For Fixing Into Solid Brick, Dense Concrete Blocks, And Non-Cracked Concrete
- ✓ Torque Controlled Expansion



HEXAGON FLANGE NUT SLEEVE ANCHORS ZYP

- ✓ Non-Cracked Concrete
- ✓ Supplied Pre-Assembled For Rapid Installation



**ZINC AND
YELLOW PLATED**

Part Number	Anchor Hole Size mm d_0	Anchor Length mm L	Max Fixture Thickness mm t_{fix}	Minimum Hole Depth mm h_1	Quantity Per Box	Price £ Per 100
SLN08040	8	40	5	35	100	14.13
SLN08065	8	65	30	40	50	17.94
SLN08085	8	85	45	40	50	20.98
SLN10050	10	50	5	45	50	23.29
SLN10075	10	75	30	45	50	29.40
SLN10100	10	100	55	45	50	35.48
SLN10125	10	125	80	45	50	44.67
SLN12060	12	60	15	50	50	38.15
SLN12075	12	75	20	60	50	42.70
SLN12100	12	95	50	60	25	53.39
SLN12125	12	125	65	60	25	64.04
SLN16065	16	65	10	60	25	74.40
SLN16110	16	105	50	65	10	104.50
SLN16150	16	150	90	65	10	133.13
SLN20080	20	80	15	70	10	143.39
SLN20110	20	110	45	70	10	175.43
SLN20150	20	150	85	70	10	218.89

RETAIL BAGS

Product Part Number	Bag Part Number	Size mm	Quantity Per Bag	Price £ Per Bag
SLN08085	JB8200	8 x 85	6	3.63
SLN10075	JB8203	10 x 75	4	3.41
SLN10100	JB8206	10 x 100	4	3.84
SLN12075	JB8209	12 x 75	4	4.15
SLN12100	JB8212	12 x 100	4	4.59



HEXAGON BOLT SLEEVE ANCHORS ZYP

- ✓ Non-Cracked Concrete
- ✓ Supplied Pre-Assembled For Rapid Installation
- ✓ Hex Bolt Gives A Bolt Head Finish



ZINC AND
YELLOW PLATED

Part Number	Anchor Hole Size mm d_o	Anchor Length mm L	Max Fixture Thickness mm t_{fx}	Minimum Hole Depth mm h_1	Quantity Per Box	Price £ Per 100
SLB08045	8	45	2	45	100	16.03
SLB08070	8	70	25	45	50	20.24
SLB08090	8	90	45	45	50	23.28
SLB10045	10	45	5	45	50	23.28
SLB10055	10	55	15	45	50	25.55
SLB10080	10	80	30	50	50	31.63
SLB10100	10	100	50	50	50	36.61
SLB12065	12	65	5	65	50	41.59
SLB12080	12	80	20	65	50	46.93
SLB12100	12	100	40	65	25	55.32
SLB12125	12	125	65	65	25	67.91
SLB16075	16	75	5	65	25	79.73
SLB16110	16	110	40	65	10	107.16



COUNTERSUNK HEAD SLEEVE ANCHORS ZYP

- ✓ Non-Cracked Concrete
- ✓ Supplied Pre-Assembled For Rapid Installation
- ✓ Countersunk Head Gives A Flush Fixture



ZINC AND
YELLOW PLATED

Part Number	Anchor Hole Size mm d_o	Anchor Length mm L	Max Fixture Thickness mm t_{fx}	Minimum Hole Depth mm h_1	Head Diameter mm	Quantity Per Box	Price £ Per 100
SLC08060	8	60	30	40	14	100	43.21
SLC08085	8	85	50	40	14	50	49.56
SLC10075	10	75	40	45	16	50	61.69
SLC10100	10	100	60	45	16	50	73.72



FREE, NEXT-DAY DELIVERY WITH LOW MINIMUM ORDER LEVELS
ACROSS THE MAJORITY OF THE UK MAINLAND.



HEXAGON FLANGE NUT SLEEVE ANCHORS A4 STAINLESS STEEL



**A4-316
STAINLESS STEEL**

- ✓ Non-Cracked Concrete
- ✓ Supplied Pre-Assembled For Rapid Installation
- ✓ Suitable For External Use And Marine Environments

Part Number	Anchor Hole Size mm d_0	Anchor Length mm L	Max Fixture Thickness mm t_{fx}	Minimum Hole Depth mm h_1	Quantity Per Box	Price £ Per 100
SLSS06060	6	55	25	35	100	87.72
SLSS08040	8	40	5	40	100	104.79
SLSS08065	8	65	30	40	100	141.17
SLSS10050	10	50	10	45	50	202.38
SLSS10075	10	75	35	45	50	257.17
SLSS10100	10	95	55	45	50	319.24
SLSS12060	12	55	10	50	50	317.90
SLSS12075	12	65	20	60	50	361.44
SLSS12100	12	95	50	60	25	453.69



COUNTERSUNK HEAD SLEEVE ANCHORS A2 STAINLESS STEEL



**A2-304
STAINLESS STEEL**

- ✓ Non-Cracked Concrete
- ✓ Supplied Pre-Assembled For Rapid Installation
- ✓ Countersunk Head Gives Flush Finish
- ✓ Suitable For External Use
- ✓ Hex Drive

Part Number	Anchor Hole Size mm d_0	Anchor Length mm L	Max Fixture Thickness mm t_{fx}	Minimum Hole Depth mm h_1	Head Diameter mm	Quantity Per Box	Price £ Per 100
SLC08045SS	8	45	8	50	12	100	89.66
SLC08060SS	8	60	18	60	12	50	102.04
SLC10060SS	10	60	9	60	16	50	141.15
SLC10080SS	10	80	19	80	16	50	159.77
SLC12070SS	12	70	10	75	20	50	244.03
SLC12100SS	12	100	30	100	20	25	311.14



EYE AND HOOK BOLT SLEEVE ANCHORS ZYP

**ZINC AND
YELLOW PLATED**

- ✓ Non-Cracked Concrete/Stone/Brickwork/Dense Concrete Blocks
- ✓ Supplied Pre-Assembled For Rapid Installation
- ✓ Forged Eye For Improved Strength

Part Number	Anchor Hole Size mm d_0	Eye Diameter mm	Minimum Hole Depth mm h_1	Quantity Per Box	Price £ Per 100
Hookbolt - SLZH08040	8	11	45	100	27.44
Forged Eyebolt - SLZE08040F	8	10	45	20	44.36

Hook Bolt



Eye Bolt



EYE BOLT SLEEVE ANCHORS A2 STAINLESS STEEL

**A2-304
STAINLESS STEEL**

- ✓ Non-Cracked Concrete/Stone/Brickwork/Dense Concrete Blocks
- ✓ Supplied Pre-Assembled For Rapid Installation
- ✓ Forged Eye For Improved Strength
- ✓ Suitable For External Use


Part Number	Anchor Hole Size mm d_0	Length mm L	Eye Diameter mm	Minimum Hole Depth mm h_1	Quantity Per Box	Price £ Per 100
SLZE08045SS	8	78	10	50	50	311.39
SLZE10060SS	10	90	11	65	50	463.50



SHIELD ANCHORS

The torque-controlled shield anchor is suitable for use in brick and concrete, with the thick walls of the expanders giving the anchor its exceptional grip.

- ✓ Torque Controlled Expansion
- ✓ Medium To Heavy Duty Loads
- ✓ All Steel Anchor



M=Thread Diameter d_0 =Shield Hole Size t_{fix} =Maximum Fixture Thickness L=Length h_1 =Minimum Hole Depth



LOOSE BOLT SHIELD ANCHORS ZYP

- ✓ Non-Cracked Concrete C20/25 To C50/60
- ✓ Solid Concrete Blocks
- ✓ Solid Brickwork



ZINC AND
YELLOW PLATED

Part Number	Thread Diameter M	Shield Hole Size mm d_0	Max Fixture Thickness mm t_{fix}	Length Under Head mm L	Minimum Hole Depth mm h_1	Quantity Per Box	Price £ Per 100
ALB0610	6	12	10	55	50	50	37.14
ALB0625	6	12	25	70	50	50	38.38
ALB0640	6	12	40	85	50	50	45.07
ALB0810	8	14	10	60	55	50	51.50
ALB0825	8	14	25	75	55	50	54.97
ALB0840	8	14	40	90	55	50	58.93
ALB1010	10	16	10	70	65	50	81.22
ALB1025	10	16	25	85	65	50	86.17
ALB1050	10	16	50	110	65	50	92.61
ALB1075	10	16	75	135	65	25	104.00
ALB1210	12	20	10	85	85	25	134.70
ALB1225	12	20	25	100	85	25	139.66
ALB1240	12	20	40	115	85	25	146.09
ALB1260	12	20	60	135	85	25	157.49
ALB1615	16	25	15	135	125	10	323.39
ALB1630	16	25	30	150	125	10	336.76
ALB1660	16	25	60	180	125	10	364.00

RETAIL BAGS

Product Part Number	Bag Part Number	Size	Quantity Per Bag	Price £ Per Bag
ALB0610	JB8000	M6 x 10	10	5.91
ALB0625	JB8003	M6 x 25	10	6.37
ALB0810	JB8006	M8 x 10	6	5.48
ALB1025	JB8009	M8 x 25	6	5.91
ALB0840	JB8012	M8 x 40	6	6.37
ALB1010	JB8015	M10 x 10	4	5.91
ALB1025	JB8018	M10 x 25	4	6.37
ALB1050	JB8021	M10 x 50	4	6.81
ALB1075	JB8024	M10 x 75	4	7.69
ALB1210	JB8027	M12 x 10	2	5.03
ALB1225	JB8030	M12 x 25	2	5.48
ALB1260	JB8033	M12 x 60	2	6.37



TRADE BAGS

Product Part Number	Bag Part Number	Size	Quantity Per Bag	Price £ Per Bag
ALB0610	JP3147	M6 x 10	48	18.12
ALB0625	JP3150	M6 x 25	46	18.12
ALB0810	JP3153	M8 x 10	26	18.12
ALB1025	JP3156	M8 x 25	26	18.12
ALB0840	JP3159	M8 x 40	22	18.12
ALB1010	JP3162	M10 x 10	22	18.12
ALB1025	JP3165	M10 x 25	116	18.12
ALB1050	JP3168	M10 x 50	14	18.12
ALB1075	JP3171	M10 x 75	14	18.12
ALB1260	JP3174	M12 x 60	10	18.12



PROJECTING BOLT SHIELD ANCHORS ZYP

- ✓ Non-Cracked Concrete C20/25 To C50/60
- ✓ Solid Concrete Blocks
- ✓ Solid Brickwork



ZINC AND YELLOW PLATED

Part Number	Thread Diameter M	Shield Hole Size mm d ₀	Max Fixture Thickness mm t _{fix}	Overall Length mm L	Minimum Hole Depth mm h _i	Quantity Per Box	Price £ Per 100
APB0610	6	12	10	60	50	50	37.82
APB0625	6	12	25	75	50	50	40.24
APB0650	6	12	50	100	50	50	44.60
APB0815	8	14	15	75	55	50	55.27
APB0840	8	14	40	100	55	50	58.18
APB0880	8	14	80	140	55	25	63.03
APB1010	10	16	10	80	65	50	80.48
APB1030	10	16	30	100	65	50	89.69
APB1050	10	16	50	120	65	25	100.84
APB1070	10	16	70	140	65	25	109.08
APB1215	12	20	15	100	85	25	136.72
APB1225	12	20	25	110	85	25	143.99
APB1250	12	20	50	135	85	10	158.53
APB1270	12	20	70	155	85	10	173.08
APB1635	16	25	35	160	125	10	301.07

RETAIL BAGS

Product Part Number	Bag Part Number	Size	Quantity Per Bag	Price £ Per Bag
APB0610	JB8039	M6 x 10	6	4.15
APB0815	JB8042	M8 x 15	6	5.91
APB0880	JB8045	M8 x 80	4	5.48
APB1030	JB8048	M10 x 30	4	6.81
APB1070	JB8051	M10 x 70	4	7.69
APB1250	JB8054	M12 x 50	2	5.91



TRADE BAGS

Product Part Number	Bag Part Number	Size	Quantity Per Bag	Price £ Per Bag
APB1030	JP3177	M10 x 30	15	18.12



SHIELD ONLY SHIELD ANCHORS ZYP

ZINC AND YELLOW PLATED

☒ Non-Cracked Concrete C20/25 To C50/60
 ☒ Solid Concrete Blocks
 ☒ Solid Brickwork

Part Number	Thread Diameter M	Drill Hole Diameter mm d ₀	Max Fixture Thickness mm t _{fix}	Shield Length mm L	Minimum Hole Depth mm h _i	Quantity Per Box	Price £ Per 100
ASHOM06	6	12	-	45	50	50	25.60
ASHOM08	8	14	-	50	55	50	32.69
ASHOM10	10	16	-	60	65	50	45.07
ASHOM12	12	20	-	75	85	25	73.29
ASHOM16	16	25	-	110	125	10	153.52

SHIELD ONLY SHIELD ANCHORS A4 STAINLESS STEEL



A4-316 STAINLESS STEEL

☒ Non-Cracked Concrete C20/25 To C50/60
 ☒ Solid Concrete Blocks
 ☒ Solid Brickwork
 ☒ Suitable For External Use

Part Number	Thread Diameter M	Drill Hole Diameter mm d ₀	Max Fixture Thickness mm t _{fix}	Shield Length mm L	Minimum Hole Depth mm h _i	Quantity Per Box	Price £ Per 100
PSM06SS	6	12	-	45	50	25	279.05
PSM08SS	8	14	-	50	55	25	373.68
PSM10SS	10	16	-	60	65	25	495.00
PSM12SS	12	20	-	75	85	10	655.15



EYE BOLT SHIELD ANCHORS ZYP

ZINC AND
YELLOW PLATED

- ✓ Non-Cracked Concrete C20/25 To C50/60
- ✓ Forged Eye For Improved Strength
- ✓ Solid Concrete Blocks

Part Number	Thread Diameter	Drill Hole Diameter mm d_0	Eye Diameter mm	Overall Length mm L	Minimum Hole Depth mm h_1	Quantity Per Box	Price £ Per 100
AEBM06	6	12	10	80	50	25	78.02
AEBM08	8	14	11	95	55	25	102.71
AEBM10	10	16	14	115	65	10	140.97
AEBM12	12	20	16	130	85	10	216.03

RETAIL BAGS

Product Part Number	Bag Part Number	Size	Quantity Per Bag	Price £ Per Bag
AEBM08	JB8060	M8	4	6.81



HOOK BOLT SHIELD ANCHORS ZYP

ZINC AND
YELLOW PLATED

- ✓ Non-Cracked Concrete C20/25 To C50/60
- ✓ Forged Eye For Improved Strength
- ✓ Solid Concrete Blocks

Part Number	Thread Diameter	Drill Hole Diameter mm d_0	Eye Diameter mm	Overall Length mm L	Minimum Hole Depth mm h_1	Quantity Per Box	Price £ Per 100
AHBM06	6	12	8	80	50	25	78.02
AHBM08	8	14	10	95	55	25	102.71
AHBM10	10	16	12	115	65	10	140.97
AHBM12	12	20	16	145	85	10	216.03

JCP PRODUCTS ARE AVAILABLE TO ORDER VIA

owlett-jaton.com



FREE
NEXT-DAY
DELIVERY



MERCHANDISING
SOLUTIONS



COMPLETE
WHOLESALE
SOLUTION



FULL UK ASM
COVERAGE


FOR TECHNICAL ADVICE CALL OUR TECHNICAL HELPLINE ON 020 8943 1800



CONCRETE SCREWS

Countersunk head self-tapping screws, suitable for use in concrete, concrete blocks, and masonry.

- ☒ Reaction To Fire Class A1
 ☒ Fast And Secure Installation
 ☒ Good Performance
 ☒ Expansion Free



d_0 = Drill Diameter L = Screw Length t_{fix} = Maximum Fixture Thickness h_1 = Minimum Hole Depth



COUNTERSUNK HEAD CONCRETE SCREWS ZYP

**ZINC AND
YELLOW PLATED**

- ☒ Complete With White Cover Cap
 ☒ T30 Drive Bit Included*
 ☒ Locking Ribs Under Head
 ☒ Undercutting Action

Part Number	Drill Diameter mm d_0	Screw Length mm L	Max Fixture Thickness mm t_{fix}	Minimum Hole Depth mm h_1	Quantity Per Box	Price £ Per 1000
CS75040	6	40	-	45	100	69.15
CS75060	6	60	20	45	100	95.86
CS75080	6	80	40	45	100	123.14
CS75100	6	100	60	45	100	151.96
CS75120	6	120	80	45	100	182.13
CS75150	6	150	110	45	100	232.38
CS75180	6	180	140	45	100	286.78

RETAIL BAGS

Product Part Number	Bag Part Number	Size mm	Quantity Per Bag	Price £ Per Bag
CS75060A	JB8700	6 x 60	20	4.15
CS75080A	JB8703	6 x 80	20	5.48
CS75100A	JB8706	6 x 100	20	5.91
CS75120A	JB8709	6 x 120	10	4.59
CS75150A	JB8712	6 x 150	10	5.48



TRADE BAGS

Product Part Number	Part Number	Screw mm	Quantity Per Bag	Price £ Per Bag
CS75080A	JP3030	6 x 80	65	11.44
CS75100A	JP3033	6 x 100	55	11.44
CS75120A	JP3036	6 x 120	45	11.44
CS75150A	JP3039	6 x 150	30	11.44



* Not included in retail or trade bags



COUNTERSUNK HEAD CONCRETE SCREWS NO COVER CAPS ZYP

NEW SIZES ADDED

- ✓ Locking Ribs Under Head
- ✓ Undercutting Action

ZINC AND
YELLOW PLATED

Part Number	Drill Diameter mm d_0	Screw Length mm L	Max Fixture Thickness mm t_{fix}	Minimum Hole Depth mm h_1	Quantity Per Box	Price £ Per 1000
CS75040A	6	40	-	45	100	54.69
CS75050A	6	50	10	45	100	65.50
CS75060A	6	60	20	45	100	80.72
CS75070A	6	70	30	45	100	92.54
CS75080A	6	80	40	45	100	106.82
CS75090A	6	90	50	45	100	125.76
CS75100A	6	100	60	45	100	132.85
CS75110A	6	110	70	45	100	150.00
CS75120A	6	120	80	45	100	158.88
CS75130A	6	130	90	45	100	170.00
CS75150A	6	150	110	45	100	207.93
CS75180A	6	180	140	45	100	248.89
CS75200A	6	200	160	45	100	260.00
CS75250A	6	250	210	45	100	523.69
CS75300A	6	300	260	45	100	823.56

CONCRETE SCREW COVER CAPS

- ✓ Simply Pushes Into The Head Of The Screw
- ✓ Available In White Or Brown

Part Number	Colour	Quantity Per Box	Price £ Per 100
CSCAPWH	White	100	1.25
CSCAPBR	Brown	100	1.25



Technical data sheets can be found on the JCP website for products within the range.

The data sheets provide detailed information on the following; where applicable.

- ✓ Product information
- ✓ Load and range data
- ✓ Performance data
- ✓ Installation instructions
- ✓ Features
- ✓ Base material guidance
- ✓ Related products

www.jcpfixings.co.uk



FOR TECHNICAL ADVICE CALL OUR TECHNICAL HELPLINE ON 020 8943 1800



METALFIX SELF-DRILLING SCREWS

Self-drilling, self-tapping screws for fixing various materials to steel.


- ✓ High-Clamping Action
- ✓ Range With EDPM Washers To Provide Waterproof Seal
- ✓ Stainless Steel Provides Excellent Corrosion Resistance



METALFIX SELF-DRILLING SCREWS BZP

**BRIGHT ZINC
PLATED**

- ✓ For Fixing Steel To Steel
- ✓ Hexagon Head
- ✓ DIN 7504K
- ✓ C1022 Steel Case Hardened



LIGHT SECTION



HEAVY SECTION

Part Number	Thread Diameter mm d	Length mm L	Point Type	Steel Thickness t_{steel}	Max Fixture Thickness mm t_{fix}	Washer Diameter mm	Quantity Per Box	Price £ Per 100
LIGHT SECTION								
MFL55019	5.5	19	3	1.2-3.0	4	-	100	4.70
MFL55025	5.5	25	3	1.2-3.0	10	-	100	5.11
MFL55025	5.5	32	3	1.2-3.0	17	-	100	6.00
MFL55038	5.5	38	3	1.2-3.0	23	-	100	6.66
MFL55050	5.5	50	3	1.2-3.0	35	-	100	8.12
HEAVY SECTION								
MFH55022	5.5	22	4	3.0-6.0	5	-	100	5.79
MFH55032	5.5	32	5	4.0-12.5	5	-	100	7.82
MFH55040	5.5	40	5	4.0-12.5	13	-	100	9.35
MFH55050	5.5	50	5	4.0-12.5	23	-	100	10.55
MFH55060	5.5	60	5	4.0-12.5	33	-	100	12.41
MFH55070	5.5	70	5	4.0-12.5	43	-	100	14.05
MFH55080	5.5	80	5	4.0-12.5	53	-	100	15.90

RETAIL BAGS

Product Part Number	Bag Part Number	Size mm	Quantity Per Bag	Price £ Per Bag
LIGHT SECTION				
MFL55025	JB8815	5.5 x 25	30	3.73
MFL55038	JB8818	5.5 x 38	30	4.03
MFL55050	JB8821	5.5 x 50	30	4.46



TRADE BAGS

Product Part Number	Bag Part Number	Size mm	Quantity Per Bag	Price £ Per Bag
LIGHT SECTION				
MFL55025	JP3108	5.5 x 25	200	15.73
MFL55025	JP3111	5.5 x 32	160	15.73
MFL55038	JP3114	5.5 x 38	150	15.73
MFL55050	JP3117	5.5 x 50	150	15.73
HEAVY SECTION				
MFH55060	JP3125	5.5 x 60	150	15.73
MFH55070	JP3127	5.5 x 70	150	15.73
MFH55080	JP3128	5.5 x 80	150	15.73



METALFIX SELF-DRILLING SCREWS BI-METAL A2 STAINLESS STEEL

A2-304
STAINLESS STEEL

- ✓ For Fixing Steel To Steel ✓ Hexagon Head


Part Number	Thread Diameter mm d	Length mm L	Point Type	Steel Thickness t_{steel}	Max Fixture Thickness mm t_{fix}	Washer Diameter mm	Quantity Per Box	Price £ Per 100
LIGHT SECTION								
MFL55022SS	5.5	22	3	1.3-3.0	2	-	100	34.05
MFL55025SS	5.5	25	3	1.3-3.0	7	-	100	34.22
MFL55032SS	5.5	32	3	1.3-3.0	14	-	100	37.95
MFL55038SS	5.5	38	3	1.3-3.0	20	-	100	41.03
MFL55050SS	5.5	50	3	1.3-3.0	32	-	100	46.23
HEAVY SECTION								
MFH55032SS	5.5	32	5	4-12.5	3	-	100	44.57
MFH55038SS	5.5	38	5	4.0-12.5	8	-	100	52.11
MFH55050SS	5.5	50	5	4.0-12.5	20	-	100	58.19

HEAVY SECTION

METALFIX SELF-DRILLING SCREWS WITH 16MM WASHER BZP

BRIGHT ZINC
PLATED

- ✓ For Fixing Steel To Steel ✓ Supplied With 16mm Washer ✓ EPDM Washer To Prevent Water Ingress
✓ For General Purpose Applications ✓ Hexagon Head ✓ DIN 7504K ✓ C1022 Steel Case Hardened



Part Number	Thread Diameter mm d	Length mm L	Point Type	Steel Thickness t_{steel}	Max Fixture Thickness mm t_{fix}	Washer Diameter mm	Quantity Per Box	Price £ Per 100
LIGHT SECTION								
MFL55025W16	5.5	25	3	1.2-3.0	7	16	100	7.57
MFL55032W16	5.5	32	3	1.2-3.0	14	16	100	8.33
MFL55038W16	5.5	38	3	1.2-3.0	20	16	100	8.99
MFL55043W16	5.5	43	3	1.2-3.0	25	16	100	9.90
MFL55050W16	5.5	50	3	1.2-3.0	32	16	100	10.52
MFL55057W16	5.5	57	3	1.2-3.0	39	16	100	11.65
MFL55070W16	5.5	70	3	1.2-3.0	52	16	100	13.17
MFL55075W16	5.5	75	3	1.2-3.0	57	16	100	13.61
HEAVY SECTION								
MFH55022W16	5.5	22	4	3.0-6.0	2	16	100	8.30
MFH55032W16	5.5	32	5	4.0-12.5	2	16	100	10.01
MFH55040W16	5.5	40	5	4.0-12.5	10	16	100	11.72
MFH55050W16	5.5	50	5	4.0-12.5	20	16	100	12.92
MFH55060W16	5.5	60	5	4.0-12.5	30	16	100	14.70
MFH55070W16	5.5	70	5	4.0-12.5	40	16	100	16.19
MFH55080W16	5.5	80	5	4.0-12.5	50	16	100	17.98
MFH55100W16	5.5	100	5	4.0-12.5	70	16	100	22.89
MFH55120W16	5.5	120	5	4.0-12.5	90	16	100	26.86

RETAIL BAGS

Product Part Number	Bag Part Number	Size mm	Quantity Per Bag	Price £ Per Bag
LIGHT SECTION				
MFL55025W16	JB8800	5.5 x 25	30	4.03
MFL55032W16	JB8803	5.5 x 32	30	4.46
MFL55038W16	JB8806	5.5 x 38	20	3.73
MFL55050W16	JB8809	5.5 x 50	20	4.46
HEAVY SECTION				
MFH55032W16	JB8827	5.5 x 32	20	3.73
MFH55040W16	JB8830	5.5 x 40	20	4.03
MFH55050W16	JB8833	5.5 x 50	20	4.46



TRADE BAGS

Product Part Number	Bag Part Number	Size mm	Quantity Per Bag	Price £ Per Bag
LIGHT SECTION				
MFL55025W16	JP3120	5.5 x 25	140	15.73
MFL55038W16	JP3123	5.5 x 38	110	15.73
MFL55050W16	JP3126	5.5 x 50	85	15.73
HEAVY SECTION				
MFH55040W16	JP3129	5.5 x 40	100	15.73
MFH55060W16	JP3130	5.5 x 60	140	15.73
MFH55070W16	JP3131	5.5 x 70	140	15.73
MFH55080W16	JP3210	5.5 x 80	140	15.73
MFH55100W16	JP3133	5.5 x 100	100	15.73
MFH55120W16	JP3134	5.5 x 120	100	15.73



LIGHT SECTION



HEAVY SECTION

METALFIX SELF-DRILLING SCREWS WITH 16MM WASHER BI-METAL A2 STAINLESS STEEL

**A2-304
STAINLESS STEEL**

- ✓ For Fixing Steel To Steel
- ✓ Supplied With 16mm Washer
- ✓ EPDM Washer To Prevent Water Ingress
- ✓ For General Purpose Applications
- ✓ Hexagon Head


Part Number	Thread Diameter mm d	Length mm L	Point Type	Steel Thickness t _{steel}	Max Fixture Thickness mm t _{fix}	Washer Diameter mm	Quantity Per Box	Price £ Per 100
LIGHT SECTION								
MFL55022SSW16	5.5	22	3	1.2-3.0	2	16	100	40.54
MFL55025SSW16	5.5	25	3	1.2-3.0	7	16	100	40.55
MFL55032SSW16	5.5	32	3	1.2-3.0	14	16	100	44.23
MFL55038SSW16	5.5	38	3	1.2-3.0	20	16	100	48.06
MFL55050SSW16	5.5	50	3	1.2-3.0	32	16	100	53.25
HEAVY SECTION								
MFH55032SSW16	5.5	32	5	4-12.5	3	16	100	51.74
MFH55038SSW16	5.5	38	5	4.0-12.5	8	16	100	58.20
MFH55050SSW16	5.5	50	5	4.0-12.5	20	16	100	66.86



METALFIX SELF-DRILLING SCREWS WITH 19MM WASHER BZP

**BRIGHT ZINC
PLATED**

- ✓ For Fixing Steel To Steel
- ✓ Supplied With 19mm Washer
- ✓ EPDM Washer To Prevent Water Ingress
- ✓ For Roofing Applications
- ✓ Hexagon Head
- ✓ DIN 7504K
- ✓ C1022 Steel Case Hardened



d=Thread Diameter L=Length t_{steel} =Steel Thickness t_{fix} =Maximum Fixture Thickness


Part Number	Thread Diameter mm d	Length mm L	Point Type	Steel Thickness t_{steel}	Max Fixture Thickness mm t_{fix}	Washer Diameter mm	Quantity Per Box	Price £ Per 100
LIGHT SECTION								
MFL55025W19	5.5	25	3	1.2-3.0	7	19	100	8.19
MFL55032W19	5.5	32	3	1.2-3.0	14	19	100	9.21
MFL55038W19	5.5	38	3	1.2-3.0	20	19	100	10.34
MFL55050W19	5.5	50	3	1.2-3.0	32	19	100	12.01
MFL55075W19	5.5	75	3	1.2-3.0	57	19	100	14.92
HEAVY SECTION								
MFH55022W19	5.5	22	4	3.0-6.0	2	19	100	9.10
MFH55032W19	5.5	32	5	4.0-12.5	2	19	100	10.92
MFH55040W19	5.5	40	5	4.0-12.5	10	19	100	12.45
MFH55050W19	5.5	50	5	4.0-12.5	20	19	100	13.83
MFH55060W19	5.5	60	5	4.0-12.5	30	19	100	15.90
MFH55070W19	5.5	70	5	4.0-12.5	40	19	100	16.92
MFH55080W19	5.5	80	5	4.0-12.5	50	19	100	19.25
MFH55100W19	5.5	100	5	4.0-12.5	70	19	100	24.16
MFH55120W19	5.5	120	5	4.0-12.5	90	19	100	29.08



METALFIX GENERAL PURPOSE SELF-DRILLING SCREWS BZP

**BRIGHT ZINC
PLATED**

- ✓ For Fixing Steel To Steel
- ✓ Hexagon Head
- ✓ DIN 7504K
- ✓ C1022 Steel Case Hardened



d=Thread Diameter L=Length t_{steel} =Steel Thickness t_{fix} =Maximum Fixture Thickness


Part Number	Thread Diameter mm d	Length mm L	Point Type	Steel Thickness t_{steel}	Max Fixture Thickness mm t_{fix}	Washer Diameter mm	Across Flats "	Quantity Per Box	Price £ Per 100
GP42013	4.2	13	2	1.2-2.5	5	-	1/4 (7mm)	200	2.39
GP42016	4.2	16	2	1.2-2.5	8	-	1/4 (7mm)	200	2.52
GP42019	4.2	19	2	1.2-2.5	11	-	1/4 (7mm)	200	2.77
GP42025	4.2	25	2	1.2-2.5	17	-	1/4 (7mm)	200	3.17
GP48016	4.8	16	3	1.2-3.0	2	-	5/16 (8mm)	100	3.43
GP48019	4.8	19	3	1.2-3.0	5	-	5/16 (8mm)	100	3.75
GP48025	4.8	25	3	1.2-3.0	11	-	5/16 (8mm)	100	4.18



METALFIX LOOSE WASHERS BZP

**BRIGHT ZINC
PLATED**

- ✓ For Use With Self-Drilling Screw ✓ 1mm Steel With A 2mm Bonded EPDM Backing ✓ Creates A Watertight Seal



D=Washer Diameter

Part Number	Thread Diameter mm	Washer Diameter mm D	Quantity Per Box	Price £ Per 100
MFW16	6	16	100	3.93
MFW19	6	19	100	5.05

RETAIL BAGS

Product Part Number	Bag Part Number	Size mm	Quantity Per Bag	Price £ Per Bag
MFW16	JB8839	16	50	3.03
MFW19	JB8842	19	50	3.52



METALFIX LOOSE WASHERS A2 STAINLESS STEEL

**A2-304
STAINLESS STEEL**

- ✓ For Use With Self-Drilling Screws ✓ 1mm A2 Stainless Steel With A 2mm Bonded EPDM Backing
✓ Creates A Watertight Seal

D=Washer Diameter


Part Number	Hole Diameter mm	Washer Diameter mm D	Quantity Per Box	Price £ Per 100
MFW16SS	6	16	100	6.03
MFW19SS	6	19	100	7.17



METALFIX POZI PAN HEAD SELF-DRILLING SCREWS BZP

**BRIGHT ZINC
PLATED**

- ✓ For Fixing Steel To Steel ✓ DIN 7504N ✓ C1022 Steel Case Hardened



d=Thread Diameter L=Length t_{steel} =Steel Thickness t_{fix} =Maximum Fixture Thickness


Part Number	Thread Diameter mm d	Length mm L	Point Type	Steel Thickness t_{steel}	Max Fixture Thickness mm t_{fix}	Washer Diameter mm	Quantity Per Box	Price £ Per 100
PH35095	3.5	9.5	2	1.2-2.5	1	-	200	1.73
PH35013	3.5	13	2	1.2-2.5	5	-	200	1.87
PH35019	3.5	19	2	1.2-2.5	11	-	200	2.16
PH42013	4.2	13	2	1.2-2.5	5	-	200	2.40
PH42016	4.2	16	2	1.2-2.5	8	-	200	2.60
PH42019	4.2	19	2	1.2-2.5	11	-	200	2.82
PH42025	4.2	25	2	1.2-2.5	17	-	200	3.26
PH48013	4.8	13	3	1.2-3.0	2	-	200	3.10
PH48019	4.8	19	3	1.2-3.0	5	-	200	3.62
PH48025	4.8	25	3	1.2-3.0	11	-	200	4.31



METALFIX STITCHING SCREWS BZP WITH GALVANISED WASHER

**BRIGHT ZINC
PLATED**

- ✓ For Joining Two Thin Sheets Of Steel
- ✓ Supplied With 16mm Or 19mm Washer
- ✓ EPDM Washer To Prevent Water Ingress
- ✓ Hexagon Head
- ✓ DIN 7504K
- ✓ Larger Diameter To Give Better Grip In Steel



d=Thread Diameter L=Length t_{steel} =Steel Thickness D=Washer Diameter

Part Number	Thread Diameter mm d	Length mm L	Point Type	Steel Thickness t_{steel}	Washer Diameter mm D	Quantity Per Box	Price £ Per 100
SS63022W16	6.3	22	1	2 x 0.9	16	100	8.25
SS63025W16	6.3	25	1	2 x 1.2	16	100	8.39
SS63022W19	6.3	22	1	2 x 0.9	19	100	9.22
SS63025W19	6.3	25	1	2 x 1.2	19	100	9.36

Maximum Fixture Thickness allows for Maximum Steel Thickness

RETAIL BAGS

Product Part Number	Bag Part Number	Size mm	Quantity Per Bag	Price £ Per Bag
SS63025W16	JB8857	6.3 x 25	30	4.03



TRADE BAGS

Product Part Number	Bag Part Number	Size mm	Quantity Per Bag	Price £ Per Bag
SS63025W16	JP3132	6.3 x 25	120	15.73



METALFIX STITCHING SCREWS A2 STAINLESS STEEL

**A2-304
STAINLESS STEEL**


- ✓ For Joining Two Thin Sheets of Steel
- ✓ Supplied With 16mm Washer
- ✓ EPDM Washer To Prevent Water Ingress
- ✓ Hexagon Head
- ✓ Larger Diameter To Give Better Grip In Steel

Part Number	Thread Diameter mm d	Length mm L	Point Type	Steel Thickness t_{steel}	Max Fixture Thickness mm	Washer Diameter mm D	Quantity Per Box	Price £ Per 100
SS63025SSW16	6.3	25	1	2 x 0.9	16	16	100	46.60
SS63035SSW16	6.3	35	1	2 x 1.2	16	16	100	53.45

METALFIX HIGH-THREAD SELF-DRILLING SCREWS BZP WITH GALVANISED WASHER

**BRIGHT ZINC
PLATED**

- ✓ For Fixing Composite Panels To Steel
- ✓ Supplied With 19mm Washer
- ✓ EPDM Washer To Prevent Water Ingress
- ✓ Hexagon Head




d=Thread Diameter L=Length t_{fix} =Insulation Thickness

Part Number	Thread Diameter mm d	Length mm L	Point Type	Steel Thickness	Insulation Thickness mm t_{fix}	Washer Diameter mm	Quantity Per Box	Price £ Per 100
LIGHT SECTION								
HT55065	5.5	65	3	1.2-3.0	30-45	19	100	18.06
HT55070	5.5	70	3	1.2-3.0	35-50	19	100	18.60
HT55075	5.5	75	3	1.2-3.0	40-55	19	100	19.27
HT55085	5.5	85	3	1.2-3.0	40-60	19	100	22.13
HT55100	5.5	100	3	1.2-3.0	45-75	19	100	24.10
HT55125	5.5	125	3	1.2-3.0	75-100	19	100	32.42
HT55150	5.5	150	3	1.2-3.0	90-120	19	100	36.49
HEAVY SECTION								
HTH55075	5.5	75	5	4.0-12.5	30-45	19	100	21.75
HTH55105	5.5	105	5	4.0-12.5	50-64	19	100	29.52
HTH55130	5.5	130	5	4.0-12.5	60-95	19	100	36.07

METALFIX LOW PROFILE SELF-DRILLING SCREWS BZP

**BRIGHT ZINC
PLATED**

- ✓ For Fixing Steel To Steel
- ✓ Large Head For Increased Clamping
- ✓ Coarse Thread For Improved Grip And Pull Out



d=Thread Diameter L=Length t_{steel} =Steel Thickness t_{fix} =Maximum Fixture Thickness


Part Number	Thread Diameter mm d	Length mm L	Point Type	Steel Thickness t_{steel}	Max Fixture Thickness mm t_{fix}	Head Diameter mm	Quantity Per Box	Price £ Per 100
LIGHT SECTION								
LLP48016	4.8	16	3	1.2-2.5	8	11	200	8.56
LLP48025	4.8	25	3	1.2-2.5	17	11	200	9.57
LLP48030	4.8	30	3	1.2-2.5	22	11	200	10.08
LLP48040	4.8	40	3	1.2-2.5	32	11	100	11.46
HEAVY SECTION								
HLP55020	5.5	20	3	1.2-3.5	5	11	200	9.44
HLP55040	5.5	40	3	1.2-3.5	25	11	100	12.76



WAFER HEAD SELF-DRILLING SCREWS BZP

**BRIGHT ZINC
PLATED**

- ✓ For Fixing Steel To Steel
- ✓ Low Profile Wafer Head For Larger Bearing Surface
- ✓ Sharp Point Designed To Penetrate Effectively
- ✓ Fine Thread Ensures Strong Connection



d=Thread Diameter L=Length t_{steel} =Steel Thickness t_{fix} =Maximum Fixture Thickness

Part Number	Thread Diameter mm d	Length mm L	Point Type	Steel Thickness t_{steel}	Max Fixture Thickness mm t_{fix}	Head Diameter mm	Quantity Per Box	Price £ Per 100
WH4213	4.2	13	2	1.2-2.5	2	11	200	2.52
WH4816	4.8	16	3	1.2-3.0	3	11	100	3.95
WH5520	5.5	20	3	1.2-3.0	5	12	100	6.15
WH5540	5.5	40	3	1.2-3.0	24	12	100	8.95

RETAIL BAGS

Product Part Number	Bag Part Number	Size mm	Quantity Per Bag	Price £ Per Bag
WH4213	JB8893	4.2 x 13	30	2.45



METALFIX MAGNETIC SOCKETS BZP

**BRIGHT ZINC
PLATED**

- ✓ Magnetic To Hold Screw in Place

Part Number	Size "	Quantity Per Box	Price £ Per 100
MF516	5/16	1	221.00

RETAIL BAGS

Product Part Number	Bag Part Number	Size "	Quantity Per Bag	Price £ Per Bag
MF516	JB8899	5/16	1	4.03





WOODFIX SELF-DRILLING SCREWS

Self-drilling, self-tapping screws for fixing timber to steel, or fixing into timber.


- ✓ High-Clamping Action
- ✓ Range With EDPM Washers To Provide Waterproof Seal
- ✓ Stainless Steel Provides Excellent Corrosion Resistance



WOODFIX SELF-DRILLING SCREWS BZP

**BRIGHT ZINC
PLATED**

- ✓ For Fixing Timber To Steel
- ✓ Countersunk Head Gives Flush Finish
- ✓ DIN 7504P
- ✓ Wings Drill A Clearance Hole To Prevent The Timber Jacking
- ✓ C1022 Steel Case Hardened



L=Length t_{steel} =Steel Thickness t_{fix} =Maximum Fixture Thickness

Part Number	Thread Diameter mm	Length mm L	Point Type	Steel Thickness t_{steel}	Max Fixture Thickness mm t_{fix}	Washer Diameter mm	Quantity Per Box	Price £ Per 100
LIGHT SECTION								
WFL55040	5.5	40	3	1.2-3.0	22	-	100	7.14
WFL55050	5.5	50	3	1.2-3.0	32	-	100	8.31
WFL55060	5.5	60	3	1.2-3.0	42	-	100	9.71
WFL55080	5.5	80	3	1.2-3.0	62	-	100	13.71
WFL55100	5.5	100	3	1.2-3.0	82	-	100	17.28
WFL55110	5.5	110	3	1.2-3.0	92	-	100	21.11
WFL55120	5.5	120	3	1.2-3.0	112	-	100	24.55
HEAVY SECTION								
WFH55050	5.5	50	5	4.0-12.5	23	-	100	11.00
WFH55060	5.5	60	5	4.0-12.5	33	-	100	12.67
WFH55070	5.5	70	5	4.0-12.5	43	-	100	14.27
WFH55085	5.5	85	5	4.0-12.5	58	-	100	17.91
WFH55109	5.5	109	5	4.0-12.5	82	-	100	23.23
WFH55120	5.5	120	5	4.0-12.5	92	-	100	30.36

RETAIL BAGS

Product Part Number	Bag Part Number	Size mm	Quantity Per Bag	Price £ Per Bag
LIGHT SECTION				
WFL55040	JB8863	5.5 x 40	30	3.73
WFL55050	JB8866	5.5 x 50	30	4.03
WFL55060	JB8869	5.5 x 60	20	3.52
WFL55080	JB8872	5.5 x 80	20	4.46
WFL55100	JB8875	5.5 x 100	20	5.74
HEAVY SECTION				
WFH55060	JB8881	5.5 x 60	20	3.18
WFH55085	JB8884	5.5 x 85	20	4.21
WFH55109	JB8887	5.5 x 109	20	5.22



TRADE BAGS


Product Part Number	Bag Part Number	Size mm	Quantity Per Bag	Price £ Per Bag
LIGHT SECTION				
WFL55040	JP3135	5.5 x 40	100	15.73
WFL55050	JP3138	5.5 x 50	100	15.73
WFL55060	JP3141	5.5 x 60	100	15.73
WFL55080	JP3144	5.5 x 80	100	15.73
WFL55100	JP3146	5.5 x 120	100	15.73
HEAVY SECTION				
WFH55120	JP3230	5.5 x 120	100	15.73



WOODFIX GASH POINT SELF-DRILLING SCREWS BZP WITH GALVANISED WASHER

BRIGHT ZINC PLATED

- ✓ For Fixing Steel To Timber
- ✓ Supplied With 16mm Or 19mm Washer
- ✓ EPDM Washer To Prevent Water Ingress
- ✓ Gash Point For Quick Penetration
- ✓ Hexagon Head
- ✓ Sharp Threads Ensure A Low Torque And Strong Fixing



d=Thread Diameter L=Length t_{steel} =Steel Thickness t_{fix} =Maximum Fixture Thickness

Part Number	Thread Diameter mm d	Length mm L	Steel Thickness t_{steel}	Max Fixture Thickness mm t_{fix}	Washer Diameter mm D	Quantity Per Box	Price £ Per 100
GP6303216W	6.3	32	0.7-1.4	1	16	100	10.44
GP6304516W	6.3	45	0.7-1.4	5	16	100	12.53
GP6306016W	6.3	60	0.7-1.4	15	16	100	15.46
GP6308016W	6.3	80	0.7-1.4	35	16	100	19.16
GP6310016W	6.3	100	0.7-1.4	55	16	100	22.13
GP6312516W	6.3	125	0.7-1.4	80	16	100	29.74
GP6302519W	6.3	25	0.7-1.4	1	19	100	10.32
GP6303219W	6.3	32	0.7-1.4	1	19	100	11.50
GP6304519W	6.3	45	0.7-1.4	5	19	100	13.33
GP6306019W	6.3	60	0.7-1.4	15	19	100	17.02
GP6308019W	6.3	80	0.7-1.4	35	19	100	21.02
GP6310019W	6.3	100	0.7-1.4	55	19	100	25.63
GP6312519W	6.3	125	0.7-1.4	80	19	100	32.87
GP6315019W	6.3	150	0.7-1.4	105	19	100	41.09

RETAIL BAGS

Product Part Number	Bag Part Number	Size mm	Quantity Per Bag	Price £ Per Bag
GP6303216W	JB8848	6.3 x 32	30	4.46
GP6304516W	JB8851	6.3 x 45	30	5.32



TRADE BAGS

Product Part Number	Bag Part Number	Size mm	Quantity Per Bag	Price £ Per Bag
GP6303216W	JP3102	6.3 x 32	120	15.73
GP6304516W	JP3105	6.3 x 45	90	15.73





WOODFIX SELF-DRILLING SCREWS BI-METAL A2 STAINLESS STEEL

**A2-304
STAINLESS STEEL**

- ✓ For Fixing Timber To Steel
- ✓ Countersunk Head For Flush Finish
- ✓ Wings Drill A Clearance Hole To Prevent The Timber Jacking


Part Number	Thread Diameter mm d	Length mm L	Point Type	Steel Thickness t_{steel}	Max Fixture Thickness mm t_{fix}	Quantity Per Box	Price £ Per 100
LIGHT SECTION							
WFL55040SS	5.5	40	3	1.2-3.0	22	100	49.22
WFL55050SS	5.5	50	3	1.2-3.0	32	100	52.53
WFL55060SS	5.5	60	3	1.2-3.0	42	100	57.30
WFL55080SS	5.5	80	3	1.2-3.0	62	100	65.47



WOODFIX HIGH-THREAD SELF-DRILLING SCREWS FOR TIMBER BZP

**BRIGHT ZINC
PLATED**

- ✓ For Fixing Composite Panels To Timber
- ✓ DIN 7504P
- ✓ C1022 Steel Case Hardened



d=Thread Diameter L=Length t_{fix} =Maximum Fixture Thickness

Part Number	Thread Diameter mm d	Length mm L	Point Type	Thread Length mm L	Max Fixture Thickness mm t_{fix}	Washer Diameter mm	Quantity Per Box	Price £ Per 100
HTW63060	6.3	60	-	40	10	19	100	18.10
HTW63080	6.3	80	-	40	30	19	100	21.50
HTW63100	6.3	100	-	50	50	19	100	27.50
HTW63125	6.3	125	-	50	75	19	100	35.50
HTW63150	6.3	150	-	50	100	19	100	45.25



WOODFIX DRIVE BIT BZP

**BRIGHT ZINC
PLATED**

- ✓ PH3 Drive Bit
- ✓ Heat Treated For Longer Life

Part Number	Quantity Per Box	Price £ Per 100
WFPH3	10	31.53



FIBRE CEMENT SCREWS

Self-drilling, self-tapping screws for fixing various materials to steel or timber.


- ✓ High-Clamping Action
- ✓ Range With EDPM Washers To Provide Waterproof Seal
- ✓ Gash Points For Fixing Steel To Wood
- ✓ Stainless Steel Provides Excellent Corrosion Resistance



FIBRE CEMENT SCREWS FOR STEEL BZP WITH A2 STAINLESS STEEL AND BLACK NEOPRENE WASHER

BRIGHT ZINC PLATED

- ✓ For Fixing Fibre Cement Profiles To Steel
- ✓ Supplied With Washer For Watertight Fixing
- ✓ Reamer On Shank Makes A Clearance To Allow Sheet Expansion And Contraction



d=Thread Diameter L=Length t_{fix} =Maximum Fixture Thickness

LIGHT SECTION


HEAVY SECTION

Part Number	Thread Diameter mm d	Length mm L	Point Type	Steel Thickness	Max Fixture Thickness mm t_{fix}	Washer Diameter mm	Quantity Per Box	Price £ Per 100
LIGHT SECTION								
FCL63110	6.3	110	3	1.2-3.0	75	22/25	50	45.06
FCL63125	6.3	125	3	1.2-3.0	95	22/25	50	49.76
FCL63155	6.3	155	3	1.2-3.0	125	22/25	50	64.29
FCL63175	6.3	175	3	1.2-3.0	145	22/25	50	73.01
FCL63195	6.3	195	3	1.2-3.0	165	22/25	50	84.31
FCL63230	6.3	230	3	1.2-3.0	200	22/25	50	118.39
HEAVY SECTION								
FCH63110	6.3	110	5	4.0-12.5	75	22/25	50	47.96
FCH63130	6.3	130	5	4.0-12.5	95	22/25	50	51.16
FCH63150	6.3	150	5	4.0-12.5	120	22/25	50	62.89
FCH63180	6.3	180	5	4.0-12.5	145	22/25	50	80.00
FCH63200	6.3	200	5	4.0-12.5	165	22/25	50	100.52
FCH63235	6.3	235	5	4.0-12.5	200	22/25	50	132.74

FIBRE CEMENT SCREWS FOR TIMBER BZP WITH A2 STAINLESS STEEL AND BLACK NEOPRENE WASHER

BRIGHT ZINC PLATED

- ✓ For Fixing Fibre Cement Profiles To Wood
- ✓ Supplied With Washer For Watertight Fixing
- ✓ Reamer On Shank Makes A Clearance To Allow Sheet Expansion And Contraction



d=Thread Diameter L=Length t_{fix} =Maximum Fixture Thickness

Part Number	Thread Diameter mm d	Length mm L	Thread Length mm	Max Fixture Thickness mm t_{fix}	Washer Diameter mm	Quantity Per Box	Price £ Per 100
FCW63110	6.3	110	65	60	22/25	50	44.70
FCW63130	6.3	130	65	80	22/25	50	49.65
FCW63150	6.3	150	90	100	22/25	50	59.50



COVER CAPS

A range of coloured cover caps to suit hexagon head self-drilling screws.

- ✓ Colour Coded To British Standard
- ✓ Push Fit Over 16mm And 19mm Washers
- ✓ Provide An Additional Weather Seal



COLOURED COVER CAPS

Part Number 16mm Washer	Part Number 19mm Washer	Colour	Quantity Per Bag	Price £ Per 100
MFC16AN	MFC19AN	Anthracite (18A14)	1000	4.50
MFC16BL	MFC19BL	Black (00E53)	1000	4.50
MFC16GG	MFC19GG	Goosewing Light Grey (10A05)	1000	4.50
MFC16JG	MFC19JG	Juniper Green (12B29)	1000	4.50
MFC16MG	MFC19MG	Merlin Dark Grey (18B25)	1000	4.50
MFC16MO	MFC19MO	Moorland Green (12B21)	1000	4.50
MFC16MU	MFC19MU	Mushroom (10B19)	1000	4.50
MFC16OB	MFC19OB	Ocean Blue (18C39)	1000	4.50
MFC16OG	MFC19OG	Olive Green (12B27)	1000	4.50
MFC16PR	MFC19PR	Poppy Red (04E53)	1000	4.50
MFC16SB	MFC19SB	Slate Blue (18B29)	1000	4.50
MFC16SG	MFC19SG	Slate Grey (18B27)	1000	4.50
MFC16VB	MFC19VB	Vandyke Brown (08B29)	1000	4.50
MFC16WH	MFC19WH	White (00E55)	1000	4.50





INTERNAL THREADED SELF-DRILLING SCREWS

Internally threaded sockets for hanging vertically threaded rods, and internal threaded screws for fixing horizontally into purlins and steel or timber.


- ✓ One Piece Internally Threaded Fastening System ✓ All Steel ✓ Gash Point For Fixing Into Timber



METALFIX VERTICAL HANGERS BZP

**BRIGHT ZINC
PLATED**

- ✓ For Hanging Threaded Rods From Purlins, Light Steel Or Heavy Steel
✓ Fast Overhead Installation With A Screwgun ✓ Supplied Complete With Back-Nut For Additional Security



LIGHT SECTION

d=Thread Diameter L=Length



HEAVY SECTION


Part Number	Thread Diameter " d	Length mm L	Point Type	Steel Thickness	Internal Thread Diameter M	Across Flats " A/F	Quantity Per Box	Price £ Per 100
LIGHT SECTION								
MFL55M1025V	1/4	25	3	1.2-3.0	10	5/8	100	71.46
MFL55M1038V	1/4	38	3	1.2-3.0	10	5/8	100	73.36
HEAVY SECTION								
MFH55M1032V	12g	38	5	4.0-12.5	10	5/8	100	76.27



METALFIX HORIZONTAL HANGERS BZP

**BRIGHT ZINC
PLATED**

- ✓ For Hanging Threaded Rods From Purlins, Light Steel Or Heavy Steel
✓ Fast Overhead Installation With A Screwgun ✓ Supplied Complete With Back-Nut For Additional Security



d=Thread Diameter L=Length

LIGHT SECTION




HEAVY SECTION

Part Number	Thread Diameter " d	Length mm L	Point Type	Steel Thickness	Internal Thread Diameter mm	Across Flats " A/F	Quantity Per Box	Price £ Per 100
LIGHT SECTION								
MFL55M0825H	1/4	25	3	1.2-3.0	8	5/8	100	94.49
MFL55M1025H	1/4	25	3	1.2-3.0	10	5/8	100	93.53
MFL55M1038H	1/4	38	3	1.2-3.0	10	5/8	100	96.40
HEAVY SECTION								
MFH55M1032H	12g	38	5	4.0-12.5	10	5/8	100	94.71



GASH POINT VERTICAL HANGERS BZP

- ✓ For Fixing Into Timber For Suspending Threaded Rod
- ✓ Fast Overhead Installation With A Screwgun
- ✓ Gash Point For Self-Drilling



d=Thread Diameter L=Length t_{steel} =Steel Thickness


**BRIGHT ZINC
PLATED**

Part Number	Thread Diameter " d	Length mm L	Point Type	Steel Thickness t_{steel}	Internal Thread Diameter M	Across Flats " A/F	Quantity Per Box	Price £ Per 100
GP63M0825V	1/4	25	-	0.7-1.4	8	5/8	100	70.35
GP63M0850V	1/4	50	-	0.7-1.4	8	5/8	100	72.97
GP63M1025V	1/4	25	-	0.7-1.4	10	5/8	100	67.01
GP63M1050V	1/4	50	-	0.7-1.4	10	5/8	100	69.71
GP79M1063V	1/3	63	-	0.7-1.4	10	5/8	100	79.79



GASH POINT HORIZONTAL HANGERS BZP

- ✓ For Fixing Into Timber For Suspending Threaded Rod
- ✓ Fast Overhead Installation With A Screwgun
- ✓ Gash Point For Self-Drilling



d=Thread Diameter L=Length t_{steel} =Steel Thickness

**BRIGHT ZINC
PLATED**

Part Number	Thread Diameter " d	Length mm L	Point Type	Steel Thickness t_{steel}	Internal Thread Diameter M	Across Flats " A/F	Quantity Per Box	Price £ Per 100
GP63M0825H	1/4	25	-	0.7-1.4	8	5/8	100	89.11
GP63M1025H	1/4	25	-	0.7-1.4	10	5/8	100	88.04
GP63M1050H	1/4	50	-	0.7-1.4	10	5/8	100	93.13



SETTING TOOL FOR ROD HANGERS BZP

- ✓ Install And Remove Internally Threaded Self-Drilling Rod Hangers
- ✓ 5/8" A/F

Part Number	Quantity Per Box	Price £ Per Each
MF508RH	5	5.96

**BRIGHT ZINC
PLATED**

NEW TO THE RANGE



FSDU STANDS



SIZE: 1496 X 419 X 293mm

- ✓ IDEAL FOR SMALL AREAS
- ✓ EASY TO BUILD AND RE-STOCK

Owlett-Jaton


MORE STOCK PROFILES COMING SOON



NAIL IN ANCHORS

A steel hammer-in fixing suitable for most solid base materials including reinforced concrete, concrete blocks, brickwork and natural stone. Nail in anchors are non-removable and therefore vandal-proof.

- ✓ No Setting Tool Required
- ✓ Internally Tapered Body Gives Exceptional Grip
- ✓ Through Fixing
- ✓ Non-Cracked Concrete
- ✓ Hammer-In Expansion



NAIL IN ANCHORS METAL

METAL

- ✓ Suitable For Most Solid Base Materials
- ✓ Flush Finish
- ✓ Large Head Diameter Offers High Pull Over Strength For Thin Straps Or Brackets

Part Number	Anchor Hole Size mm d_0	Total Anchor Length mm L	Max Fixture Thickness mm t_{fix}	Flange Head Diameter mm	Quantity Per Box	Price £ Per 100
MDA06040	6	40	5	15	100	12.36
MDA06065	6	65	30	15	100	21.24



NAIL IN ANCHORS ALLOY

ALLOY

- ✓ Suitable For Most Solid Base Materials
- ✓ Dome Flange Head

Part Number	Anchor Hole Size mm d_0	Total Anchor Length mm L	Max Fixture Thickness mm t_{fix}	Flange Head Diameter mm	Quantity Per Box	Price £ Per 100
LANI06030	6	30	10	13	100	16.54
LANI06040	6	40	20	13	100	20.92
LANI06050	6	50	30	13	100	24.30



NAIL IN ANCHORS STEEL

STEEL

- ✓ Suitable For Most Solid Base Materials
- ✓ Increased Fire Resistance
- ✓ Dome Flange Head


Part Number	Anchor Hole Size mm d_0	Total Anchor Length mm L	Max Fixture Thickness mm t_{fix}	Flange Head Diameter mm	Quantity Per Box	Price £ Per 100
MNI06030	6	30	10	13	100	33.78
MNI06040	6	40	20	13	100	35.08
MNI06050	6	50	30	13	100	38.75



CONSTRUCTION NAILS

Stainless steel and steel nails for building construction.

- ✓ Masonry Nails For Use In Concrete And Block
- ✓ Plastic Headed Nails For Use In Windows, Soffits And Fascias



L=Length d=Shank Diameter



PLASTIC HEADED NAILS

**A4-316
STAINLESS STEEL**

- ✓ Available With Black Or White Heads To Match Soffit
- ✓ HDPE Impact Resistant Poly Head
- ✓ Annular Ring Shank Design
- ✓ UV Factor 5 Stabilised
- ✓ Maintenance Free
- ✓ Suitable For External Use And Marine Environments

Part Number	Shank Length mm L	Shank Diameter mm d	Head Colour	Quantity Per Box	Price £ Per 100
POLY030WH	30	2.00	White	250	7.75
POLY040WH	40	2.00	White	250	8.79
POLY050WH	50	2.65	White	100	16.17
POLY065WH	65	3.35	White	100	23.79
POLY030BL	30	2.00	Black	250	7.21
POLY040BL	40	2.00	Black	250	8.38
POLY050BL	50	2.65	Black	100	15.08
POLY065BL	65	3.35	Black	100	22.92

RETAIL BAGS

Product Part Number	Bag Part Number	Colour	Size mm	Quantity Per Bag	Price £ Per Bag
POLY030WH	JB8937	White	2 x 30	25	3.05
POLY040WH	JB8940	White	2 x 40	25	3.29
POLY030BL	JB8931	Black	2 x 30	25	3.05
POLY040BL	JB8934	Black	2 x 40	25	3.29





MASONRY NAILS WITH WASHER BZP

**BRIGHT ZINC
PLATED**

- ✓ Manufactured From Austempered High Carbon Steel
- ✓ Hardened And Tempered
- ✓ Complete With Washer For Greater Pull Over
- ✓ Oil Bathed
- ✓ 8mm Diameter Washer

Part Number	Length mm L	Shank Diameter mm d	Quantity Per Box	Price £ Per 100
AMNL025MP	25	2.5	200	7.65
AMNL030MP	30	2.5	200	8.16



MASONRY NAILS BZP

**BRIGHT ZINC
PLATED**

- ✓ Hardened And Tempered
- ✓ Manufactured From Austempered High Carbon Steel
- ✓ Versatile Nail Set By Hammer
- ✓ Oil Bathed

Part Number	Length mm L	Shank Diameter mm d	Quantity Per Box	Price £ Per 100
LIGHT SHANK - COUNTERSUNK HEAD				
AMNL025	25	2.5	100	2.21
AMNL040	40	2.5	100	3.23
AMNL050	50	2.5	100	3.70
AMNL060	60	2.5	100	4.17
MEDIUM SHANK - COUNTERSUNK HEAD				
AMNM025	25	3.0	100	3.02
AMNM030	30	3.0	100	3.36
AMNM040	40	3.0	100	4.04
AMNM050	50	3.0	100	5.14
AMNM060	60	3.0	100	5.65
HEAVY SHANK - ROUND HEAD				
AMNH050	50	3.5	100	6.50
AMNH060	60	3.5	100	7.23
AMNH075	75	3.5	100	8.88
AMNH090	90	3.5	100	10.75
AMNH100	100	3.5	100	11.31

RETAIL BAGS

Product Part Number	Bag Part Number	Size mm	Quantity Per Bag	Price £ Per Bag
LIGHT SHANK				
AMNL025	JB8900	2.5 x 25	30	2.37
AMNL060	JB8903	2.5 x 60	25	2.37
AMNL040	JB8906	2.5 x 40	20	2.37
MEDIUM SHANK				
AMNM050	JB8909	3.0 x 50	14	2.37
AMNM060	JB8912	3.0 x 60	12	2.37
HEAVY SHANK				
AMNH075	JB8915	3.5 x 75	7	2.37






SANITARY FIXINGS

Complete fixing sets for wash basins, urinals, and sanitary installations.

✓ Complete With Cover Caps



BASIN FIXINGS

STEEL

Part Number	Screw Size mm	Plug Size mm	Anchor Hole Diameter mm d_0	Individual Quantity Per Box	Individual £ Price Per 100	Price £ Per Bag of 2
NBFS10140	10 x 140	14 x 70	14	10	83.33	1.67

RETAIL BAGS

Product Part Number	Bag Part Number	Size mm	Quantity Per Bag	Price £ Per Bag
NBFS10140	JB8945	10 x 140	2	4.15



W.C. FIXINGS

STEEL

Part Number	Screw Size mm	Plug Size mm	Colour	Anchor Hole Diameter mm d_0	Individual Quantity Per Box	Individual £ Price Per 100	Price £ Per Bag of 2
NWCW06070	6.0 x 70	8 x 40	White	8	50	55.17	1.10
NWCC06070	6.0 x 70	8 x 40	Chrome	8	50	55.17	1.10

RETAIL BAGS

Product Part Number	Bag Part Number	Colour	Size mm	Quantity Per Bag	Price £ Per Bag
NWCW06070	JB8948	White	6 x 70	2	3.25
NWCC06070	JB8951	Chrome	6 x 70	2	3.25






BRACKETS

Vertical flange clips ideal for fixing suspended wire hangers to steel profiles.
Angle brackets for suspending lightweight ceilings and services.

- ✓ Flexible Positioning
- ✓ High Strength
- ✓ Simple Installation



VERTICAL FLANGE CLIPS ZYP

- ✓ Fixes To A Range Of Steel Profiles
- ✓ Projecting Lugs For Secure Attachment
- ✓ Spring Steel Clip
- ✓ No Screws Required
- ✓ High Strength Steel



**ZINC AND
YELLOW PLATED**

Part Number	Size mm	Min Purlin Gauge mm	Max Purlin Gauge mm	Height mm	Width mm	Quantity Per Box	Price £ Per 100
VFC1	20 x 42	1.6	2.5	42	20	100	11.50

ANGLE BRACKETS BZP

- ✓ Can Be Attached To Any Base Material
- ✓ Small And Lightweight
- ✓ Mild Steel

**BRIGHT ZINC
PLATED**

Part Number	Size mm	Width mm	Hole Diameter mm	Thickness mm	Quantity Per Box	Price £ Per 100
AB2020	20 x 20	17	4.7	1.2	100	4.40






WALL SCREWS

A light duty carbon steel fixing for use in concrete and masonry base materials, with fast and easy installation and no pre-drilling required.

- ✓ Undercutting Action With No Spinning Or Stripping
- ✓ Non-Cracked Concrete
- ✓ Reaction To Fire Class A1
- ✓ Masonry Base Materials
- ✓ Expansion Free



d_0 =Hole Diameter h_1 *=Minimum Hole Depth L=Shank Length H=Head Thickness

* See JCP Technical Data Sheet on www.jcpfixings.co.uk for details



COUNTERSUNK HEAD WALL SCREWS BZP

BRIGHT ZINC PLATED

- ✓ Head Colour To Match Application
- ✓ Fast And Secure Installation

Part Number	Hole Diameter mm d_0	Thread Diameter mm	Shank Length mm L	Head Thickness mm H	Head Colour	Quantity Per Box	Price £ Per 100
WS5032CSZ	5	6	32	4	Bright Zinc Plated	100	8.79
WS5038CSZ	5	6	38	4	Bright Zinc Plated	100	9.25
WS5050CSZ	5	6	50	4	Bright Zinc Plated	100	10.03
WS5032CSW	5	6	32	4	White	100	9.67
WS5038CSW	5	6	38	4	White	100	10.06
WS5050CSW	5	6	50	4	White	100	10.84

RETAIL BAGS

Product Part Number	Bag Part Number	Size mm	Head Colour	Quantity Per Bag	Price £ Per Bag
WS5032CSZ	JB8953	5 x 32	Bright Zinc Plated	20	2.56
WS5038CSZ	JB8956	5 x 38	Bright Zinc Plated	20	2.88
WS5050CSZ	JB8959	5 x 50	Bright Zinc Plated	20	3.20



TRADE BAGS

Product Part Number	Bag Part Number	Size mm	Head Colour	Quantity Per Bag	Price £ Per Bag
WS5032CSZ	JP3192	5 x 32mm	Bright Zinc Plated	100	10.57
WS5038CSZ	JP3195	5 x 38mm	Bright Zinc Plated	100	11.28
WS5050CSZ	JP3198	5 x 50mm	Bright Zinc Plated	100	11.98





PAN HEAD WALL SCREWS BZP

**BRIGHT ZINC
PLATED**

- ✓ Head Colour To Match Application ✓ Fast And Secure Installation

Part Number	Hole Diameter mm d ₀	Thread Diameter mm	Shank Length mm L	Head Thickness mm H	Head Colour	Quantity Per Box	Price £ Per 100
WS5032PHZ	5	6	32	3	Bright Zinc Plated	100	8.79
WS5038PHZ	5	6	38	3	Bright Zinc Plated	100	9.25
WS5050PHZ	5	6	50	3	Bright Zinc Plated	100	10.03
WS5032PHW	5	6	32	3	White	100	9.67
WS5038PHW	5	6	38	3	White	100	10.06
WS5050PHW	5	6	50	3	White	100	10.84

RETAIL BAGS

Product Part Number	Bag Part Number	Size mm	Head Colour	Quantity Per Bag	Price £ Per Bag
WS5032PHZ	JB8962	5 x 32	Bright Zinc Plated	20	2.82
WS5038PHZ	JB8965	5 x 38	Bright Zinc Plated	20	3.17
WS5050PHZ	JB8968	5 x 50	Bright Zinc Plated	20	3.52



TRADE BAGS

Product Part Number	Bag Part Number	Size mm	Head Colour	Quantity Per Bag	Price £ Per Bag
WS5032PHZ	JP3201	5 x 32mm	Bright Zinc Plated	100	10.57
WS5038PHZ	JP3204	5 x 38mm	Bright Zinc Plated	100	11.28
WS5050PHZ	JP3207	5 x 50mm	Bright Zinc Plated	100	11.98



TRAINING

Our technical team offer training sessions to provide a hands-on experience with our fixings. Sessions are tailored to meet the needs of the audience and can also be delivered virtually.

Who Should Attend?



Construction Professionals



Civil and Structural Engineers



Architects

BASIC TRAINING



2-3 Hours

ADVANCED TRAINING



5-6 Hours


FOR MORE INFORMATION CALL OUR TECHNICAL HELPLINE ON 020 8943 1800



BIGTWIST NAILS

A twist nail for fixing composite panels to wooden battens. The nail rotates during installation to reduce the risk of splitting timber.

- ✓ No Drilling Required
- ✓ Large 20mm Head
- ✓ Quick Installation



L=Anchor Length $t_{fix\ max}$ =Maximum Fixture Thickness



BIGTWIST NAILS BZP

**BRIGHT ZINC
PLATED**

- ✓ Unique One Piece Stress Free Fixing
- ✓ No Need For Screws
- ✓ Grade 8.8 High Tensile Steel
- ✓ Rotates During Installation To Reduce The Risk Of Splitting Timber

Part Number	Shank Diameter mm	Anchor Length mm L	Rec.Tensile Load kN	Max Fixture Thickness mm $t_{fix\ max}$	Quantity Per Bag/Box	Price £ Per 100
TC08090BG	8	90	0.22	55	Bag of 25	50.86
TC08135BG	8	135	0.22	100	Bag of 25	58.18
TC08165BG	8	165	0.22	130	Bag of 25	66.73
TC08195BG	8	195	0.22	160	Bag of 25	77.92
TC08220BG	8	220	0.22	185	Bag of 25	87.08
TC08090BX	8	90	0.22	55	Box of 500	49.54
TC08135BX	8	135	0.22	100	Box of 500	57.42
TC08165BX	8	165	0.22	130	Box of 500	63.84
TC08195BX	8	195	0.22	160	Box of 300	74.99
TC08220BX	8	220	0.22	185	Box of 300	85.47

RETAIL BAGS

Product Part Number	Bag Part Number	Size mm	Quantity Per Bag	Price £ Per Bag
TC08165BG	JB8921	8 x 165	10	10.21






FIXING BANDS

For general strapping applications available in both straight and round formats, supplied in rigid plastic dispensers for ease of use.

- ✓ Easy To Cut
- ✓ Easy To Dispense
- ✓ Various Hole Configurations
- ✓ Stainless Steel For External Use




L=Length

FIXING BANDS

1	ROUND PERFORATED						
	Part Number	Colour/Finish	Length M L	Width mm	Thickness mm	Quantity	Price £ Per Each
	FBR0312G	Mechanical Galvanised	3	12	0.7	1	2.27
	FBR1012G	Mechanical Galvanised	10	12	0.7	1	5.22
2	STRAIGHT PERFORATED						
	Part Number	Colour/Finish	Length M L	Width mm	Thickness mm	Quantity	Price £ Per Each
	FBS0312G	Mechanical Galvanised	3	12	0.7	1	2.57
	FBS1012G	Mechanical Galvanised	10	12	0.7	1	5.81
3	ROUND PERFORATED						
	Part Number	Colour/Finish	Length M L	Width mm	Thickness mm	Quantity	Price £ Per Each
	FBR1017SS	A2-304 Stainless Steel	10	17	0.7	1	19.60
	PLASTIC COATED						
4	Part Number	Colour/Finish	Length M L	Width mm	Thickness mm	Quantity	Price £ Per Each
	FBR10W	White	10	12	0.7*	1	11.17
	FBR10B	Black	10	12	0.7*	1	11.17
	FBR10R	Red	10	12	0.7*	1	11.73

*The measures are before plastic coating.






NYLON HAMMER SCREWS

A range of hammer in nylon screws, suitable for concrete and masonry.

- ✓ For Use In Timber Battens, Frame Ties, Electrical Boxes And Conduit Clips
- ✓ Ribbed Plug Manufactured From Polyamide PA6 Nylon
- ✓ Through Fixing



d_0 =Anchor Hole Size L_{plug} =Anchor Plug Length t_{fix} =Maximum Fixture Thickness h_1 =Minimum Hole Depth



COUNTERSUNK HEAD NYLON HAMMER SCREWS ZYP

ZINC AND
YELLOW PLATED

- ✓ For Use In Concrete And Masonry
- ✓ Ideal For Fast Fixing Repetitive Applications
- ✓ Countersunk Head Gives A Flush Finish

Part Number	Anchor Hole Size mm d_0	Anchor Plug Length mm L_{plug}	Max Fixture Thickness mm t_{fix}	Min Hole Depth mm h_1	Quantity Per Box	Price £ Per 100
NHS05030	5	30	5	30	100	3.99
NHS05050	5	50	25	30	100	5.56
NHS06040	6	40	10	35	100	4.73
NHS06050	6	50	20	35	100	6.14
NHS06060	6	60	30	35	100	6.58
NHS06070	6	70	40	35	100	7.18
NHS08060	8	60	20	45	100	10.36
NHS08080	8	80	40	45	100	13.69
NHS08100	8	100	60	45	50	16.07
NHS08120	8	120	80	45	50	19.20
NHS08140	8	140	100	45	50	21.09

RETAIL BAGS

Product Part Number	Bag Part Number	Size mm	Quantity Per Bag	Price £ Per Bag
NHS06040	JB8427	6 x 40	20	2.96
NHS06060	JB8430	6 x 60	20	3.25
NHS08080	JB8433	8 x 80	10	3.41
NHS08100	JB8436	8 x 100	10	4.15
NHS08120	JB8439	8 x 120	10	4.59



TRADE BAGS

Product Part Number	Bag Part Number	Size mm	Quantity Per Bag	Price £ Per Bag
NHS06040	JP3018	6 x 40	135	8.06
NHS06060	JP3021	6 x 60	100	8.06
NHS08080	JP3024	8 x 80	50	8.06
NHS08100	JP3027	8 x 100	40	8.06





FLANGE HEAD NYLON HAMMER SCREWS ZYP

ZINC AND
YELLOW PLATED

- ✓ For Use In Concrete And Masonry ✓ Large Diameter Flange Head ✓ Flat Head Finish

Part Number	Anchor Hole Size mm d_0	Anchor Plug Length mm L_{plug}	Max Fixture Thickness mm t_{fix}	Min Hole Depth mm h_1	Head Diameter mm	Quantity Per Box	Price £ Per 100
NHS06040FH	6	40	10	35	13	100	4.62



COUNTERSUNK HEAD NYLON HAMMER SCREWS A2 STAINLESS STEEL

A2-304
STAINLESS STEEL

- ✓ For Use In Concrete And Masonry ✓ Ideal For Fast Fixing Repetitive Applications ✓ Countersunk Head Gives A Flush Finish
✓ Suitable For External Use

Part Number	Anchor Hole Size mm d_0	Anchor Plug Length mm L_{plug}	Max Fixture Thickness mm t_{fix}	Min Hole Depth mm h_1	Quantity Per Box	Price £ Per 100
NHS05030SS	5	30	5	30	200	11.37
NHS06040SS	6	40	10	35	200	12.13
NHS06060SS	6	60	30	35	100	17.77
NHS06070SS	6	70	40	35	100	20.46
NHS08060SS	8	60	20	45	100	29.10
NHS08080SS	8	80	40	45	100	25.79
NHS08100SS	8	100	60	45	50	26.38



MUSHROOM HEAD NYLON HAMMER SCREWS

- ✓ For Use In Concrete And Masonry ✓ Suitable For External Use ✓ Mushroom Head Gives A Low Profile Finish

Part Number	Anchor Hole Size mm	Anchor Length mm	Max Fixture Thickness mm	Min Hole Depth mm	Head Diameter mm	Quantity Per Box	Price £ Per 100
NNP06040	6	40	7	50	13	100	11.41




FREE, NEXT-DAY DELIVERY WITH LOW MINIMUM ORDER LEVELS
ACROSS THE MAJORITY OF THE UK MAINLAND.



NYLON FRAME FIXINGS

The nylon frame fixing includes a matched screw and extended plug for anchoring to a wide variety of materials.

- ✓ For Fixing Timber Frames, Battens, Windows And Other Wooden Products To Concrete And Masonry
- ✓ High-Expansion Ratio
- ✓ Ribbed Plug Manufactured From Polyamide PA6 Nylon
- ✓ Through Fixing



COUNTERSUNK NYLON FRAME FIXINGS ZYP

ZINC AND
YELLOW PLATED

- ✓ For Use In Solid Base Materials
- ✓ Countersunk Head Gives A Flush Finish
- ✓ Strong Grip In Weaker Materials



Part Number	Anchor Hole Size mm d_0	Anchor Plug Length mm L_{plug}	Max Fixture Thickness mm t_{fix}	Min Hole Depth mm h_1	Quantity Per Box	Price £ Per 100
NFF08060	8	60	20	45	100	12.53
NFF08080	8	80	40	45	100	16.21
NFF08100	8	100	60	45	100	19.39
NFF08120	8	120	80	45	100	23.61
NFF10080	10	80	35	50	100	27.82
NFF10100	10	100	55	50	100	32.88
NFF10120	10	120	75	50	100	39.68
NFF10140	10	140	95	50	100	42.66
NFF10160	10	160	115	50	100	48.99

RETAIL BAGS

Product Part Number	Bag Part Number	Size mm	Quantity Per Bag	Price £ Per Bag
NFF08060	JB8400	8 x 60	10	3.25
NFF08080	JB8403	8 x 80	10	3.63
NFF08100	JB8406	8 x 100	10	4.15
NFF08120	JB8409	8 x 120	10	4.59
NFF10100	JB8412	10 x 100	6	4.15
NFF10120	JB8415	10 x 120	6	4.59
NFF10140	JB8418	10 x 140	6	5.03
NFF10160	JB8421	10 x 160	6	5.48



TRADE BAGS

Product Part Number	Bag Part Number	Size mm	Quantity Per Bag	Price £ Per Bag
NFF08080	JP3000	8 x 80	50	8.06
NFF08100	JP3003	8 x 100	40	8.06
NFF10100	JP3006	10 x 100	30	8.06
NFF10120	JP3009	10 x 120	25	8.06
NFF10140	JP3012	10 x 140	20	8.06
NFF10160	JP3015	10 x 160	15	8.06





ETA COUNTERSUNK HEAD NYLON FRAME FIXINGS BZP

- ✓ For Use In Solid And Hollow Base Materials
- ✓ TX Drive: 8mm - T30, 10mm - T40
- ✓ Countersunk Head Gives A Flush Finish
- ✓ Fire Resistance Loading
- ✓ Tested To ETAG 020-01, Plastic Anchors For Multiple Use For Non-Structural Application



**BRIGHT ZINC
PLATED**

Part Number	Anchor Hole Size mm d_0	Anchor Plug Length mm L_{plug}	Max Fixture Thickness mm t_{fix}	Min Hole Depth mm h_1	Quantity Per Box	Price £ Per 100
NFF08080ETA	8	80	10	90	100	43.84
NFF08100ETA	8	100	30	90	100	49.19
NFF08120ETA	8	120	50	90	100	61.81
NFF08140ETA	8	140	70	90	50	76.75
NFF10080ETA	10	80	10	90	50	51.04
NFF10100ETA	10	100	30	90	50	63.15
NFF10120ETA	10	120	50	90	50	68.87
NFF10140ETA	10	140	70	90	50	83.66
NFF10160ETA	10	160	90	90	50	109.27



ETA HEXAGON HEAD NYLON FRAME FIXINGS BZP

- ✓ For Use In Solid And Hollow Base Materials
- ✓ Fire Resistance Loading
- ✓ Tested To ETAG 020-01, Plastic Anchors For Multiple Use For Non-Structural Application



**BRIGHT ZINC
PLATED**

Part Number	Anchor Hole Size mm d_0	Anchor Plug Length mm L_{plug}	Max Fixture Thickness mm t_{fix}	Min Hole Depth mm h_1	Quantity Per Box	Price £ Per 100
NFF08080ETAH	8	80	10	90	100	48.11
NFF08100ETAH	8	100	30	90	100	55.99
NFF08120ETAH	8	120	50	90	100	73.46
NFF08140ETAH	8	140	70	90	50	94.55
NFF10080ETAH	10	80	10	90	50	61.20
NFF10100ETAH	10	100	30	90	50	74.47
NFF10120ETAH	10	120	50	90	50	97.80
NFF10140ETAH	10	140	70	90	50	125.00
NFF10160ETAH	10	160	90	90	25	166.82



ETA COUNTERSUNK HEAD NYLON FRAME FIXINGS A4 STAINLESS STEEL

- ✓ For Use In Solid And Hollow Base Materials
- ✓ Countersunk Head Gives A Flush Finish
- ✓ Fire Resistance Loading
- ✓ TX Drive: 8mm - T30, 10mm - T40
- ✓ Tested To ETAG 020-01, Plastic Anchors For Multiple Use For Non-Structural Application
- ✓ Suitable For External Use And Marine Environments



**A4-316
STAINLESS STEEL**

Part Number	Anchor Hole Size mm d_0	Anchor Plug Length mm L_{plug}	Max Fixture Thickness mm t_{fix}	Min Hole Depth mm h_1	Quantity Per Box	Price £ Per 100
NFF08080ETASS	8	80	10	90	100	148.15
NFF08100ETASS	8	100	30	90	100	176.91
NFF08120ETASS	8	120	50	90	100	206.24
NFF08140ETASS	8	140	70	90	50	289.47
NFF10080ETASS	10	80	10	90	50	204.72
NFF10100ETASS	10	100	30	90	50	240.53
NFF10120ETASS	10	120	50	90	50	276.16
NFF10140ETASS	10	140	70	90	50	353.31
NFF10160ETASS	10	160	90	90	50	421.71



PLUGS

A range of plastic and metal plugs for various applications.

- ✓ Different Strengths Available
- ✓ Allow For Secure Fixings
- ✓ Standard And Premium Range Available



PUSH PLUGS


- ✓ For Retaining Damp-Proof Membranes
- ✓ No Expansion Forces
- ✓ Corrosion Resistant
- ✓ Grips The Hole With Flexible Wings

Part Number	Anchor Hole Size mm	Anchor Plug Length mm	Max Fixture Thickness mm	Min Hole Depth mm	Head Diameter mm	Quantity Per Box	Price £ Per 100
PP06035	6	35	5	45	13	100	4.24



NYLON WALL PLUGS

- ✓ For Use In Solid Base Materials
- ✓ Suitable For Wood And Chipboard Screws
- ✓ 2 Way Expansion
- ✓ Screw Guidance
- ✓ Rimless



Part Number	Anchor Hole Size mm d_0	Anchor Plug Length mm L_{plug}	Woodscrew Gauge No mm	Metric Screw Size mm	Min Hole Depth mm h_1	Quantity Per Box	Price £ Per 100
NP05	5	25	4-6	2.5-3.5	30	100	1.91
NP06	6	30	6-10	3.5-5.0	35	100	2.07
NP07	7	35	8-12	4.0-5.5	40	100	2.47
NP08	8	40	10-14	5.0-6.0	45	100	3.14
NP10	10	50	14-18	6.0-8.0	55	50	5.67
NP12	12	60	18-24	8.0-10.0	70	25	10.86
NP14	14	75	24-32	10.0-12.0	85	20	15.44

RETAIL BAGS

Product Part Number	Bag Part Number	Size mm	Quantity Per Bag	Price £ Per Bag
NP06	JB8509	6	40	3.12
NP08	JB8512	8	40	3.63
NP10	JB8515	10	20	3.84



TRADE BAGS


Product Part Number	Bag Part Number	Size mm	Quantity Per Bag	Price £ Per Bag
NP06	JP3180	6	200	4.74
NP08	JP3183	8	100	4.74
NP10	JP3186	10	70	4.74





UNIVERSAL WALL PLUGS

✓ For Use In Solid And Hollow Base Materials



d_0 =Anchor Hole Size L_{plug} =Anchor Plug Length h_1 =Minimum Hole Depth

Part Number	Anchor Hole Size mm d_0	Anchor Plug Length mm L_{plug}	Woodscrew Gauge No mm	Metric Screw Size mm	Min Hole Depth mm h_1	Quantity Per Box	Price £ Per 100
NUP06035	6	40	6-8	3.5-4.0	45	200	2.73
NUP08050	8	50	10-12	4.5-5.5	55	100	5.29
NUP10060	10	60	12-14	5.5-6.0	65	50	7.99


RETAIL BAGS

Product Part Number	Bag Part Number	Size mm	Quantity Per Bag	Price £ Per Bag
NUP06035	JB8521	6 x 40	40	3.63
NUP08050	JB8524	8 x 50	40	4.59



PREMIUM NYLON WALL PLUGS

✓ For Use In Solid And Hollow Base Materials ✓ Suitable For Wood And Chipboard Screws ✓ 2 Way Expansion
✓ Rimless ✓ Anti-Rotation Lugs ✓ Castellated Split Guides Screw To Keep It Inside Plug



d_0 =Anchor Hole Size L_{plug} =Anchor Plug Length h_1 =Minimum Hole Depth

Part Number	Anchor Hole Size mm d_0	Anchor Plug Length mm L_{plug}	Woodscrew Gauge No mm	Metric Screw Size mm	Min Hole Depth mm h_1	Quantity Per Box	Price £ Per 100
NP06030	6	30	6-10	3.5-5.0	35	100	1.88
NP06055	6	55	6-10	3.5-5.0	60	100	2.27
NP08040	8	40	10-14	4.5 - 6.0	45	100	2.39
NP08060	8	60	10-14	4.5 - 6.0	70	100	3.09
NP10080	10	80	14-18	6.0 - 8.0	90	100	5.90
NP12055	12	55	18-24	8.0 - 10.0	60	100	4.82

JCP STANDARD PLASTIC PLUGS

✓ Supplied On A Sprue ✓ For Use In Solid And Hollow Base Materials ✓ Supplied In Outers Of 1,000
✓ Suitable For Standard Trade Requirements

Part Number	Colour	Drill Diameter mm	Plug Length mm	Woodscrew Gauge No mm	Metric Screw Size mm	Min Hole Depth mm	Quantity Per Box	Price £ Per 1000
AYP	Yellow	5	22	4-8	2.5-4.0	30	10 x 100	11.46
ARP	Red	5.5	30	6-10	3.5-5.0	40	10 x 100	11.61
ABP	Brown	7	37	10-14	5.0-6.0	45	10 x 100	16.59



AYP



ARP



ABP





JCP BULK PLASTIC PLUGS


✓ Supplied Loose

Part Number	Colour	Drill Diameter mm	Plug Length mm	Woodscrew Gauge No mm	Metric Screw Size mm	Min Hole Depth mm	Quantity Per Box	Price £ Per 1000
LBARP	Red	6	37	6-10	3.5-5.0	40	10000	9.69
LBABP	Brown	7	37	10-14	5.0-6.0	45	5000	13.73

JCP PREMIUM PLASTIC PLUGS

✓ Supplied On A Sprue ✓ For Use In Concrete And Masonry Base Materials ✓ Supplied In Outers Of 1,000

✓ Suitable For Wood And Chipboard Screws



d_0 =Anchor Hole Size L_{plug} =Anchor Plug Length h_1 =Minimum Hole Depth

Part Number	Colour	Drill Diameter mm d_0	Plug Length mm L_{plug}	Woodscrew Gauge No mm	Metric Screw Size mm	Min Hole Depth mm h_1	Quantity Per Box	Price £ Per 1000
JCPRED	Red	6	37	6-10	3.5-5.0	45	10 x 100	15.83
JCPBROWN	Brown	7	37	10-14	5.0-6.0	45	10 x 100	19.34



JCPRED



JCPBROWN


RETAIL BAGS

Product Part Number	Bag Part Number	Colour	Drill Diameter mm	Quantity Per Bag	Price £ Per Bag
JCPRED	JB8500	Red	6	50	2.82
JCPBROWN	JB8503	Brown	7	50	2.96



METAL EXPANSION PLUGS

✓ For Use In Concrete, Masonry And Aerated Concrete Blocks ✓ 4 Segment Design ✓ For Use With Woodscrews



Part Number	Drill Diameter mm d_0	Plug Length mm L_{plug}	Screw Size mm	Min Hole Depth mm h_1	Quantity Per Box	Price £ Per 100
MP05030	5	30	4.5	40	100	5.48
MP06032	6	32	4.5-5.0	40	100	6.28
MP08038	8	38	5.0-6.0	50	100	10.34
MP08060	8	60	5.0-6.0	70	50	12.96





CAVITY FIXINGS


A range of fixings to suit all plasterboard and cavity applications.

- ✓ Secure And Solid Fixing ✓ All-Metal, Nylon And Spring Toggles Available



J-PLUG PLASTERBOARD FIXINGS

- ✓ Comes Complete With Screw ✓ Self-Drilling ✓ Compatible With Hand Or Power Screwdrivers



L_{screw} = Screw Length t_{fix} = Maximum Fixture Thickness

Part Number	Screw Thread Diameter mm	Screw Length mm L_{screw}	Max. Fixture Thickness mm t_{fix}	Hole Depth mm	Quantity Per Box	Price £ Per 100
JJP15	4.5	35	15	37	100	18.08
JJP30	4.5	50	30	37	100	19.67
JJP15A	4.5	35	15	32	100	17.29
JJP30A	4.5	50	30	32	100	18.29
JJPN10A	4.5	30	10	29	100	8.44



JJP15/30
Zinc Alloy



JJP15A/30A
Zinc Alloy



JJPN10A
Nylon

RETAIL BAGS

Product Part Number	Bag Part Number	Description	Quantity Per Bag	Price £ Per Bag
JJP15A	JB8615	Metal Plasterboard Fixing up to 15mm	6	2.67
JJP15A	JB8618	Metal Plasterboard Fixing up to 15mm	20	5.03
JJPN10A	JB8621	Nylon Plasterboard Fixing up to 10mm	6	2.67
JJPN10A	JB8624	Nylon Plasterboard Fixing up to 10mm	20	5.03



TRADE BAGS


Product Part Number	Bag Part Number	Description	Quantity Per Bag	Price £ Per Bag
JJP15A	JP3057	Metal Plasterboard Fixing Up to 15mm	75	14.31



ROSETT CAVITY FIXINGS

For use in plasterboard and other materials where a fixing into a cavity is required.

✓ Single And Double Skin Plasterboard Options Available ✓ Heavy Duty ✓ 30% Glass Fibre Re-Enforced Thread



L_{screw} = Screw Length t_{wall} = Wall Thickness t_{fix} = Maximum Fixture Thickness d_0 = Hole Diameter

Part Number	Screw Length mm L_{screw}	Wall Thickness mm t_{wall}	Max. Fixture Thickness mm t_{fix}	Hole Diameter mm d_0	Quantity Per Box	Price £ Per 100
BR05055	55	9-18	15	10	25	71.66
BR05080	85	9-18	40	10	25	76.15
RR05065	65	18-30	12	10	25	75.04
RR05090	90	18-30	38	10	25	82.58
BRHOOK	-	9-18	-	10	25	115.52
RRHOOK	-	18-30	-	10	25	117.00



BR05055
Pan Head



RR05065
Pan Head



BRHOOK
Hook



RRHOOK
Hook

RETAIL BAGS

Product Part Number	Bag Part Number	Colour	Size	Quantity Per Bag	Price £ Per Bag
BR05055	JB8600	Blue	M5 x 55	6	5.91
BR05080	JB8603	Blue	M5 x 80	6	5.91
RR05065	JB8606	Red	M5 x 65	6	5.91
RR05090	JB8609	Red	M5 x 90	6	5.91



TRADE BAGS

Product Part Number	Bag Part Number	Colour	Size	Quantity Per Bag	Price £ Per Bag
BR05055	JP3063	Blue	M5 x 55	10	21.32



PLASTERBOARD PLUGS

✓ Short Length Ideal For Dry Lined Walls ✓ Flange Head Prevents Push Through



Part Number	Woodscrew Size mm	Woodscrew Gauge mm	Wall Thickness mm	Minimum Cavity Depth mm	Hole Diameter mm	Quantity Per Box	Price £ Per 100
PPLUG	4.5	8	4-12	30	7	100	4.08

RETAIL BAGS


Product Part Number	Bag Part Number	Drill Diameter mm	Quantity Per Bag	Price £ Per Bag
PPLUG	JB8663	7	20	3.84





ANKERNUTS

- ✓ For Use In Hollow Materials And Occasional Use In Solid Materials
- ✓ Flange Head
- ✓ Vibration Resistant
- ✓ Synthetic Rubber Sleeve (EPDM) With Brass Threaded Insert
- ✓ Ideal For Irregular Shaped Holes



M=Thread Diameter d₀=Hole Diameter t_{wall}=Wall Thickness L=Length t_{flange}=Flange Thickness OD=Flange Diameter

Part Number	Thread Diameter M	Hole Diameter mm d ₀	Wall Thickness mm t _{wall}	Length mm L	Flange Thickness mm t _{flange}	Flange Diameter mm OD	Rec. Tightening Torque mm	Quantity Per Box	Price £ Per 100
LNN03024	3	8	2.0-15.0	24	1	11	1	50	24.97
LNN04011	4	8	0.4-2.0	13	1	11	1	50	24.46
LNN04024	4	8	2.0-15.0	25	1	11	1	50	24.97
LNN05015	5	10	0.4-4.0	14	1	13	1.8	50	29.41
LNN05025	5	10	8.0-16.0	25	1.3	14	1.8	50	35.86
LNN05040	5	10	20.0-30.0	40	1.3	14	1.8	50	37.15
LNN06015	6	13	0.4-3.0	15	1.3	16	4	50	50.40
LNN06025	6	13	6.0-12.0	25	1.3	16	4	50	39.72
LNN06035	6	13	12.0-25.0	35	1.3	16	4	50	44.01
LNN06050	6	13	25.0-40.0	50	1.3	16	4	50	50.40
LNN08025	8	18	4.0-10.0	25	5.7	22	8	50	71.49
LNN08050	8	18	25.0-35.0	50	1.6	20	8	50	85.30
LNN10055	10	20	25.0-35.0	55	1.3	22.5	10	25	169.92
LNN12075	12	24	35.0-45.0	75	1.3	27	15	20	232.27
LNN12125	12	24	35.0-45.0	125	1.3	27	15	20	376.67

ROAD FIXING KIT

- ✓ For Attaching Fixtures To Tarmac
- ✓ Complete With Bolt
- ✓ For Fixing Down Speed Ramps, Smoking Shelters, Bicycle Storage Racks And Other Non-Structural Applications

Part Number	Description	Price £ Per Each
RFK12125	4 x M12 x 125 Ankernuts C/W M12 x 160 Set Bolt and Washer	11.09




**FREE, NEXT-DAY DELIVERY WITH LOW MINIMUM ORDER LEVELS
ACROSS THE MAJORITY OF THE UK MAINLAND.**



HOLLOW WALL ANCHORS ZYP

ZINC AND
YELLOW PLATED

- ✓ Provides A Strong, Permanent Anchorage To Plasterboard And Other Partition Materials
- ✓ Five Way Expansion
- ✓ All Metal Expanding Cavity Anchor
- ✓ Anti-Rotation Lugs
- ✓ Flange Head
- ✓ Complete With Pan Head Screws



L_{screw} = Screw Size t_{wall} = Wall Thickness t_{fix} = Maximum Fixture Thickness d_0 = Hole Diameter M^* = Thread Diameter

Part Number	Screw Size mm L_{screw}	Wall Thickness mm t_{wall}	Max Fixture Thickness mm t_{fix}	Hole Diameter mm d_0	Quantity Per Box	Price £ Per 100
LHWA04025	M4 x 25	0-4	10	7	100	12.60
LHWA04045	M4 x 45	8-13	15	7	100	12.95
LHWA04050	M4 x 50	16-20	15	7	100	14.31
LHWA04065	M4 x 65	22-27	30	7	100	16.48
LHWA05045	M5 x 45	5-10	15	9	100	19.55
LHWA05060	M5 x 60	5-13	23	9	50	23.01
LHWA05070	M5 x 70	17-25	23	9	50	25.59
LHWA06060	M6 x 60	7-13	23	10	50	28.63
LHWA06070	M6 x 70	16-24	24	10	50	32.54

RETAIL BAGS

Product Part Number	Bag Part Number	Size	Quantity Per Bag	Price £ Per Bag
LHWA04045	JB8630	M4 x 45	10	3.41
LHWA05045	JB8633	M5 x 45	10	4.15
LHWA05060	JB8634	M5 x 60	10	4.41
LHWA06060	JB8636	M6 x 60	10	5.03



TRADE BAGS

Product Part Number	Bag Part Number	Size	Quantity Per Bag	Price £ Per Bag
LHWA06060	JP3060	M6 x 60	40	14.31



HOLLOW WALL ANCHOR SETTING TOOL

- ✓ For Rapid Installation Of Hollow Wall Anchors
- ✓ Eliminates The Need For A Screwdriver


Part Number	Quantity Per Box	Price £ Per Each
LHWAST	1	14.30



SPRING TOGGLES ZYP

ZINC AND
YELLOW PLATED

- ✓ Can Be Used In Virtually Any Cavity Or Blind Fixing Situation From Hardboard To Hollow Steel Sections
- ✓ Various Sizes To Suit Different Wall Thicknesses
- ✓ Complete With Screws



M=Thread Diameter L_{screw} =Screw Length $t_{wall+fixture}$ =Wall and Fixture Thickness d_h =Hole Diameter

Part Number	Thread Diameter M	Screw Length mm L_{screw}	Wall and Fixture Thickness mm $t_{wall+fixture}$	Cavity Depth mm	Hole Diameter mm d_h	Quantity Per Box	Price £ Per 100
LST03050	3	50	30	20	11	100	21.13
LST05050	5	50	20	30	14	100	23.85
LST05075	5	75	45	30	14	100	29.85
LST05100	5	100	70	30	14	100	31.09
LST06075	6	75	45	30	18	100	40.46

RETAIL BAGS

Product Part Number	Bag Part Number	Size	Quantity Per Bag	Price £ Per Bag
LST05050	JB8642	M5 x 50	6	3.63
LST05075	JB8645	M5 x 75	6	4.15
LST06075	JB8648	M6 x 75	6	4.59



SPRING TOGGLES (WINGS ONLY) ZYP

ZINC AND
YELLOW PLATED

- ✓ Can Be Used In Virtually Any Cavity Or Blind Fixing Situation
- ✓ Various Sizes To Suit Different Wall Thicknesses

Part Number	Thread Diameter M	Cavity Depth mm	Hole Diameter mm	Quantity Per Box	Price £ Per 100
LSTM03	3	20	11	100	10.00
LSTM05	5	30	14	100	11.58
LSTM06	6	30	18	100	14.11
LSTM08	8	40	22	50	30.00
LSTM10	10	40	25	50	32.59



PLASTIC TOGGLES

- ✓ For Use In Hollow And Cavity Applications
- ✓ Quick And Easy To Apply
- ✓ Use With Standard Woodscrew
- ✓ Light Duty Applications

Part Number	Woodscrew Size mm	Woodscrew Gauge mm	Wall Thickness mm	Minimum Cavity Depth mm	Hole Diameter mm	Quantity Per Box	Price £ Per 100
NT10	4.5	8	4-12	30	10	100	11.23
NT12	4.5	8	15-19	35	10	100	12.20
NT16	4.5	8	24-28	40	10	100	13.20

RETAIL BAGS

Product Part Number	Bag Part Number	Wall Thickness mm	Quantity Per Bag	Price £ Per Bag
NT10	JB8654	4-12	20	3.84
NT12	JB8657	15-19	20	4.15





GAS NAILS

A range of gas nails and fuel cell packs for fixing timber to timber (first fix).

- ✓ Highest Quality
- ✓ CE Marked
- ✓ Additional Fuel Cells Available
- ✓ Stainless Steel For External Use




CLIPPED HEAD DRIVEFAST GAS NAILS

- ✓ 34° Angled Clipped Head Nails
- ✓ Includes 2 Fuel Cell Packs
- ✓ Conform To Eurocode 5 Service Class 1
- ✓ 1 Fuel Cell Per 1,100 Nails
- ✓ Suitable For Use In Drivefast DF90, IM350, NR90GC2, GN900S, WW90CH, GS690CH, GT90CH And D90S



In accordance with
BS EN 14592:2008+A1:2002

Part Number	Nail Length mm	Shank Diameter mm	Description	Quantity Per Box	Price £ Per Box
IM35051RB	51	2.8	1 Ring Bright	2200	65.73
IM35063RB	63	2.8	1 Ring Bright	2200	73.33
IM35075RB	75	3.1	1 Ring Bright	2200	85.71
IM35051EG	51	2.8	2 Ring Electro Galv	2200	72.42
IM35063EG	63	2.8	2 Ring Electro Galv	2200	81.77
IM35075EG	75	3.1	2 Ring Electro Galv	2200	84.50
IM35063RG	63	2.8	3 Ring Hot Dip Galv	2200	85.00
IM35075RG	75	3.1	3 Ring Hot Dip Galv	2200	87.63
IM35090SB	90	3.1	4 Smooth Bright	2200	78.65
IM35090EG	90	3.1	5 Smooth Electro Galv	2200	99.55
IM35090SG	90	3.1	6 Screwed Electro Galv	2200	106.61



STAINLESS STEEL CLIPPED HEAD DRIVEFAST GAS NAILS

- ✓ 34° Angled Clipped Head Nails
- ✓ Includes Fuel Cell Pack
- ✓ Conform To Eurocode 5 Service Classes 1, 2, And 3
- ✓ 1 Fuel Cell Per 1,000 Nails
- ✓ Suitable For External Use



In accordance with
BS EN 14592:2008+A1:2002

**A2-304
STAINLESS STEEL**


Part Number	Nail Length mm	Shank Diameter mm	Quantity Per Box	Price £ Per Box
IM35051SS	51	2.8	1000	124.42
IM35063SS	63	2.8	1000	161.29
IM35080SS	80	3.1	1000	175.00
IM35090SS	90	3.1	1000	191.21



CLIPPED HEAD DRIVEFAST NAILS ONLY **NEW**



Part Number	Nail Length mm	Shank Diameter mm	Description	Quantity Per Box	Price £ Per Box
DF2851RB	51	2.8	1 Ring Bright	1000	16.04
DF2863RB	63	2.8	1 Ring Bright	1000	19.29
DF3175RB	75	3.1	1 Ring Bright	1000	24.38
DF2851EG	51	2.8	2 Ring Electro Galv	1000	17.63
DF2863EG	63	2.8	2 Ring Electro Galv	1000	18.17
DF3175EG	75	3.1	2 Ring Electro Galv	1000	28.75
DF2863RG	63	2.8	3 Ring HDG	1000	25.60
DF3175RG	75	3.1	3 Ring HDG	1000	35.50
DF3190SB	90	3.1	4 Smooth Bright	1000	24.38
DF3190EG	90	3.1	5 Smooth Electro Galv	1000	31.75
DF3190SG	90	3.1	6 Screwed Electro Galv	1000	34.71



DRIVEFAST GAS NAILS

WE HAVE CHANGED OUR DRIVEFAST GAS NAIL PACKAGING TO A NEW AND IMPROVED DESIGN.

- DESCRIPTIVE AND DETAILED DESIGN, FOR EASY SELECTION.
- STRONG, ASSEMBLED BOXES FOR LONGEVITY.
- ONE-PART BOX FOR EASY ACCESS.
- STRIKING JCP LIVRY FOR EASY BRAND IDENTIFICATION.
- STURDY HANDLE FOR EASY TRANSPORT BETWEEN PROJECTS.




CLIPPED HEAD HANDI PACK DRIVEFAST GAS NAILS

- ✓ 34° Angled Clipped Head Nails
- ✓ Includes Fuel Cell Pack
- ✓ Conform To Eurocode 5 Service Class 1
- ✓ 1 Fuel Cell Per 1,000 Nails



In accordance with
BS EN 14592:2008+A1:2002

Part Number	Nail Length mm	Shank Diameter mm	Description	Quantity Per Box	Price £ Per Box
HAN51RB	51	2.8	1 Ring Bright	1000	33.33
HAN63RB	63	2.8	1 Ring Bright	1000	34.92
HAN75RB	75	2.8	1 Ring Bright	1000	36.58
HAN51EG	51	2.8	2 Ring Electro Galv	1000	35.46
HAN63EG	63	2.8	2 Ring Electro Galv	1000	41.67
HAN75EG	75	3.1	2 Ring Electro Galv	1000	46.04
HAN90SB	90	3.1	3 Smooth Bright	1000	41.67
HAN90EG	90	3.1	4 Smooth Electro Galv	1000	51.79
HAN90SG	90	3.1	5 Screwed Electro Galv	1000	52.00



BRAD NAILS AND GAS

- ✓ Suitable For Use In IM250, NT65GS And DC616KB
- ✓ Includes 2 Fuel Cell Packs
- ✓ 1 Fuel Cell Per 1000 Nails
- ✓ Conform To Eurocode 5 Service Classes 1, 2, And 3



In accordance with
BS EN 14592:2008+A1:2002

16 GAUGE GALVANISED STRAIGHT BRAD NAILS						
Part Number	Nail Length mm	Shank Diameter mm	Description	Quantity Per Outer Box	Quantity Per Inner Box	Price £ Per Box
IM25038G	38	F16	Straight Brad	8000	2000	36.00
IM25050G	50	F16	Straight Brad	8000	2000	52.58
IM25064G	64	F16	Straight Brad	8000	2000	58.33
A2-304 STAINLESS STEEL STRAIGHT BRAD NAILS						
Part Number	Nail Length mm	Shank Diameter mm	Description	Quantity Per Outer Box	Quantity Per Inner Box	Price £ Per Box
IM25038SS	38	F16	Straight Brad	2000	2000	366.83
IM25050SS	50	F16	Straight Brad	2000	2000	458.33
16 GAUGE GALVANISED ANGLED BRAD NAILS						
Part Number	Nail Length mm	Shank Diameter mm	Description	Quantity Per Outer Box	Quantity Per Inner Box	Price £ Per Box
IM25038A	38	F16	Angled Brad	2000	2000	39.17
IM25050A	50	F16	Angled Brad	2000	2000	46.17



DRIVEFAST GAS ONLY

- ✓ To Suit The Drivefast DF90 And The Paslode IM350
- ✓ Mix Of Propane And Butane To Optimise Performance
- ✓ Contains A Top Grade Mobil Fully Synthetic Lubrication Oil To Protect The Tool

Part Number	Description	Quantity Per Inner Box	Price £ Per Each
IMGAS250	To suit IM250/IM250A	1	16.67
IMGAS350	To suit IM350/DF90	1	17.29



IMGAS250

IMGAS350



CARTRIDGE TOOLS AND ACCESSORIES

Cartridge tool, strips and pins for fastening wood or sheet metal to concrete, steel or brick.

- ✓ Easy Installation ✓ Strong Fixing ✓ Concrete, Steel And Masonry Subject To Correct Selection And Application



CEILING HANGERS

- ✓ Suspension Clip Suitable For 8mm Cartridge Tools

Part Number	Shank Diameter mm	Shank Length mm	Quantity Per Box	Price £ Per 100
VCH32	3.8	32	100	27.10

PA97 CARTRIDGE TOOL KIT

Strip feed tool with power adjuster suitable for 12mm metal washered drive pins up to 97mm long. (82mm and 97mm pins require pre-driving).



- ✓ A Low Velocity, Indirect Acting Tool ✓ Comes Complete With Carry Case ✓ Portable And Robust
✓ Spare Parts Available

Part Number	Description	Quantity Per Unit	Price £ Per Each
PA97KIT	Strip Feed Cartridge Tool C/W Kit in Toolbox	1	695.00



PA97

Safety Goggles



Retaining Ring



Spall Shield



Stop Ring



Cleaning Brushes




CARTRIDGE STRIPS

- ✓ Suitable For PA97 And Most Other Strip Fed Tools ✓ Colour Coded For Strength Indication



Part Number	Colour	Strength	Quantity Per Box	Price £ Per 100
V4LVS27Y	Yellow	Low/Medium	100	35.00
V6REDLVS27	Red	Medium/High	100	35.00
V7BLKLVS27	Black	Extra High	100	40.00





SHOT FIRED PINS

- ✓ For Fixing Into Steel And Concrete
- ✓ Suitable For Use In The PA97, DX450 and Other Cartridge Tools That Take Metal Washered Drive Pins
- ✓ 12mm Steel Washer For Guidance Within The Tool
- ✓ Increased Pull-Over Strength When Fixing Softer Materials

Part Number	Shank Diameter mm	Shank Length mm	Quantity Per Box	Price £ Per 100
VMW16	3.7	16	100	8.36
VMW19	3.7	19	100	8.36
VMW22	3.7	22	100	8.05
VMW27	3.7	27	100	8.43
VMW32	3.7	32	100	8.73
VMW37	3.7	37	100	9.56
VMW42	3.7	42	100	10.46
VMW47	3.7	47	100	10.46
VMW52	3.7	52	100	12.12
VMW57	3.7	57	100	12.72
VMW62	3.7	62	100	12.95
VMW72	3.7	72	100	14.75
VMW82	3.7	82	100	18.36
VMW97	3.7	97	100	20.40



PLASTIC WASHERED PINS

- ✓ For Fixing Into Steel And Concrete
- ✓ Suitable For Use In 8mm Cartridge Tools
- ✓ 8mm Plastic Washer For Guidance Within The Tool

Part Number	Shank Diameter mm	Shank Length mm	Quantity Per Box	Price £ Per 100
VPW16	3.8	16	100	7.38
VPW19	3.8	19	100	7.90
VPW22	3.8	22	100	7.45
VPW27	3.8	27	100	8.21
VPW32	3.8	32	100	8.88
VPW37	3.8	37	100	9.64
VPW42	3.8	42	100	10.39
VPW47	3.8	47	100	11.06
VPW52	3.8	52	100	11.89
VPW57	3.8	57	100	12.57
VPW62	3.8	62	100	13.25
VPW72	3.8	72	100	14.08



MAGAZINE PINS

- ✓ For Fixing Into Steel And Concrete
- ✓ Suitable For Use In 8mm Magazine Cartridge Tools
- ✓ Magazine Ensures Swift And Accurate Deployment

Part Number	Shank Diameter mm	Shank Length mm	Quantity Per Box	Price £ Per 100
VSN19	3.8	19	100	9.11
VSN22	3.8	22	100	8.65
VSN27	3.8	27	100	9.41
VSN32	3.8	32	100	10.16
VSN37	3.8	37	100	10.84
VSN42	3.8	42	100	11.59
VSN47	3.8	47	100	12.27
VSN52	3.8	52	100	12.95
VSN57	3.8	57	100	13.77
VSN62	3.8	62	100	14.45
VSN72	3.8	72	100	15.13



DRILL BITS

A range of drill bits for various uses including drilling into harder materials, masonry, stainless steel and wood.

✓ Heavy-Duty Drilling Options ✓ Sets Available



SDS+ DRILL BITS

✓ For Drilling Into Concrete, Natural Stone And Masonry ✓ High Strength Steel To Avoid Bending Or Snapping
✓ Tungsten Carbide Tip ✓ Heavy-Duty Drilling ✓ Two Tungsten Carbide Cutting Edges

Part Number	Diameter mm	Working Length mm	Overall Length mm	Price £ Per Each
SD04110	4.0	50	110	1.42
SD05110	5.0	50	110	1.46
SD05160	5.0	100	160	1.62
SD55110	5.5	50	110	1.46
SD55160	5.5	100	160	1.62
SD55210	5.5	150	210	1.99
SD06110	6.0	50	110	1.46
SD06160	6.0	100	160	1.62
SD06200	6.0	150	200	1.99
SD06260	6.0	200	260	2.55
SD65110	6.5	50	110	1.54
SD65160	6.5	100	160	1.66
SD65210	6.5	150	210	2.07
SD65250	6.5	200	250	2.23
SD07110	7.0	50	110	1.62
SD07160	7.0	100	160	1.78
SD07210	7.0	150	210	2.19
SD08110	8.0	50	110	1.62
SD08160	8.0	100	160	1.74
SD08210	8.0	150	210	2.19
SD08260	8.0	200	260	2.55
SD08450	8.0	400	450	4.46
SD08600	8.0	550	600	5.76
SD10110	10.0	50	110	1.87
SD10160	10.0	100	160	1.99
SD10210	10.0	150	210	2.47
SD10260	10.0	200	260	2.76
SD10450	10.0	400	450	4.54
SD12160	12.0	100	160	2.39
SD12210	12.0	150	210	2.76
SD12260	12.0	200	260	3.04
SD12300	12.0	250	300	3.37
SD12450	12.0	400	450	4.87
SD12600	12.0	550	600	6.08

Part Number	Diameter mm	Working Length mm	Overall Length mm	Price £ Per Each
SD13160	13.0	100	160	2.84
SD13210	13.0	150	210	3.04
SD13260	13.0	200	260	3.24
SD14160	14.0	100	160	2.92
SD14210	14.0	150	210	3.33
SD14300	14.0	250	300	4.01
SD14450	14.0	400	450	5.76
SD14600	14.0	550	600	7.10
SD15160	15.0	100	160	3.53
SD15260	15.0	200	260	4.34
SD16210	16.0	150	210	3.93
SD16300	16.0	250	300	4.66
SD16450	16.0	400	450	6.69
SD16600	16.0	550	600	8.31
SD18200	18.0	150	200	5.27
SD18450	18.0	400	450	8.68
SD20200	20.0	150	200	6.00
SD20300	20.0	250	300	7.34
SD20450	20.0	400	450	10.02
SD22250	22.0	200	250	8.03
SD22450	22.0	400	450	11.36
SD24260	24.0	200	260	10.38
SD24450	24.0	400	450	14.40
SD25250	25.0	200	250	10.71
SD25450	25.0	400	450	14.72
SD26450	26.0	400	450	15.01
SD28450	28.0	400	450	15.82
SD30450	30.0	400	450	20.68



SDS+ HIGH PERFORMANCE DRILL BITS



- ✓ For Drilling Into Reinforced Concrete, Natural Stone And Masonry
- ✓ Force X Drill Bit
- ✓ Four Tungsten Carbide Cutting Edges
- ✓ Four Flute Design For More Efficient Dust Removal
- ✓ Long Lasting And Long Service Life
- ✓ Heavy Duty Drilling

Part Number	Diameter mm	Working Length mm	Overall Length mm	Price £ Per Each
SDHP05110	5.0	50	110	7.56
SDHP05160	5.0	100	160	8.21
SDHP55110	5.5	50	110	7.79
SDHP55160	5.5	100	160	8.55
SDHP06110	6.0	50	110	7.39
SDHP06160	6.0	100	160	8.15
SDHP06210	6.0	150	210	10.88
SDHP06260	6.0	200	260	14.70
SDHP65210	6.5	150	210	14.11
SDHP65260	6.5	200	260	19.65
SDHP07110	7.0	50	110	9.93
SDHP07160	7.0	100	160	10.78
SDHP08110	8.0	50	110	8.63
SDHP08160	8.0	100	160	9.43
SDHP08210	8.0	150	210	10.61
SDHP10110	10.0	50	110	9.25
SDHP10160	10.0	100	160	11.11
SDHP10210	10.0	150	210	12.21
SDHP10260	10.0	200	260	15.69
SDHP10450	10.0	400	450	35.06

Part Number	Diameter mm	Working Length mm	Overall Length mm	Price £ Per Each
SDHP12160	12.0	100	160	13.39
SDHP12210	12.0	150	210	14.80
SDHP12260	12.0	200	260	18.57
SDHP12450	12.0	400	450	38.05
SDHP14160	14.0	100	160	17.64
SDHP14210	14.0	150	210	24.18
SDHP14310	14.0	250	310	30.05
SDHP15160	15.0	100	160	24.93
SDHP16210	16.0	150	210	29.94
SDHP16310	16.0	250	310	41.93
SDHP16450	16.0	400	450	51.07
SDHP18250	18.0	200	250	45.31
SDHP18450	18.0	400	450	56.52
SDHP20250	20.0	200	250	49.79
SDHP20450	20.0	350	400	64.15
SDHP22250	22.0	200	250	57.57
SDHP22450	22.0	400	450	76.03

SDS MAX DRILL BITS

- ✓ For Drilling Into Concrete, Natural Stone And Masonry
- ✓ Cross Head Design
- ✓ Four Tungsten Carbide Cutting Edges
- ✓ Four Cutting Heads
- ✓ High Efficiency
- ✓ For SDS Max Heavy-Duty Hammer Drilling



Part Number	Diameter mm	Working Length mm	Overall Length mm	Price £ Per Each
MAX12340	12.0	188	340	9.17
MAX12540	12.0	388	540	17.33
MAX13340	13.0	188	340	9.56
MAX13540	13.0	388	540	16.56
MAX14340	14.0	188	340	10.17
MAX14540	14.0	388	540	16.83
MAX14690	14.0	538	690	21.28
MAX15340	15.0	188	340	12.67
MAX15540	15.0	388	540	17.72
MAX16340	16.0	188	340	11.44
MAX16540	16.0	388	540	16.67
MAX16690	16.0	538	690	20.11
MAX18340	18.0	188	340	12.50
MAX18540	18.0	388	540	17.67
MAX20370	20.0	218	370	13.17
MAX20520	20.0	368	520	18.78
MAX20920	20.0	768	920	53.11
MAX22370	22.0	218	370	17.44
MAX22520	22.0	368	520	19.78
MAX22920	22.0	768	920	46.83

Part Number	Diameter mm	Working Length mm	Overall Length mm	Price £ Per Each
MAX24370	24.0	218	370	16.78
MAX24520	24.0	368	520	23.17
MAX25320	25.0	168	320	17.50
MAX25520	25.0	368	520	23.44
MAX25920	25.0	768	920	53.28
MAX26370	26.0	218	370	21.61
MAX26520	26.0	368	520	26.11
MAX28370	28.0	218	370	23.33
MAX28570	28.0	418	570	30.11
MAX30370	30.0	218	370	30.00
MAX30570	30.0	418	570	36.28
MAX32370	32.0	218	370	32.72
MAX32570	32.0	418	570	43.78
MAX32920	32.0	768	920	79.00
MAX35570	35.0	418	570	53.61
MAX38570	38.0	418	570	68.22
MAX40570	40.0	418	570	90.28

SDS+ DRILL BIT SETS

- ✓ For Drilling Into Concrete, Natural Stone And Masonry
- ✓ High Strength Steel To Avoid Bending Or Snapping
- ✓ Tungsten Carbide Tip ✓ Heavy Duty Drilling ✓ Two Tungsten Carbide Cutting Edges

Part Number	Description	Price £ Per Each
SDSET5	5 Piece Set - 5, 5.5, 6, 7 and 8mm	8.39
SDSET8	8 Piece Set - 5, 5.5, 6, 6.5, 7, 8, 10 and 12mm	15.01



SDSET5



SDSET8

MASONRY DRILL BITS

- ✓ For Drilling Into Brick, Block And Natural Stone ✓ Straight Shank ✓ For Percussion And Rotary Drilling
- ✓ Tungsten Carbide Tip For Greater Wear ✓ Size Stamped On Body

Part Number	Diameter mm	Working Length mm	Overall Length mm	Price £ Per Each
JMD04085	4.0	50	85	1.01
JMD45085	4.5	50	85	1.01
JMD05085	5.0	50	85	1.06
JMD05150	5.0	90	150	1.54
JMD55100	5.5	60	100	1.06
JMD55150	5.5	90	150	1.59
JMD06100	6.0	60	100	1.12
JMD06150	6.0	90	150	1.70
JMD06200	6.0	140	200	2.02
JMD65100	6.5	60	100	1.12
JMD65150	6.5	90	150	1.70
JMD65400	6.5	300	400	7.33
JMD07100	7.0	60	100	1.28
JMD07150	7.0	90	150	1.70
JMD08120	8.0	80	120	1.43
JMD08150	8.0	90	150	1.70
JMD08200	8.0	140	200	2.13
JMD08300	8.0	240	300	3.19
JMD08400	8.0	300	400	5.85
JMD10120	10.0	80	120	1.70
JMD10150	10.0	90	150	1.97
JMD10200	10.0	140	200	2.34
JMD10300	10.0	240	300	3.24
JMD10400	10.0	300	400	4.52
JMD10600	10.0	500	600	7.55
JMD101000	10.0	900	1000	16.74

Part Number	Diameter mm	Working Length mm	Overall Length mm	Price £ Per Each
JMD12150	12.0	90	150	2.60
JMD12200	12.0	140	200	2.71
JMD12300	12.0	240	300	3.61
JMD12400	12.0	300	400	6.32
JMD12600	12.0	500	600	7.97
JMD13400	13.0	300	400	6.64
JMD14150	14.0	90	150	3.83
JMD14200	14.0	140	200	5.05
JMD14400	14.0	300	400	6.32
JMD16150	16.0	90	150	4.25
JMD16200	16.0	140	200	5.21
JMD16300	16.0	240	300	5.90
JMD16400	16.0	300	400	6.96
JMD18200	18.0	140	200	6.16
JMD20160	20.0	100	160	7.23
JMD20200	20.0	140	200	7.71
JMD20300	20.0	240	300	8.61
JMD20400	20.0	300	400	9.94
JMD25160	25.0	100	160	8.61
JMD25200	25.0	140	200	10.42
JMD25300	25.0	240	300	12.22
JMD25400	25.0	300	400	14.93

MASONRY DRILL BIT SETS

- ✓ For Drilling Into Brick, Block And Natural Stone ✓ Straight Shank ✓ For Percussion And Rotary Drilling
- ✓ Tungsten Carbide Tip For Greater Wear ✓ Size Stamped On Body

Part Number	Description	Price £ Per Each
JMDSET5	5 Piece Set - 5, 5.5, 6, 7 and 8mm	6.25





HSS DRILL BITS

- ✓ For Drilling Into Alloyed Carbon And Plain Steel
- ✓ Ideal For Handheld Operations
- ✓ Twist Drill
- ✓ Hardwearing
- ✓ 135° Split Point Prevents Bit From Drifting And Enables Faster Penetration



Part Number	Diameter mm	Overall Length mm	Pack Quantity	Price £ Per Each
HSS010	1.0	34	10	1.08
HSS015	1.5	40	10	1.08
HSS016	1.6	43	10	1.15
HSS020	2.0	49	10	1.08
HSS022	2.2	53	10	1.15
HSS024	2.4	57	10	1.15
HSS025	2.5	57	10	1.08
HSS026	2.6	57	10	1.15
HSS028	2.8	61	10	1.15
HSS030	3.0	61	10	1.08
HSS032	3.2	65	10	1.25
HSS033	3.3	65	10	1.36
HSS034	3.4	70	10	1.36
HSS035	3.5	70	10	1.36
HSS036	3.6	70	10	1.36
HSS038	3.8	75	10	1.36
HSS040	4.0	75	10	1.35
HSS042	4.2	75	10	1.46
HSS045	4.5	80	10	1.61
HSS048	4.8	86	10	1.61
HSS050	5.0	86	10	1.79
HSS052	5.2	86	10	1.79
HSS055	5.5	93	10	1.88
HSS058	5.8	93	10	2.17
HSS060	6.0	93	10	2.25

Part Number	Diameter mm	Overall Length mm	Pack Quantity	Price £ Per Each
HSS062	6.2	101	10	2.39
HSS064	6.4	101	10	2.39
HSS065	6.5	101	10	2.39
HSS066	6.6	101	10	2.52
HSS068	6.8	109	10	2.79
HSS070	7.0	109	10	2.79
HSS072	7.2	109	10	2.94
HSS075	7.5	109	10	3.20
HSS078	7.8	117	10	3.47
HSS080	8.0	117	10	3.47
HSS082	8.2	117	10	3.73
HSS085	8.5	117	10	3.87
HSS088	8.8	125	10	4.19
HSS090	9.0	125	10	4.19
HSS094	9.4	125	10	4.57
HSS095	9.5	125	10	4.57
HSS098	9.8	133	10	4.95
HSS100	10.0	133	5	4.95
HSS102	10.2	133	5	4.95
HSS105	10.5	133	5	5.53
HSS110	11.0	142	5	6.44
HSS115	11.5	142	5	6.80
HSS120	12.0	151	5	7.75
HSS125	12.5	151	5	8.15
HSS130	13.0	151	5	8.42



HSS DRILL BITS (In Wallets)

- ✓ For Drilling Into Alloyed Carbon And Plain Steel
- ✓ Hardwearing
- ✓ Ideal For Handheld Operations
- ✓ 135° Split Point Prevents Bit From Drifting And Enables Faster Penetration
- ✓ Twist Drill



Part Number	Diameter mm	Overall Length mm	Pack Quantity	Price £ Per Each
HSSW010	1.0	34	3	4.15
HSSW015	1.5	40	3	4.15
HSSW020	2.0	49	3	4.15
HSSW025	2.5	57	3	4.15
HSSW030	3.0	61	3	4.15
HSSW035	3.5	70	2	3.74
HSSW040	4.0	75	2	3.74
HSSW045	4.5	80	2	4.23
HSSW050	5.0	86	2	4.61
HSSW055	5.5	93	2	4.76
HSSW060	6.0	93	2	5.48
HSSW065	6.5	101	1	3.47

Part Number	Diameter mm	Overall Length mm	Pack Quantity	Price £ Per Each
HSSW070	7.0	109	1	3.84
HSSW075	7.5	109	1	4.23
HSSW080	8.0	117	1	4.46
HSSW085	8.5	117	1	4.85
HSSW090	9.0	125	1	5.08
HSSW095	9.5	125	1	5.42
HSSW100	10.0	133	1	5.87
HSSW105	10.5	133	1	6.36
HSSW110	11.0	142	1	7.21
HSSW115	11.5	142	1	7.62
HSSW120	12.0	151	1	8.46
HSSW125	12.5	151	1	8.91
HSSW130	13.0	151	1	9.12



HSS DRILL BITS (Imperial)

- ✓ For Drilling Into Alloyed Carbon And Plain Steel
- ✓ Ideal For Handheld Operations
- ✓ Twist Drill
- ✓ Hardwearing
- ✓ 135° Split Point Prevents Bit From Drifting And Enables Faster Penetration



Part Number	Diameter "	Overall Length mm	Pack Quantity	Price £ Per Each
HSSI00116	1/16	43	10	1.15
HSSI00332	3/32	57	10	1.15
HSSI00764	7/64	61	10	1.15
HSSI00108	1/8	65	10	1.25
HSSI00964	9/64	70	10	1.36
HSSI00532	5/32	75	10	1.35
HSSI001164	11/64	80	10	1.46
HSSI00316	3/16	80	10	1.61
HSSI001364	13/64	86	10	1.79
HSSI00732	7/32	93	10	2.17
HSSI00104	1/4	101	10	2.39
HSSI001764	17/64	109	10	2.79
HSSI00932	9/32	109	10	2.94
HSSI00516	5/16	117	10	3.47
HSSI001132	11/32	125	10	4.01
HSSI00308	3/8	133	10	4.57
HSSI001332	13/32	133	5	4.95
HSSI00716	7/16	142	5	6.44
HSSI00102	1/2	151	5	8.42



COBALT HSS DRILL BITS

- ✓ For Drilling Into High Alloyed Steels, Bearing Steels, Hot/Cold Rolled Steel, And Stainless Steel
- ✓ Long Lasting Performance
- ✓ Cobalt Alloy
- ✓ Ideal For Handheld Operations



Part Number	Diameter mm	Overall Length mm	Pack Quantity	Price £ Per Each
COB020	2.0	49	10	3.69
COB025	2.5	57	10	3.98
COB030	3.0	61	10	3.98
COB033	3.3	65	10	4.49
COB035	3.5	70	10	4.49
COB040	4.0	75	10	4.79
COB042	4.2	75	10	5.97
COB045	4.5	80	10	6.07
COB050	5.0	86	10	5.86
COB055	5.5	93	10	8.13
COB060	6.0	93	10	7.65
COB065	6.5	101	10	8.64
COB068	6.8	109	10	10.16
COB070	7.0	109	10	9.06
COB075	7.5	109	10	9.59

Part Number	Diameter mm	Overall Length mm	Pack Quantity	Price £ Per Each
COB080	8.0	117	10	11.97
COB085	8.5	117	10	11.74
COB090	9.0	125	10	15.35
COB095	9.5	125	10	17.95
COB100	10.0	133	5	17.39
COB105	10.5	133	5	25.14
COB110	11.0	142	5	27.84
COB115	11.5	142	5	35.30
COB120	12.0	151	5	40.09
COB125	12.5	151	5	47.87
COB130	13.0	151	1	51.46



HSS REDUCED SHANK DRILL BITS

- ✓ For Drilling Into Alloyed Carbon And Plain Steel
- ✓ Hardwearing
- ✓ Ideal For Handheld Operations
- ✓ Allow For Drilling Larger Holes With Standard Drill Chucks
- ✓ Toughness And Precision Allow For Excellent Cutting Efficiency
- ✓ Twist Drill



Part Number	Diameter mm	Overall Length mm	Pack Quantity	Price £ Per Each
HSSRS14	14.0	160	5	13.24
HSSRS15	15.0	169	5	15.09
HSSRS16	16.0	178	3	17.89

Part Number	Diameter mm	Overall Length mm	Pack Quantity	Price £ Per Each
HSSRS17	17.0	184	3	25.34
HSSRS18	18.0	191	3	27.43
HSSRS20	20.0	205	3	40.63



HSS LONG SHANK DRILL BITS



- ✓ For Drilling Into Alloyed Carbon And Plain Steel
- ✓ Hardwearing
- ✓ Ideal For Handheld Operations
- ✓ Long Shank Enables Deeper Drilling Capability
- ✓ Toughness And Precision Allow For Excellent Cutting Efficiency
- ✓ Twist Drill

Part Number	Diameter mm	Overall Length mm	Pack Quantity	Price £ Per Each	Part Number	Diameter mm	Overall Length mm	Pack Quantity	Price £ Per Each
HSSLS030	3.0	100	1	2.96	HSSLS048	4.8	132	1	5.43
HSSLS032	3.2	100	1	3.18	HSSLS050	5.0	132	1	4.68
HSSLS035	3.5	112	1	3.36	HSSLS060	6.0	139	1	5.83
HSSLS040	4.0	119	1	3.71	HSSLS080	8.0	165	1	8.83

HSS DRILL BIT CASES



- ✓ HSS For Drilling Into Alloyed Carbon And Plain Steel
- ✓ Cobalt For Drilling Into High Alloyed Steels, Bearing Steels, Hot/Cold Rolled Steel, And Stainless Steel

Part Number	Description	Price £ Per Each
HSSTM06	6 Piece HSS Set - 2 - 8mm in Plastic Case	18.17
HSSTM10	10 Piece HSS Set - 1 - 10mm in Plastic Case	27.62
HSSKM19	19 Piece HSS Set - 1 - 10mm in Metal Case	39.00
HSSKM25	25 Piece HSS Set - 1 - 13mm in Metal Case	97.66
COBKM19	19 Piece HSS Cobalt Set - 1 - 10mm in Metal Case	102.90
COBKM25	25 Piece HSS Cobalt Set - 1 - 13mm in Metal Case	147.83



HSSTM06



HSSTM10



HSSKM19



HSSKM25



COBKM19



COBKM25

HSS COUNTERSINK DRILL BITS



- ✓ For Countersinking And Deburring Of Steels
- ✓ Three 90° Cutting Edges
- ✓ Used To Ensure Flat Headed Screws Sit Flush

Part Number	Description	Price £ Per Each
HSSCS0803	8.3mm (M4)	15.38
HSSCS1004	10.4mm (M5)	17.01
HSSCS1204	12.4mm (M6)	19.41
HSSCS1605	16.5mm (M8)	25.19
HSSCS2005	20.5mm (M10)	32.14
HSSCS2500	25.0mm (M12)	40.07



COBALT COUNTERSINK DRILL BITS

- ✓ For Countersinking And Deburring Of Steels
- ✓ Three 90° Cutting Edges
- ✓ Cobalt Alloy
- ✓ Particularly Suited For Use On Stainless Steel
- ✓ Used To Ensure Flat Headed Screws Sit Flush

Part Number	Diameter mm	Price £ Per Each
COBCS0803	8.3 (M4)	19.58
COBCS1004	10.4 (M5)	23.22
COBCS1204	12.4 (M6)	24.76
COBCS1605	16.5 (M8)	30.43
COBCS2005	20.5 (M10)	41.60
COBCS2500	25.0 (M12)	55.92
COBCS3100	31.0 (M16)	85.76



COBALT SLOTTED COUNTERSINK DRILL BITS

- ✓ For Countersinking And Deburring Of Steels
- ✓ Three 90° Cutting Edges
- ✓ Particularly Suited For Use On Stainless Steel
- ✓ Used To Ensure Flat Headed Screws Sit Flush
- ✓ Spoil Is Removed Through The Centre Of The Cutter To Prevent Damage To Tool

Part Number	Diameter	Price £ Per Each
COBSL0205	M2-M5 90°	19.91
COBSL0510	M5-M10 90°	27.14



MULTIDRILL TUNGSTEN CARBIDE UNIVERSAL DRILL BITS

- ✓ For Drilling Into Various Materials
- ✓ Universal And Versatile
- ✓ Four Step Profile For Fast Dust Extraction
- ✓ Carbide Tip
- ✓ Precise Drilling

Part Number	Diameter mm	Overall Length mm	Pack Quantity	Price £ Per Each
MUL040075	4.0	75	1	7.02
MUL050085	5.0	85	1	7.22
MUL050150	5.0	150	1	8.30
MUL055085	5.5	85	1	7.32
MUL055150	5.5	150	1	9.20
MUL060100	6.0	100	1	7.40
MUL060200	6.0	200	1	8.76
MUL065100	6.5	100	1	7.50
MUL065200	6.5	200	1	10.67
MUL070100	7.0	100	1	8.61
MUL070200	7.0	200	1	11.50
MUL080120	8.0	120	1	9.32
MUL080200	8.0	200	1	11.50
MUL100120	10.0	120	1	10.70
MUL100200	10.0	200	1	13.36
MUL120220	12.0	220	1	14.68
MUL140220	14.0	220	1	16.67
MULSET	4,5,6,8,10	-	1	31.54





AUGER DRILL BITS

- ✓ For Drilling Into Wood
- ✓ The Screw Tip Keeps The Drill Bit Accurate Throughout The Drilling
- ✓ Hexagon Shank For Improved Hold In The Drill Chuck
- ✓ A Spiral-Shaped Bit With A Threaded Tip At The Front And Two Chisels At Each Tip End

Part Number	Diameter mm	Overall Length mm	Pack Quantity	Price £ Per Each
AUG06230	6.0	230	1	1.78
AUG08230	8.0	230	1	1.87
AUG08460	8.0	460	1	3.16
AUG10230	10.0	230	1	2.19
AUG10460	10.0	460	1	3.61
AUG12230	12.0	230	1	2.68
AUG12460	12.0	460	1	4.42
AUG13230	13.0	230	1	2.80
AUG14230	14.0	230	1	3.00
AUG14460	14.0	460	1	5.39
AUG16230	16.0	230	1	3.57
AUG16460	16.0	460	1	6.61

Part Number	Diameter mm	Overall Length mm	Pack Quantity	Price £ Per Each
AUG18230	18.0	230	1	4.06
AUG18460	18.0	460	1	7.66
AUG19230	19.0	230	1	5.19
AUG20230	20.0	230	1	4.95
AUG20460	20.0	460	1	9.25
AUG22230	22.0	230	1	5.76
AUG25230	25.0	230	1	6.25
AUG25460	25.0	460	1	12.77
AUG28230	28.0	230	1	8.64
AUG30230	30.0	230	1	9.45
AUG32230	32.0	230	1	10.42



FLAT WOOD BITS

- ✓ For Drilling Larger Holes Into Wood, Rapidly
- ✓ Available Up To 38mm
- ✓ The Centre Spur Keeps The Drill Bit Accurate Throughout The Drilling

Part Number	Diameter mm	Overall Length mm	Price £ Per Each
FW06	6.0	158	1.54
FW08	8.0	158	1.54
FW10	10.0	158	1.54
FW12	12.0	158	1.83
FW13	13.0	158	1.83
FW14	14.0	158	2.08
FW16	16.0	158	2.08
FW18	18.0	158	2.08
FW19	19.0	158	2.08

Part Number	Diameter mm	Overall Length mm	Price £ Per Each
FW20	20.0	158	2.25
FW22	22.0	158	2.29
FW24	24.0	161	2.42
FW25	25.0	161	2.42
FW28	28.0	161	3.17
FW30	30.0	174	3.17
FW32	32.0	174	3.46
FW35	35.0	174	4.04
FW38	38.0	174	4.13



CENTRE SPUR WOOD BITS

- ✓ For Drilling Holes Into Softwood And Plywood
- ✓ Cuts A Clean-Sided Hole
- ✓ The Centre Spur Keeps The Drill Bit Accurate Throughout The Drilling

Part Number	Diameter mm	Overall Length mm	Price £ Per Each
TP03	3.0	60	1.00
TP04	4.0	70	1.00
TP05	5.0	85	1.04
TP06	6.0	90	1.13
TP07	7.0	105	1.29

Part Number	Diameter mm	Overall Length mm	Price £ Per Each
TP08	8.0	110	1.33
TP09	9.0	115	1.50
TP10	10.0	120	1.71
TP12	12.0	140	2.38



TORX DRIVER BITS

- ✓ Torx Drive Enables Higher Torque Transmission Than Other Drive Systems
- ✓ Torx Drive Helps Prevent Cam out

Part Number	Pack Quantity	Price £ Per Each
T25	1	0.33
T30	1	0.42
T40	1	0.50

Part Number	Pack Quantity	Price £ Per Each
T45	1	0.58
T50	1	0.67



Merchandising Solutions

- ✓ Suitable for all JCP products
- ✓ Striking Livery
- ✓ Multiple Configurations



KEEP YOUR STORE VIBRANT WITH OUR MERCHANDISING SOLUTIONS

The JCP boxed, trade and retail bag range marry well, making for an eye-catching display. For more information on our new merchandising solutions, please contact your local sales office.

SUPPORTING YOU EVERY STEP OF THE WAY

Our Area Sales Managers have many years of experience in the field and are ready to work closely with our customers.

They can recommend and tailor a range of products that best suit your requirements.



MAKING FIXINGS LOOK GREAT IN A RETAIL ENVIRONMENT

TRADE AND RETAIL PACKAGING

The JCP trade and retail packaging is full of information, making it user-friendly and enabling correct product selection and application. They also look great on our merchandising stands in a retail environment.

RETAIL

The retail range follows a similar offering to the trade bag range, conveniently packed in smaller quantities.



TRADE

The trade bag range covers popular products and sizes from the JCP range. The packaging is robust, re-sealable, drop-proof, water-resistant, easy to identify, and an ideal size to carry.



All products within the trade and retail range are categorised into one of four categories, with each product clearly colour coded on the front label.



HEAVY DUTY



MEDIUM DUTY



NYLON AND CAVITY



SELF-DRILLING SCREWS



The see-through bags allow for quick product identification whilst the image on the front clearly depicts its use. Clear instructions for installation can be found on the rear, along with extended technical details to aid in application.

JHANG/384

AWA Throughbolt
Clear Zinc Plated

	M8	M10	M12	M16
Bolt Diameter (mm)	8	10	12	16
Thread Diameter	M8	M10	M12	M16
Head Depth (mm)	50	60	70	90
Minimum Structure Thickness (mm)	100	100	110	130
Picture Clearance Hole (mm)	9	12	14	18
Tightening Torque (Nm)	20	35	60	120

CE 14 JCP Construction Products Ltd. 1219 www.jcpfixings.co.uk

QR Code

The labels feature a QR code which takes the customer to the product technical data sheet.

The label also shows base material icons which the product is recommended for.



Concrete




Our Merchandising Representatives first assess the store area to be addressed and determine which configuration works best, ensuring that products are available and engaging at the point of sale. They will then oversee the building and positioning of the stands, along with loading them with stock. They will oversee all of the physical aspects of the project** whilst minimising disruption.

Our after-sales support includes representatives making regular visits to replenish stock and ensure the display remains looking its best.

- ✓ **Striking Livery**
- ✓ **Multiple Configurations To Suit Your Space And Product Offering**
- ✓ **Professional Installation With Minimal Disruption**
- ✓ **Maximise Sales Across Market Leading Brands**

POS DISPLAYS



Article Number: OJ0004
Large Magnetic Header 987 x 300mm



Article Number: OJ0088
Small Magnetic Header 987 x 200mm



Article Number: OJ0022
Small Magnetic Header/Footer 987 x 200mm



Article Number: OJ0008
Info Board 996 x 158mm



Article Number: OJ0027
Shelf Strip 998 x 38mm



Article Number: OJ0012
Hanging Banner 987 x 200mm
(Includes Banner Arm)

** Excluding fixing the stand down.

STAND OPTIONS

ARTICLE NUMBER: OJ0019

SIZE: 2200 X 1000 X 470mm

Merchandising Stand With 5 Shelves

ARTICLE NUMBER: OJ0001

SIZE: 2200 X 1000 X 470mm

Merchandising Stand
With 50/50 Shelved and Perforated

ARTICLE NUMBER: OJ0040

SIZE: 2200 X 1000 X 470mm

Merchandising Stand Fully Perforated

ARTICLE NUMBER: OJ0020

SIZE: 1400 X 1000 X 470mm

Merchandising Stand With 3 Shelves

ARTICLE NUMBER: OJ0016

SIZE: 1400 X 1000 X 470mm

Merchandising Stand
With 50/50 Shelved and Perforated

ARTICLE NUMBER: OJ0021

SIZE: 1400 X 1000 X 470mm

Merchandising Stand Fully Perforated

A range of stand extras are also available.
See the merchandising stand brochure for
more information.

**Ask your Area Sales Manager for a printed copy of our
merchandising stands brochure or download a copy here**



Download here





CUSTOMER SUPPORT

A range of marketing support exclusively for our distributors.

As a stockist of JCP products we are here to support you. Our range of marketing support materials includes branded wall stickers, posters and banners suitable for internal and external displays.

For more information, speak to your Area Sales Manager.

WINDOW STICKERS

Help your store stand out with our branded window sticker.

BRAND	SIZE
JCP	150mm x 150mm




OUTDOOR BANNERS


Our branded banners are ideal for eye-catching indoor and outdoor advertising. PVC-free, they are fully recyclable and an environmentally friendly alternative to PVC banners.



BRAND	SIZE
JCP	2000mm x 600mm



PRINTED AND DOWNLOADABLE POSTERS



A range of branded posters showcasing features, benefits and range highlights.

Ideal for advertising in-store.

Can be put into an existing frame or fixed to the wall.

All posters are available for instant download.

Download here



BRAND	SIZE
JCP	Printed A1 - Download A1 or A3
JCP Range Guide	Printed A1 - Download A1
JCP Self-Drillers Range	Download A1





JCP
CONSTRUCTION
PRODUCTS®
SPECIALIST FIXINGS BACKED
BY TECHNICAL SUPPORT
www.jcpfixings.co.uk
AVAILABLE IN-STORE

- HEAVY DUTY ANCHORS
- CHEMICAL ANCHORS
- MEDIUM DUTY ANCHORS
- SELF-DRILLING SCREWS
- LIGHT DUTY FIXINGS
- NYLON AND CAVITY FIXINGS
- PA AND GAS
- DRILL BITS

RANGE GUIDE

JCP
CONSTRUCTION
PRODUCTS®

HEAVY DUTY ANCHORS	 THROUGHBOLTS	 OPTION 1 THROUGHBOLTS	 OPTION 7 THROUGHBOLTS	 THROUGHBOLTS STAINLESS STEEL	 WIREHANGERS	 NAIL IN SOCKETS	 ANKERBOLTS	 OPTION 1 ANKERBOLTS	 ANKERBOLTS STAINLESS STEEL	 SOCKET BOLTS	 HOOK BOLTS AND EYE BOLTS	 DROP IN ANCHORS
	 APPROVED DROP IN ANCHORS	 DROP IN ANCHOR SETTING PUNCHES	 STOP DRILL BITS	 FORGED HOOK AND EYE BOLTS	 SCAFFOLD EYES AND PLUGS	 OPTION 1 HEAVY DUTY ANCHORS	 BLINDBOLTS	 BLINDBOLTS HEAVY DUTY BOLTS	 BLINDBOLTS THIN WALL BOLTS			
CHEMICAL ANCHORS AND ACCESSORIES	 PURE EPOXY RESINS	 VINYLESTER RESINS	 EPOXY ACRYLATE RESINS	 POLYESTER STYRENE FREE RESINS	 POLYESTER RESINS	 SPIN IN CAPSULES	 HAMMER IN CAPSULES	 ROCKITE (Interior)	 KWIKSET (Exterior)	 J-FIX STUDS	 INTERNAL THREADED SOCKETS	 INJECTION RESIN SLEEVE
	 INJECTION RESIN ACCESSORIES	 CRACK STITCHING	 B3 RATED FOAM	 B2 RATED FOAM	 B1 RATED FOAM	 B1 FIRE SEALANT	 INTUMESCENT AND ACOUSTIC MASTIC	 POLYURETHANE CLEANER				
MEDIUM DUTY ANCHORS	 SLEEVE ANCHORS	 SLEEVE ANCHORS STAINLESS STEEL	 EYE AND HOOK BOLT SLEEVE ANCHORS	 SHIELD ANCHORS	 SHIELD ANCHORS STAINLESS STEEL	 EYE BOLT AND HOOK BOLT SHIELD ANCHORS	 CONCRETE SCREWS					
SELF DRILLING SCREWS	 SELF-DRILLING SCREWS HEAVY SECTION	 SELF-DRILLING SCREWS LIGHT SECTION	 STITCHING SCREWS	 GASH POINT SCREWS	 WOODFIX SCREWS	 FIBRE CEMENT SCREWS	 COVER CAPS	 VERTICAL HANGERS	 HORIZONTAL HANGERS			
LIGHT DUTY FIXINGS	 NAIL IN ANCHORS	 PLASTIC HEADED NAILS	 MASONRY NAILS	 SANITARY FIXINGS	 VERTICAL FLANGE CLIPS	 ANGLE BRACKETS	 WALL SCREWS	 BIGTWIST NAILS	 FIXING BANDS			
NYLON AND CAVITY FIXINGS	 HAMMER SCREWS	 NYLON FRAME FIXINGS	 APPROVED NYLON FRAME FIXINGS	 PUSH PLUGS	 NYLON PLUGS	 PLASTIC PLUGS	 METAL PLUGS	 PLASTERBOARD FIXINGS	 ROSETT CAVITY FIXINGS	 ANKERNUTS	 HOLLOW WALL ANCHORS	
	 SPRING TOGGLES	 PLASTIC TOGGLES										
PA AND GAS	 DRIVEFAST NAILS	 CEILING HANGERS	 TOOL KIT P897	 POWDER ACTUATED DRIVE PINS								
DRILL BITS	 SDS+ DRILL BITS	 MASONRY DRILL BITS	 HIGH SPEED DRILL BITS	 REDUCED SHANK DRILL BITS	 LONG SHANK DRILL BITS	 COUNTERSINK BITS	 AUGER DRILL BITS	 FLAT WOOD BITS	 CENTRE SPUR WOOD BITS	 TORX DRIVER BITS		





INDEX

Alloy Nail In Anchors.....	79	Hexagon Bolt Heavy Duty Anchors	34-35	Polyester Resin	43
Alpen Drill Bits	106, 108-111	Hexagon Bolt Sleeve Anchors	55	Polyurethane Cleaner	52
Angle Brackets	83	Hexagon Flange Head Ankerbolts	20-21, 24-25	Pozi Pan Head Self-Drilling Screws	67
Ankerbolts	20-26	Hexagon Head Ankerbolts	22-24	Premium Nylon Wall Plugs	93
Ankerbolt Drop In Anchors.....	26	Hexagon Head Nylon Frame Fixings.....	91	Projecting Bolt Shield Anchors	58-59
Ankerbolt Drop In Setting Tool	31	Hexagon Flange Nut Sleeve Anchors	54, 56	Pure Epoxy Resin.....	41
Ankernuts	97	High Speed Steel Drill Bits	108-110	Push Plugs	92
Applicator Guns	49	Hollow Wall Anchors	98	Road Fixing Kit	97
Auger Drill Bits	112	Hollow Wall Anchor Setting Tool	98	Rockite.....	44
B1 Rated Expanding Foam	53	Hook Bolts	27	Rosett Cavity Fixings.....	96
B3 Rated Expanding Foam	53	Hook Bolt Shield Anchors	60	Round Perforated Fixing Band	87
Basin Fixings	82	Hook Bolt Sleeve Anchors	56	Sanitary Fixings	82
Bigtwist Nails	86	Hot Dipped Galvanised Throughbolts.....	17	Scaffold Eye Plugs	33
Bi-Metal Masonry Screws	26	Hot Dipped Galvanised J-Fix Studs	46-47	Scaffold Retaining Eyes	33
Blind Bolts	37-39	HSS Cobalt High Speed Steel Drill Bits.....	109	Scaffold Ring Bolts	33
Blow Out Pump	50	HSS Countersink Drill Bits	110	SDS+ Drill Bits	105-107
Brad Nails and Gas	102	HSS Drill Bit Cases	110	SDS+ High Performance Drill Bits	106
Bright Zinc Plated Ankerbolt	20-24	HSS Long Shank Drill Bits	110	SDS+ Drill Bit Sets	107
Bright Zinc Plated Drop In Anchors	28-31	HSS Reduced Shank Drill Bits	109	SDS Max Drill Bits	106
Bright Zinc Plated Fibre Cement Screws.....	74	Imperial High Speed Steel Drill Bits	109	Self-Drilling Screws	63-77
Bright Zinc Plated Heavy Duty Anchors.....	24-25	Injection Resin Accessories	49-50	Setting Tool for Rod Hangers	77
Bright Zinc Plated Internal Threaded Sockets.....	48	Injection Resin Internally Threaded Sockets	48	Shield Anchors.....	57-60
Bright Zinc Plated J-Fix Studs	45-46	Injection Tool Accessories	49	Shield Only Shield Anchors	59
Bright Zinc Plated Metalfix.....	63-73	Injection Tools	49	Shot Fired Pins	104
Bright Zinc Plated Throughbolts	15-16	Internal Threaded Sockets	48	Sleeve Anchors.....	54-56
Bright Zinc Plated Woodfix	72-73	JCP Bulk Plastic Plugs	94	Socket Bolts	26-27
Cartridge Strips	103	JCP Premium Plastic Plugs	94	Spin In Capsules	44
Cartridge Tool	103	JCP Standard Plastic Plugs	93	Spring Toggles	99
Ceiling Hangers	103	J-Fix Epoxy Acrylate Resin.....	43	Stainless Steel Brad Nails	102
Cementitious Grout.....	52	J-Fix Hammer In Glass Capsules.....	44	Stainless Steel Clipped Head Drivefast Gas Nails	100
Centre Spur Wood Bits	112	J-Fix Polyester Resin	43	Stainless Steel Heavy Duty Blind Bolts	39
Chemical Anchors and Accessories	41-53	J-Fix Polyester Styrene Free Resin	43	Stainless Steel A2 Eye Bolt Sleeve Anchors	56
Cleaning Brushes	50	J-Fix Pure Epoxy Resin	41	Stainless Steel A2 Fixing Bands	87
Clipped Head Drivefast Gas Nails.....	100-101	J-Fix Spin In Glass Capsules	44	Stainless Steel A2 Hammer Screws	89
Clipped Head Drivefast Nails Only	101	J-Fix Studs	45-48	Stainless Steel A2 Internal Threaded Sockets	48
Cobalt Countersink Drill Bits	111	J-Fix Ultra Bond 100 Epoxy Resin.....	41	Stainless Steel A2 J Fix Studs	47
Cobalt Slotted Countersink Drill Bits	111	J-Fix Vinylester Resin	42	Stainless Steel A2 Metalfix	64-68
Coloured Cover Caps	75	J-Fix Vinylester Fast Cure Winter Grade Resin.....	42	Stainless Steel A2 Metalfix Stitching Screw	68
Concrete Screws	62	J-Plug Plasterboard Fixings.....	95	Stainless Steel A2 Sleeve Anchors	56
Concrete Screws Cover Caps	62	Kwixset	45	Stainless Steel A2 Stitching Bar	52
Countersunk Head Ankerbolts	23, 25	Light Duty Fixings	79-87	Stainless Steel A2 Thin Wall Bolts	39
Countersunk Head Hammer Screws	88-89	Lipped Drop In Anchors	29-30	Stainless Steel A2 Throughbolts.....	17
Countersunk Head Sleeve Anchors	55-56	Loose Bolt Shield Anchors	57	Stainless Steel A4 Ankerbolts	25
Countersunk Head Wall Screws	84	Low Profile Metalfix Self-Drilling Screws	69	Stainless Steel A4 Blind Bolts	38-39
Countersunk Heavy Duty Anchors	35-36	Magazine Pins	104	Stainless Steel A4 Drop In Anchors	29-30
Countersunk Nylon Frame Fixing	90-91	Magnetic Drive Sockets	70	Stainless Steel A4 Heavy Duty Anchors	35-36
Cover Caps	75	Masonry Drill Bits	107	Stainless Steel A4 Internal Threaded Sockets	49
Crack Stitch Twist Starter Kit	51	Masonry Drill Bit Sets	107	Stainless Steel A4 J-Fix Studs	47-48
Drill Bits	105-112	Masonry Nails	81	Stainless Steel A4 Lipped Drop In Anchors	29
Drivefast Gas Nails	100-102	Masonry Nails with Washer	81	Stainless Steel A4 Nylon Frame Fixings.....	91
Drivefast Gas Only	102	Mechanical Galvanised Ankerbolts	24	Stainless Steel A4 Shield Anchors.....	59
Drop In Anchors	28-30	Mechanical Galvanised Fixing Bands	87	Stainless Steel A4 Sleeve Anchors.....	56
Drop In Anchor Setting Punches	31	Medium Duty Anchors	54-62	Stainless Steel A4 Throughbolts.....	18
Dual Threaded and Single Thread Socket Bolts.....	26	Metal Expansion Plugs	94	Steel Nail In Anchors	79
Epoxy Acrylate Resin	43	Metal Nail In Anchors.....	79	Stitching Bar	52
ETA Approved Drop In Anchors	28-30	Metalfix Self-Drilling Screws	63-70	Stop Drill Bits	31
ETA Drop In Anchor Setting Punches.....	31	Metalfix High Thread Self-Drilling Screws	69	Straight Perforated Fixing Band	87
ETA Approved Nylon Frame Fixings.....	91	Metalfix Horizontal Hangers	76	Straight Shank Masonry Drill Bit Sets	107
ETA Dual Threaded Socket Bolts	27	Metalfix Loose Washers	67	Straight Shank Masonry Drill Bits	107
ETA Option 1 Ankerbolts	21, 23	Metalfix Magnetic Socket	70	Stud and Nut Heavy Duty Anchors	35-36
ETA Option 1 Heavy Duty Anchors	34-36	Metalfix Stitching Screws.....	68	Thin Wall Blind Bolts.....	39
ETA Option 1 Throughbolts	15, 18	Metalfix Vertical Hangers	76	Throughbolts.....	14-18
ETA Option 7 Throughbolts	16, 18	Mixer Nozzles	49	Tool Kit PA97	103
ETA Socket Bolts	26	Multidrill Tungsten Carbide Universal Drill Bits	111	TX Driver Bits	112
Expanding Foam	53	Mushroom Head Nylon Hammer Screws	89	Universal Wall Plugs	93
Eye Bolt Shield Anchors	60	Nail In Anchors	79	Vertical Flange Clips.....	83
Eye Bolt Sleeve Anchors	56	Nail In Sockets	19	Vinylester Fast Cure Resin	42
Eye Bolts	32	Nylon and Cavity	88-99	Vinylester Resin	42
Eye and Hook Bolt Sleeve Anchors.....	56	Nylon Frame Fixings.....	90-91	Wafer Head Self-Drilling Screws	70
Fibre Cement Screws	74	Nylon Hammer Screws.....	88-89	Wall Screws.....	84-85
Fixing Bands	87	Nylon Sleeves.....	50	W.C. Fixings	82
Flange Head Hammer Screws	89	Nylon Toggles	99	Wirehangers	19
Fiat Wood Bits	112	Nylon Wall Plugs	92	Wire Cleaning Brushes	50
Forged Eye Bolts	32	PA97 Cartridge Tool Kit	103	Wire Mesh Sleeve	50
Forged Hook Bolts	32	PA and Gas	100-104	Woodfix Drive Bit	73
Galvanised Fixing Band	87	Pan Head Ankerbolts.....	24-25	Woodfix Self-Drilling Screws	71-73
Galvanised Angled Brads	102	Pan Head Wall Screws	85	Zinc and Yellow Plated Drop In Anchors.....	28-29
Gash Point Horizontal Hangers	77	Plain Ended J-Fix Studs	46, 47	Zinc and Yellow Plated Hollow Wall Anchors	98
Gash Point Vertical Hangers	77	Plasterboard Fixings	95	Zinc and Yellow Plated J-Fix Studs	45-48
General Purpose Metalfix Self-Drilling Screws.....	66	Plasterboard Plugs	96	Zinc and Yellow Plated Nylon Frame Fixings	90
Glass Capsules	44	Plastic Coated Fixing Bands	87	Zinc and Yellow Plated Nylon Hammer Screws	88-89
Hammer In Capsules	44	Plastic Headed Nails	80	Zinc and Yellow Plated Shield Anchors	57-60
Hammer Screws	88-89	Plastic Toggles	99	Zinc and Yellow Plated Sleeve Anchors	54-55
Handi Pack Drivefast	102	Plastic Wall Plugs	92-93	Zinc and Yellow Plated Spring Toggles	99
Heavy Duty Anchors	34-36	Plastic Washered Pins	104	Zinc and Yellow Plated Throughbolts	14
Heavy Duty Blind Bolts	38-39	Pointing Gun	51	Zinc Flake Blind Bolts	37-38
Heavy Duty Expansion Anchors	34-36	Polyester Styrene Free Resin.....	43	Zinc Nickel Thin Wall Blind Bolts	39

TERMS AND CONDITIONS OF SALE

1. APPLICATION

Unless otherwise agreed in writing between the company and its customer, the following terms and conditions of sales shall apply to all sales of goods by the company to its customer.

2. PRICE VARIATION

Price applicable to the sales of goods by the company to the customer shall be the price ruling at the date of despatch. The company therefore reserves the right to amend prices quoted at the date of the placing of an order by the customer by notifying the customer in writing.

3. CARRIAGE

The Company reserves the right as part of this contract to impose such surcharge or carriage charge as shall be laid down by the company policy at any time. Such terms will be available for examination at the address of the company shown on the letterhead of its invoices and are deemed to be part of all contracts unless specifically agreed to the contrary in writing by the company. The company has sole choice of method of delivery and of carrier or carriers employed unless specifically agreed in writing to the contrary.

4. DESPATCH

Despatch dates are quoted without engagement although every endeavour will be made to adhere to the date or dates quoted. In no circumstances shall the company be liable for any loss arising from delay in despatch however caused. Time shall not be of the essence of the contract.

5. DAMAGE AND LOSS IN TRANSIT

5.1 The company accepts no liability for any damage to goods in transit unless notified to the company and the carrier concerned within twenty four hours after delivery.

5.2 In the case of non-delivery the company accepts no liability of any sort unless written notice of non-delivery is given to the company within seven days after the date of the advice of despatch of the goods.

5.3 Paragraphs one and two shall not apply to despatches to countries outside the United Kingdom of Great Britain, Northern Ireland and the Isle of Man. In respect of these countries the company accepts no liability for damage or loss in transit unless the company has contracted to supply the goods C.I.F. and the customer has adhered to the terms of the insurance policy.

5.4 The company's liability for damage in transit or non-delivery of goods duly notified to it in accordance with the above, shall in any event be limited solely to replacement of the goods within a reasonable time, whether non-delivery or damage is due to the company's negligence or otherwise.

6. CLAIMS

Subject to the provision of condition 5, all claims for goods alleged to be defective must be made in writing to the company within seven days after the date of delivery. When notification is so received the company may require return of the goods or for the goods to be made available for inspection by the company. Should the company be satisfied as to the defects then it retains the option to either replace the defective goods within a reasonable time or credit to the customer within the contract price. All defective goods so returned shall be the property of the company. Except as provided above, the company shall have no liability whatsoever arising out of any agreement to sell or sale of goods including claims for direct consequential or other loss, damage or expense, whether arising or alleged to arise under any warranty statement, conditional term expressed or implied, statutory or otherwise, or in negligence or alleged negligence on the part of the company or otherwise. In no circumstances shall the company be liable for loss or damage in excess of the contract sale price.

7. PASSING OF PROPERTY

Each of the following sub-clauses 7.1 to 7.6 are separate and severable and shall be enforceable accordingly:

7.1 Notwithstanding delivery, all goods supplied by us will remain our absolute property until you pay in full for them and for all other goods previously supplied by us;

7.2 You will store the goods in such a way that they are readily identifiable as our property, but you may, as trustees for us, sell them to a third party in the normal course of your business;

7.3 Upon any sale by you of the goods (either alone or with other items) all rights which you have against the buyer shall automatically vest in us;

7.4 We shall be entitled immediately after giving notice of our intention to repossess, to enter upon any premises with such transport as may be necessary and repossess any goods to which we have title under this Clause;

7.5 If you incorporate the goods we supply to you into other products with or without materials you already possess or which are supplied to you by third parties the property in such other product will pass to us and you shall store them without charge on our behalf as bailee;

7.6 You shall not be entitled to pledge or in any way charge by way of security any of the goods which remain our property but in the event you do so all moneys owing by you to us shall without prejudice to any other right or remedy available to us forthwith become due and payable.

8. PAYMENT

For the purpose of this Clause the due date shall mean the due date specified on the face of the invoice. Customers electing to pay by Direct Debit shall mean the 28th of the month following the month of the invoice. If you do not comply punctually with these terms of payment we reserve the right to charge you interest on any amount overdue at the rate of 1½% per month from the due date to the date of receipt of the monies outstanding, and without notice to suspend further deliveries until all arrears (including interest) have been paid and, at our option, to rescind any subsisting contract with you as to all or any parts of future deliveries but without prejudice to any rights already accrued to us under such contracts. Where a settlement discount is shown on the face of the invoice the customer may deduct this from his payment provided that payment in full less this discount is made by the due date.

9. ADDITIONAL DELIVERIES

Where the company has been obliged to make an additional delivery of the goods to the premises specified in the contract due to the failure of the customer to accept the delivery of the goods, the company reserves the right to make a charge for such additional delivery, unless the company failed to meet a specified time and date of delivery agreed in writing by the company and the customer. Any proposed delivery date specified on this invoice or on a sales order does not constitute such agreement in writing.

10. INTERPRETATION

Any agreement between the company and the purchaser shall be subject to and governed by the domestic law of England.

ABOUT US

The logo for Owlett-Jaton, featuring the company name in a bold, white, sans-serif font inside a blue rounded rectangular border.

The No. 1 choice for Quality, Service, and Value

Owlett-Jaton is the UK and Ireland's leading wholesale supplier of fasteners, fixings, and associated products to the distributor and merchant trade. Offering in excess of 30,000 product lines, we are also the largest stockholder in the industry.

Operating from a purpose-built warehouse in Stone, Staffordshire, our comprehensive stock line-up is backed by large stocks and efficient operations.

Our product range is the most comprehensive within our industry sector, and we understand that an important part of our offering is good stock availability, at all times. Our commitment to stock ensures products are available, competitively priced, for next-day delivery throughout most of the UK mainland.

FREE, NEXT-DAY DELIVERY WITH LOW MINIMUM ORDER LEVELS ACROSS THE MAJORITY OF THE UK MAINLAND.

We are the name behind some of the UK's leading fastener and fixing brands, including JCP, JRP, Thunderbolt, Unifix, and Vortex. With a comprehensive stock range in depth, volume, and continuity of supply, as well as a stock buying power that is unique to the market, we are recognised for offering the complete wholesale solution.

With over 30,000 product lines under one roof, customers can order multiple items, in small quantities, all from one supplier. For customers, this improves efficiency, provides cost savings, and enhances customer service levels.

Delivering continually high service levels, we have an enviable reputation for high-quality products and unrivalled customer service.

We take our service levels seriously and pride ourselves on our high levels of reliability, and lasting customer partnerships. With a network of sales offices and Area Sales Managers (ASM's), supported by our merchandising teams, customers have access to experienced staff, whilst online ordering provides visibility to pricing, stock availability, and more.

Our commitment to customer service and quality products is demonstrated by our ISO 9001:2015 Quality Management system. We are also dedicated to operating in an environmentally sustainable manner, and we are the first wholesaler in our industry to be awarded ISO 14001:2015 Environmental Management certification.

Owlett-Jaton is a trading division of Hexstone Ltd.

www.owlett-jaton.com



Technical Office

Teddington

tel **020 8943 1800**

jcpenquiries@owlett-jaton.com

Sales Office

Stone

tel **01785 819819**

info@owlett-jaton.com

Sales Office

Dartford

tel **01322 277733**

dartford.sales@owlett-jaton.com

Sales Office

Elland

tel **01422 370121**

elland.sales@owlett-jaton.com

Sales Office

Milton Keynes

tel **01908 201600**

milton.keynes@owlett-jaton.com

Sales Office

Swindon

tel **01793 527829**

swindon.sales@owlett-jaton.com



[/jcpconstructionproducts](https://www.linkedin.com/company/jcpconstructionproducts)

Your Local Distributor



Head Office

Opal Way, Stone Business Park, Stone, Staffordshire ST15 0SW • Tel 01785 811300

Technical Helpline 020 8943 1800 • jcpenquiries@owlett-jaton.com